



	MULTI-SOCKET PLUG WITH SURGE PROTECTION ACAR-MINI-AGD	RFID PROXIMITY CARD FM11RF08-M1 13.56 MHz S50 Hikvision
		
	9.97 EUR 9.97 EUR	1.80 EUR 1.80 EUR
Standard	...	13.56 MHz S50
Rated voltage	230 V AC / 50 Hz	...
Compatibility	...	ISO/IEC 14443A
Total maximal current	10 A	...
Possibility of programming the serial number (ID)	...	—
Maximal total load	2300 W	...
Ability to write to internal memory	...	✓
Response time	< 25 ns	...
Serial Number overprint	...	—
Number of outlets	2 grounded outlets 10A/250V	...
Maximal voltage	250 V / 50 Hz	...
Protection level of surge suppressor	≤ 1.3 kV (L/N)	...
Main features	...	Range : ~ 10 cm ,
Nominal stroke current	2 kA (L/N) - (8/20μs)	...
Maximum stroke current	10 kA (L/N) - (8/20μs)	...
Electric shock protection system	Ground connectors (pins) connected with ground wire of AC mains	...
Housing	Plastic - non-flammable	...
Manufacturer / Brand	...	Hikvision
SAP Code	...	303700155
Dimensions	131 x 55 x 75 mm	86 x 54 x 0.9 mm
Weight	0.12 kg	0.006 kg
Guarantee	2 years	2 years