



	AHD, HD-CVI, HD-TVI CAMERA APTI-H50C21-36W 2Mpx / 5Mpx 3.6 mm	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP DVR IDS-7208HUHI-M1/S(C) 8 CHANNELS Hikvision
		
	310.04 SEK 310.04 SEK	4364.08 SEK 4364.08 SEK
Standard	AHD, HD-CVI, HD-TVI	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP
Sensor	1/3 " Progressive Scan CMOS	...
Matrix size	5 Mpx	...
Video inputs	...	8 pcs BNC - AHD / HD-CVI / HD-TVI / CVBS
Video outputs	...	1 pcs HDMI 4K 1 pcs VGA 1 pcs CVBS - BNC socket
Audio inputs	...	1 pcs CINCH, Coaxial audio - Audio from cameras
Audio outputs	...	1 pcs CINCH
Image compression method	...	H.265+ / H.265 / H.264+ / H.264
Resolution	<ul style="list-style-type: none"> • 2592 x 1944 - 5 Mpx @ AHD / HD-TVI @ 20 fps / 12.5 fps, • 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI @ 25, 30 fps, • 1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI @ 25, 30 fps 	...
Lens	3.6 mm	...
View angle	<ul style="list-style-type: none"> • 77 ° (manufacturer data) • 70 ° (our tests result) 	...
Range of IR illumination	30 m	...
IR illuminator power adjustment	Automatic	...
Video output	1 Vpp 75 Ω, AHD / HD-CVI / HD-TVI	...
Audio	—	...
OSD menu	✓	...
Power consumption	≤ 2.6 W	...
Housing	Compact - Aluminum	...
"Index of Protection"	IP67	...
Operation temp	-20 °C ... 60 °C	...

Image records resolutions	...	<ul style="list-style-type: none"> • HD-TVI : 8.3 Mpx 4K UHD - 3840 x 2160 , 5 Mpx - 2560 x 1944 , 3.7 Mpx - 2560 x 1440 , 3 Mpx - 1920 x 1536 , 1080p - 1920 x 1080 , 720p - 1280 x 720 , • AHD : 5 Mpx - 2560 x 1944 , 3.7 Mpx - 2560 x 1440 , 1080p - 1920 x 1080 , 720p - 1280 x 720 , • HD-CVI : 3.7 Mpx - 2560 x 1440 , 1080p - 1920 x 1080 , 720p - 1280 x 720 , • PAL : 960H - 960 x 576 , • IP : max. 8 Mpx - 3840 x 2160
Recording speed adjustment	...	8 Mpx IP @ 1 ... 25 fps 8 Mpx @ 1 ... 8 fps 5 Mpx @ 1 ... 12 fps 4 Mpx @ 1 ... 15 fps 3 Mpx @ 1 ... 18 fps 1080p @ 1 ... 25 fps 720p @ 1 ... 25 fps 960H @ 1 ... 25 fps for each channel
Operation modes	...	8 x HD-TVI / AHD / HD-CVI / CVBS / IP + 8 x IP
Recording modes	...	Manual, Sensor, Motion detection, Schedule
Supported hard drives	...	1 x 10 TB SATA
External storage devices backup	...	Backup to USB drive (pendrive, external drive)
Searching and playback the records	...	Records searching: timeline or file list. Playback: forward, fast, slow. Playback max. 8 cameras in the same time
Network interface	...	1 x RJ-45 - 10/100/1000 Base-TX
Bitrate	...	32 ... 10240 kbps
Network functions	...	Network Client Software and IE browser: live view, playback and backup of the records, partial configuration of the recorder parameters
Network protocols	...	TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP, HTTPS, ONVIF
Mobile phones support	...	Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application Hik-Connect • iOS: Free application Hik-Connect
Default IP address	...	DHCP or 192.168.1.64



Default admin user / password	...	admin / - The administrator password should be set at the first start
Web browser access ports	...	80
PC client access ports	...	554 RTSP, 8000
Mobile client access ports	...	8000
Port ONVIF	...	80
RTSP URL	...	<ul style="list-style-type: none"> • rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no01/ - Main stream • rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no02/ - Sub stream
Alarm inputs / outputs	...	—
PTZ control	...	<ul style="list-style-type: none"> • Control compatible with coax HD-TVI Hikvision • RS-485 - PELCO-D/P
Motion Detection	...	2.0
USB	...	<ul style="list-style-type: none"> • 1 x USB 2.0 • 1 x USB 3.0
Mouse support	...	✓
IR remote controller in the set	...	—
Main features	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • ICR - Movable InfraRed filter • DNR - Digital Noise Reduction • AGC - Automatic Gain Control • BLC - Back Light Compensation • Day/Night mode (color/b&w/auto) • Auto White Balance • Sharpness - sharper image outlines 	<ul style="list-style-type: none"> • DVR from the AcuSense series • Intelligent image analysis : crossing the line (tripwire), intrusion, Deep Learning technology • Smart motion detection (with recognizing people and vehicles) • Filtering of false alarms based on the recognition of persons and vehicles
Power supply	12 V DC / 220 mA	12 V DC / 2 A (power adapter included)
Color	White	Black
Weight	0.39 kg	1.25 kg
Dimensions	172 x 73 x 73 mm	315 x 250 x 45 mm
Supported languages	Polish, English, French, Spanish, Portuguese, Russian, Italian	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Greek, Spanish, Dutch, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian
Manufacturer / Brand	APTI	Hikvision
SAP Code	...	300227543
Guarantee	2 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00