





	<a href="#">SMART LIGHT SWITCH ATLO-WB1-TUYA Wi-Fi, Tuya Smart</a>	<a href="#">QUAD SMART LED LIGHTING CONTROLLER ATLO-SW4-TUYA Wi-Fi, Tuya Smart</a>	<a href="#">BLANK MODULE AD-LS/ZP-45X45 System 45</a>
			
	129.84 SEK 129.84 SEK	219.59 SEK 219.59 SEK	8.45 SEK 8.45 SEK
Material	...	...	Plastic
Application	Works with lighting - switching on/off	switching devices on/off	System 45
Number of channels	...	4	...
Rated voltage	100 ... 240 V AC, 50 / 60 Hz	...	...
Power supply	...	100 ... 240 V AC, 50 / 60 Hz	...
Maximal total load	...	4 x 150W W	...
Maximum power	300 W (for each output)	...	...
Total maximal current	...	4 x 2.5 A	...
Rated current	max. 10 A	...	...
Manufacturer / Brand	...	...	STASINSKI / JAVEL
Number of inputs	...	4	...
Number of buttons	1	...	...
Number of outputs	1	4	...
Connector type	screw terminals	screw terminals	...
Wireless	Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n	<ul style="list-style-type: none"> <li>• Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n</li> <li>• Bluetooth</li> </ul>	...
Radio communication range	...	< 100 m (open area)	...
Mobile phones support	<ul style="list-style-type: none"> <li>• The <a href="#">Tuya Smart</a> free application on Android</li> <li>• The <a href="#">Tuya Smart</a> free application on iOS</li> </ul>	<ul style="list-style-type: none"> <li>• The <a href="#">Tuya Smart</a> free application on Android</li> <li>• The <a href="#">Tuya Smart</a> free application on iOS</li> </ul>	...
Main features	<ul style="list-style-type: none"> <li>• Local control by physical button,</li> <li>• schedule,</li> <li>• timer,</li> <li>• Setting scenarios by different events,</li> <li>• remote access,</li> <li>• voice control,</li> <li>• LED indication</li> </ul>	<ul style="list-style-type: none"> <li>• Local control by physical button ,</li> <li>Tuya Smart :</li> <li>• schedule,</li> <li>• timer,</li> <li>• Setting scenarios by different events,</li> <li>• remote access,</li> <li>• voice control ,</li> </ul>	...
Housing	Plastic	Plastic	...
"Index of Protection"	...	IP20	...
Permissible relative humidity	≤ 80 %	...	...

Color	White	White	White
Operation temp	-20 °C ... 50 °C	-10 °C ... 40 °C	...
Weight	0.09 kg	0.03 kg	0.006 kg
Dimensions	87 x 86 x 41 mm	43 x 39 x 22 mm	45 x 45 x 16 mm
Guarantee	2 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00