



	<a href="#">WALL MOUNT UMA-50R100</a>	<a href="#">IP VANDALPROOF CAMERA DS-2CD1743G2-LIZU(2.8-12MM) Smart Hybrid Light - 3.7 Mpx Hikvision</a>
		
	26.23 EUR 26.23 EUR	309.86 EUR 309.86 EUR
Material	Steel galvanized	...
Standard	...	IP
Diameter	Ø 50 mm	...
Height	1030 mm	...
Tube thickness	2 mm	...
Mount	Mast base - 2 x Expansion plugs, Supports - 3 x Expansion plugs	...
Resolution	...	2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p 1280 x 720 - 720p
Sensor	...	1/3 " Progressive Scan CMOS
Main features	<ul style="list-style-type: none"> <li>• Bracket enables to mount to flat, sloping or horizontal surfaces</li> <li>• Easy and universal mounting system</li> <li>• It is perfect to mount antennas : WLAN, DVB-T</li> </ul>	...
Lens	...	2.8 ... 12 mm - Motozoom
View angle	...	97 ° ... 30 °
Range of IR illumination	...	30 m
White light LED illuminator range	...	30 m
RS-485 interface	...	—
Memory card slot	...	Micro SD card support up to 512GB
Image compression method	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs	...	—
Audio	...	<ul style="list-style-type: none"> <li>• Microphone built-in</li> <li>• Audio transmission via network</li> <li>• Noise and echo reduction</li> <li>• Compliance with the AAC standard</li> </ul>
Network interface	...	10/100 Base-T (RJ-45)
WEB Server	...	Built-in, Web Viewer
Max. number of on-line users	...	6
ONVIF	...	✓
Main stream frame rate	...	<ul style="list-style-type: none"> <li>• 20 fps @ 4 Mpx</li> <li>• 25 fps @ 1080p</li> </ul>

Mobile phones support	...	Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">Hik-Connect</a></li> <li>• iOS: Free application <a href="#">Hik-Connect</a></li> </ul>
Default IP address	...	192.168.1.64
Default admin user / password	...	admin / - The administrator password should be set at the first start
Web browser access ports	...	80
PC client access ports	...	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application
Mobile client access ports	...	8000
Port ONVIF	...	80
RTSP URL	...	<ul style="list-style-type: none"> <li>• Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ - with authorization</li> <li>• Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ - with authorization</li> </ul>
Main features	...	<ul style="list-style-type: none"> <li>• Smart Hybrid Light technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality</li> <li>• Motozoom lens</li> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• IP addresses filtering</li> <li>• Auto White Balance</li> <li>• BLC - configurable Back Light Compensation</li> <li>• ICR - Movable InfraRed filter</li> <li>• Smart motion detection (with recognizing people and vehicles)</li> <li>• Configurable Privacy Zones</li> <li>• Mirror - Mirror image</li> <li>• Sharpness - sharper image outlines</li> <li>• RESET button</li> </ul>
Power supply	...	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 800 mA</li> </ul>
Power consumption	...	<ul style="list-style-type: none"> <li>• ≤ 12 W @ PoE (802.3af/at)</li> <li>• ≤ 9.6 W @ 12 V DC</li> </ul>
Housing	...	Dome - Metal
Color	...	White
Mechanical protection class	...	IK08
"Index of Protection"	...	IP67
Operation temp	...	-30 °C ... 60 °C
Weight	4.75 kg	0.5 kg
Dimensions	...	Ø 120 x 90 mm
Supported languages	...	English, Ukrainian
Manufacturer / Brand	DELTA	Hikvision

SAP Code	...	311325240
Guarantee	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00