



	<a href="#">IP CAMERA DS-2CD2443G2-I(2MM) ACUSENSE - 4 Mpx Hikvision</a>	<a href="#">SERRATED TIN PZ-50/W</a>
		
	199.28 EUR 199.28 EUR	2.16 EUR 2.16 EUR
Material	...	Metal
Standard	TCP/IP	...
Mast diameter	...	max. 50 mm
U-bolt diameter	...	Ø 9 mm
Sensor	1/3 " Progressive Scan CMOS	...
Matrix size	4 Mpx	...
Main features	...	<ul style="list-style-type: none"> <li>• Welded</li> <li>• The whole galvanized</li> </ul>
Resolution	2688 x 1520 - 4 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p	...
Lens	2 mm	...
View angle	128 °	...
Range of IR illumination	10 m	...
Audio	<ul style="list-style-type: none"> <li>• Microphone built-in,</li> <li>• Speaker built-in,</li> <li>• Bi-directional audio streaming support</li> <li>• Compliance with the AAC standard,</li> <li>• Noise suppression and echo cancellation</li> </ul>	...
RS-485 interface	—	...
Alarm inputs / outputs	—	...
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
Main stream frame rate	25 fps @ 4 Mpx	...
ONVIF	✓	...
Network interface	10/100 Base-T (RJ-45)	...
Mobile phones support	Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">Hik-Connect</a></li> <li>• iOS: Free application <a href="#">Hik-Connect</a></li> </ul>	...
Default IP address	DHCP or 192.168.1.64	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Web browser access ports	80	...
PC client access ports	Port no.: 8000 or access by a cloud (P2P) iVMS-4200 application	...
Mobile client access ports	8000	...

Port ONVIF	80	...
RTSP URL	<ul style="list-style-type: none"> <li>• Main stream rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ - with authorization</li> <li>• Sub stream rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ - with authorization</li> </ul>	...
Memory card slot	Micro SD memory cards up to 512GB support (possible local recording)	...
Main features	<ul style="list-style-type: none"> <li>• Camera from AcuSense series</li> <li>• Built-in PIR detector, Range : 8 m / 90 °</li> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its</li> <li>• NAS - Network Attached Storage support</li> <li>• SVC (Scalable Video Coding) - technology enabling the transfer of several sub-streams of different quality within one stream</li> <li>• Anti-Flicker - The technology eliminates the tiring eyes flickering image effect</li> <li>• Image rotation and mirror</li> <li>• Built-in Infra-Red illuminator enables night monitoring</li> <li>• ICR - Movable InfraRed filter</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Sharpness - sharper image outlines</li> <li>• Smart motion detection (with recognizing people and vehicles)</li> <li>• Intelligent image analysis : intrusion, crossing the line (tripwire) - classification of people and vehicles, face detection</li> </ul>	...
Power supply	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 480 mA</li> </ul>	...
Power consumption	<ul style="list-style-type: none"> <li>• ≤ 6.8 W @ PoE,</li> <li>• ≤ 5.9 W @ 12 V DC</li> </ul>	...
Weight	0.22 kg (with stand)	...
Dimensions	76 x 135 x 82 mm (with stand)	...
Operation temp	-10 ... 40 °C	...
Supported languages	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Ukrainian, Hungarian, Italian	...
Manufacturer / Brand	Hikvision	DELTA
SAP Code	311316102	...
Guarantee	3 years	3 years