

	OVERVOLTAGE LIMITER AXON-ADSL	OVERVOLTAGE LIMITER AXON-AIR	OVERVOLTAGE LIMITER AXON-AIR/DIN	OVERVOLTAGE LIMITER AXON-AIR/PROF	OVERVOLTAGE LIMITER AXON-MULTINET-24 ETHERNET RACK	OVERVOLTAGE LIMITER AXON-MULTINET-4 ETHERNET	OVERVOLTAGE LIMITER AXON-MULTINET-8 ETHERNET	OVERVOLTAGE LIMITER AXON-PRO-IP-12POE+	OVERVOLTAGE LIMITER AXON-PRO-IP-4POE+	OVERVOLTAGE LIMITER AXON-PRO-IP-POE+	OVERVOLTAGE LIMITER AXON-VIDEO-IP	OVERVOLTAGE LIMITER AXON-VIDEO-IP-4POE	OVERVOLTAGE LIMITER AXON-VIDEO-IP-8	OVERVOLTAGE LIMITER IPP-1-20-HS.ETHERNET ATTE	OVERVOLTAGE LIMITER PTF-51-EXT/POE/MICRO EWIMAR	OVERVOLTAGE LIMITER PTF-61-ECO/POE	OVERVOLTAGE LIMITER PTF-64-ECO/POE EWIMAR	OVERVOLTAGE LIMITER AXON-POE.ETHERNET	OVERVOLTAGE LIMITER AXON-POE-MULTINET	OVERVOLTAGE LIMITER AXON-POE-MULTINET-12	OVERVOLTAGE LIMITER AXON-POE/PROF	OVERVOLTAGE LIMITER AXON-NET-PROTECTOR	OVERVOLTAGE LIMITER AXON-NET/PROF	VIDEO OVERVOLTAGE LIMITER OPV-32S RACK
																								
	13.73 EUR 13.73 EUR	26.51 EUR 26.51 EUR	60.28 EUR 60.28 EUR	44.14 EUR 44.14 EUR	363.47 EUR 363.47 EUR	91.33 EUR 91.33 EUR	149.82 EUR 149.82 EUR	229.91 EUR 229.91 EUR	104.12 EUR 104.12 EUR	46.26 EUR 46.26 EUR	25.62 EUR 25.62 EUR	91.84 EUR 91.84 EUR	149.82 EUR 149.82 EUR	14.75 EUR 14.75 EUR	31.65 EUR 31.65 EUR	38.28 EUR 38.28 EUR	122.44 EUR 122.44 EUR	27.39 EUR 27.39 EUR	91.84 EUR 91.84 EUR	202.63 EUR 202.63 EUR	41.58 EUR 41.58 EUR	25.62 EUR 25.62 EUR	39.80 EUR 39.80 EUR	220.38 EUR 220.38 EUR
Protection level	...	1000 V	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Transmission speed	...	...	...	...	...	10 / 100 / 1000 Mbps	...	10 / 100 / 1000 Mbps	...	...	...	10 / 100 Mbps	...	...	...	...	...	...	...	...	...	...	...	...
Nominal voltage (line-ground)	...	...	...	...	...	...	...	...	...	...	...	...	...	...	90 V DC	90 V	90 V	...	...	...	...	...	...	...
Nominal stroke current	...	2.5 kA (8/20µs)	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Protection level of surge suppressor	≤ 600 V	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Maximal voltage line-PG	...	...	...	...	...	...	...	...	...	...	...	...	...	...	110 V DC	110 V	110 V	...	...	...	...	...	...	...
Rated voltage	...	5 V	120 V	120 V	20 V	5 V	20 V	120 V	120 V	120 V	5 V	5 V	5 V	...	...	...	...	5 V	5 V	5 V	5 V	5 V	5 V	...
Maximal voltage	...	60 V	150 V	150 V	25 V	6 V	25 V	150 V	150 V	150 V	6 V	6 V	6 V	...	...	...	...	6 V	6 V	6 V	6 V	6 V	6 V	...
Voltage protection level line-PG (C2)	...	...	≤ 1000 V - 1.2/50 µs	...	...	...	...	...	≤ 1000 V - 1.2/50 µs	≤ 1000 V - 1.2/50 µs	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Voltage protection level (line-line)	...	...	...	...	40 V	≤ 40 V - 1 kV/µs (C3)	≤ 40 V	...	...	...	≤ 40 V	...	...	8 V	...	...	...	40 V	...	...	...	...	...	...
Voltage protection level line-line	...	...	...	...	...	...	...	...	...	...	...	≤ 40 V - 1 kV/µs (C3)	≤ 40 V - 1 kV/µs (C3)	...	...	...	...	...	40 V - 1 kV/µs	≤ 40 V - 1 kV/µs	≤ 40 V - 1 kV/µs	40 V ... 1 kV/µs	40 V ... 1 kV/µs	...
Nominal discharge current line-PG (C2)	...	...	2 kA - 8/20 µs	...	...	...	...	...	2 kA - 8/20 µs	2 kA - 8/20 µs	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Maximal discharge current (line-line)	...	...	...	...	135 A (8/20µs)	...	135 A (8/20µs)	...	...	...	135 A (8/20µs)	...	...	30 A	...	...	...	135 A (8/20µs)	...	...	...	...	...	...
Maximal discharge current (line-PG)	10 kA (8/20µs)	...	...	...	135 A (8/20µs)	...	135 A (8/20µs)	...	...	...	135 A (8/20µs)	...	...	30 A	...	...	...	135 A (8/20µs)	...	...	...	...	...	...
Standard	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	• AHD - 5 Mpx, • HD-CVI - 8 Mpx 4K UHD, • HD-TVI - 5 Mpx, • CVBS - PAL / NTSC
Nominal discharge current (line-line)	...	...	...	...	100 A (8/20µs)	20 A - 10/1000 µs (C3)	100 A (8/20µs)	...	...	...	100 A (8/20µs)	20 A - 10/1000 µs (C3)	20 A (10/1000µs) (C3)	...	...	...	...	100 A (8/20µs)	20 A (10/1000µs)	20 A (10/1000µs)	20 A (10/1000µs)	20 A (10/1000µs)	20 A (10/1000µs)	...
Threshold voltage (wire-wire)	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	> 2.4 V
Color	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	White	...	...
Length of the cable	...	...	...	...	...	...	...	...	...	0.23 m STP	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Threshold voltage (wire / ground)	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	> 18.4 V
Nominal current	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Maximum stroke current	...	5 kA (8/20µs)	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	5 kA (8/20µs)
Nominal voltage (line-line)	120 V	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Nominal discharge current (line-PG)	5 kA (8/20µs)	...	...	2 kA (8/20µs)	100 A (8/20µs)	20 A - 10/1000 µs (C3)	100 A (8/20µs)	2 kA - 8/20 µs (C2)	...	...	100 A (8/20µs)	20 A - 10/1000 µs (C3)	20 A (10/1000µs) (C3)	...	100 A - 8/20 µs	100 A - 8/20 µs	100 A - 8/20 µs	100 A (8/20µs)	20 A (10/1000µs)	20 A (10/1000µs)	20 A (10/1000µs)	20 A (10/1000µs)	20 A (10/1000µs)	...
Serial impedance per line	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	1 Ω
Nominal power voltage	...	...	...	...	...	...	...	...	...	...	...	...	...	...	50 V	...	...	...	...	...	...	...	...	...
Capacity	≤ 10 pF	...	...	...	20 pF	...	≤ 20 pF	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	≤ 7 pF
Voltage protection level for power (line-line)	...	...	...	...	...	...	...	...	...	...	...	...	...	65 V PoE	...	...	...	...	...	...	...	...	...	...
Voltage protection level line-PG	...	...	...	...	1000 V (1.2/50µs)	600 V	≤ 600 V - 1 kV/µs (C3)	≤ 600 V	≤ 1000 V - 1.2/50 µs (C2)	...	...	≤ 600 V	≤ 600 V - 1 kV/µs (C3)	≤ 600 V - 1 kV/µs (C3)	400 V	≤ 600 V	≤ 600 V	≤ 600 V	600 V 1 kV	600 V - 1 kV/µs	≤ 600 V - 1 kV/µs	≤ 600 V - 1 kV/µs	600 V ... 1 kV/µs	600 V ... 1 kV/µs
Maximal power voltage	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Reaction time	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	15 ns
Protected wires	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Nominal current	...	...	...	...	...	...	...	600 mA	600 mA	600 mA	...	...	...	...	...	...	...	...	400 mA	400 mA	400 mA	...	...	...
Grounding	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	5mm screw
Nominal discharge current for power (line-line)	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	80 A (8/20µs)	...	...	...	...	...
Maximal voltage (line-line)	150 V	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
RJ-45 connector protected wires	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	1, 2, 3, 4, 5, 6, 7, 8
Maximal discharge current for power (line-PG)	...	...	...	...	...	...	...																	

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Dimensions	66 x 60 x 30 mm	66 x 60 x 30 mm	86 x 58 x 35 mm	95 x 50 x 30 mm	490 x 85 x 44 mm	162 x 52 x 32 mm	162 x 90 x 37 mm	490 x 50 x 44 mm, RACK 19", 1U	167 x 50 x 32 mm	50 x 40 x 30 mm	66 x 60 x 30 mm	167 x 50 x 32 mm	162 x 90 x 37 mm	20 x 48 x 17 mm	57 x 31 x 27 mm	64 x 40 x 30 mm	99 x 81 x 20 mm	67 x 61 x 30 mm	167 x 50 x 32 mm	1 U Rack 19" 488 x 44 x 50 mm	95 x 50 x 30 mm	67 x 60 x 29 mm	94 x 50 x 31 mm	...
Length of grounding cable	...	...	...	0.5 m	...	52 cm	...	50 cm	0.52 m	0.29 m	...	55 cm	0.5 m	...	0.29 m	0.275 m	...	...	...	...	...	...	...	...
Guarantee	2 years	2 years	2 years	2 years	2 years	3 years	2 years	3 years	2 years	2 years	2 years	2 years	3 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	3 years