

	VIDEO SEPARATOR WITH OPTO-ISOLATION SV-1000A STANDARD: AHD, HD-CVI	REPEATER VHD-15 AHD, HD-CVI, HD-TVI SIGNAL AMPLIFIER DELTA	CONVERTER HV/HDMI+HV-V2	POWER SEPARATOR PFM790 DAHUA	VIDEO SEPARATOR AHD, HD-CVI, HD-TVI, PAL PFM791 DAHUA
					
	37.47 EUR 37.47 EUR	38.32 EUR 38.32 EUR	82.24 EUR 82.24 EUR	18.89 EUR 18.89 EUR	18.41 EUR 18.41 EUR
Input voltage	...	...	...	12 V DC $\pm$ 20 %	...
Output voltage	...	...	...	12 V DC $\pm$ 5 %	...
Input	...	...	1 x BNC - AHD / HD-CVI / HD-TVI / CVBS @ 8 Mpx (max)	...	...
Output current	...	...	...	max. 400 mA	...
Input socket type	...	...	...	2.1/5.5 mm socket	...
Output socket type	...	...	...	2.1/5.5 mm plug	...
Input impedance	75 Ω	...	...	...	75 Ω
Galvanic (optical) isolation between signal inputs and outputs	1000 V peak	...	...	...	...
Output impedance	75 Ω	...	...	...	75 Ω
Opto-isolation between power and signal inputs / outputs	1000 V peak	...	...	...	...
Efficiency	...	...	...	85 % @ 400 mA	...
Opto-isolation between input and output	...	...	...	...	800 V - peak
Gain adjustment	-3 dB ... +3 dB	...	...	...	...
Insertion loss	...	...	...	...	0.5 dB
Standard	- AHD - 4 Mpx - HD-CVI - 720p - CVBS - PAL / NTSC	- AHD - 5 Mpx, 12 fps, - HD-CVI - 1080p, 25 fps, - HD-TVI - 5 Mpx, 12 fps, - CVBS - PAL / NTSC	...	...	AHD, HD-CVI, HD-TVI, PAL
Device type	...	Active	...	...	Passive
Bandwidth	33 MHz / 1 Vpp	...	...	...	0 ... 65 MHz
Output	...	...	1 x BNC - AHD / HD-CVI / HD-TVI / CVBS @ 8.3 Mpx (max), 1 x HDMI @ 1080p 60 fps	...	...
Output signal possible standards	...	...	PAL / NTSC	...	...
Supported resolutions	...	...	- HDMI - 1080p - BNC - 8.3 Mpx (max)	...	...
OSD menu	...	...	—	...	...
The ability of signal regeneration	...	150 m - Twisted-pair cable , 300 m - RG59 , 500 m - Triset113	...	...	...
ESD protection	...	...	...	...	600 V (contact discharge) 8000 V (air-gap discharge)
Housing type	...	...	...	...	ABS
Current consumption	...	< 50 mA	...	90 mA	...
Main features	...	...	- In the case of no input signal, the device displays a test chart (color bars) on the connected screen - Automatic recognition of the resolution - LED indication - USB cable 0.9 m (included) - BNC cable 0.9 m (included)	...	- Overvoltage protection : 4 kV 10/700 μs - Compliance with IEC61000-4-2, IEC61000-4-5 standards - MTBF (Mean Time Between Faults) > 20000 h - Length of the cables 2 x 13 cm

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Coaxial socket impedance	...	75 Ω	...	...	...
Operation temp	...	...	...	-30 °C ... 60 °C	-20 °C ... 55 °C
Symmetrical socket impedance	...	100 Ω	...	...	...
Power supply	12 V DC / 90 mA	• 8 V ... 24 V DC (power adapter not included) • The possibility of remote powering through the unused pairs of twisted-pair cable	5 V DC / 2 A (power adapter included)	...	—
Number of inputs	1 pcs BNC	1	...	1	1 - BNC socket
Permissible relative humidity	...	...	...	...	0 % ... 95 %
Number of outputs	1 pcs BNC	1	...	1	1 - BNC plug
Coaxial socket type	...	BNC socket	...	...	...
Symmetrical socket type	...	terminals	...	...	...
Weight	0.088 kg	0.080 kg	0.18 kg	0.032 kg	0.034 kg
Dimensions	120 x 62 x 30 mm	103 x 62 x 29 mm	108 x 95 x 25 mm	108 x 22 x 20 mm	42 x 23 x 16 mm
Manufacturer / Brand	DELTA	DELTA	...	DAHUA	DAHUA
Guarantee	3 years	3 years	2 years	3 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00