	AHD, HD-CVI, HD-TVI CAMERA APTI-H50C2-36W 2Mpx / 5Mpx 3.6 mm	AHD, HD-CVI, HD-TVI CAMERA APTI-H50C21-28W 2Mpx / 5Mpx 2.8 mm	AHD, HD-CVI, HD-TVI CAMERA APTI-H50C21-36W 2Mpx / 5Mpx 3.6 mm	AHD, HD-CVI, HD-TVI CAMERA APTI-H50PC2-28W 2Mpx / 5Mpx 2.8 mm	AHD, HD-CVI, HD-TVI CAMERA APTI-H50PC21-28W 2Mpx / 5Mpx 2.8 mm	AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-B1A21-0360B - 1080p 3.6 mm DAHUA	AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-B2A21-0360B - 1080p 3.6 mm DAHUA	AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HFW1200C-0280B-S6 - 1080p 2.8 mm DAHUA	AHD, HD-CVI, HD-TVI, CVBS CAMERA HAC-HFW1200CT-IL-A-0360B-S6 - 1080p 3.6 mm DAHUA	AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HFW1200CM-IL-A-0360B-S6 - 1080p 3.6 mm DAHUA	AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HFW1200TH-IL-A-0280B-S6 - 1080p 2.8 mm DAHUA	AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HFW1200TH-IL-A-0360B-S6 - 1080p 3.6 mm DAHUA	AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HFW1200TLM-IL-A-0360B-S6 - 1080p 3.6 mm DAHUA	AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HFW1200TL-A-0360B-S5 - 1080p 3.6 mm DAHUA	AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HFW1200TLM-IL-A-0360B-S6 - 1080p 3.6 mm DAHUA	AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HFW1200TL-A-0360B-S6 - 1080p 3.6 mm DAHUA	AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HFW1200TLM-IL-A-0360B-S6 - 1080p 3.6 mm DAHUA	AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HFW1231TLM-IL-A-0360B - 1080p 3.6 mm DAHUA	AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HFW1231TM-IL-A-0360B - 1080p 3.6 mm DAHUA	AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HFW2241TL-A-0360B-S2-DIP - 1080p 3.6 mm DAHUA	AHD, HD-CVI, HD-TVI, PAL CAMERA DS-2CE16D0T-IRF(2.8mm)(C) - 1080p Hikvision	AHD, HD-CVI, HD-TVI, PAL CAMERA DS-2CE16D0T-IRPF(2.8MM)(C) - 1080p Hikvision	AHD, HD-CVI, HD-TVI, PAL CAMERA DS-2CE16D8T-IT3F(2.8mm) - 1080p Hikvision	AHD, HD-CVI, HD-TVI, PAL CAMERA DS-2CE16D8T-ITF(2.8mm) - 1080p Hikvision	AHD, HD-CVI, HD-TVI, PAL CAMERA DS-2CE17D0T-IT3F(2.8mm) - 1080p Hikvision
																							
	36.34 EUR 36.34 EUR	28.31 EUR 28.31 EUR	27.16 EUR 27.16 EUR	26.39 EUR 26.39 EUR	24.86 EUR 24.86 EUR	42.08 EUR 42.08 EUR	51.88 EUR 51.88 EUR	45.42 EUR 45.42 EUR	60.96 EUR 60.96 EUR	74.83 EUR 74.83 EUR	57.38 EUR 57.38 EUR	74.11 EUR 74.11 EUR	57.14 EUR 57.14 EUR	71.24 EUR 71.24 EUR	74.83 EUR 74.83 EUR	86.54 EUR 86.54 EUR	103.28 EUR 103.28 EUR	150.37 EUR 150.37 EUR	52.59 EUR 52.59 EUR	49.01 EUR 49.01 EUR	92.52 EUR 92.52 EUR	77.22 EUR 77.22 EUR	64.55 EUR 64.55 EUR
Standard	AHD, HD-CVI, HD-TVI	AHD, HD-CVI, HD-TVI	AHD, HD-CVI, HD-TVI	AHD, HD-CVI, HD-TVI	AHD, HD-CVI, HD-TVI	AHD, HD-CVI, HD-TVI, PAL	AHD, HD-CVI, HD-TVI, PAL	AHD, HD-CVI, HD-TVI, CVBS	AHD, HD-CVI, HD-TVI, CVBS	AHD, HD-CVI, HD-TVI, CVBS	AHD, HD-CVI, HD-TVI, PAL	AHD, HD-CVI, HD-TVI, CVBS	AHD, HD-CVI, HD-TVI, CVBS	AHD, HD-CVI, HD-TVI, CVBS	AHD, HD-CVI, HD-TVI, CVBS	AHD, HD-CVI, HD-TVI, CVBS	AHD, HD-CVI, HD-TVI, CVBS	AHD, HD-CVI, HD-TVI, PAL	AHD / HD-CVI / HD-TVI / PAL	AHD / HD-CVI / HD-TVI / PAL	AHD / HD-CVI / HD-TVI / PAL	AHD, HD-CVI, HD-TVI, PAL	AHD / HD-CVI / HD-TVI / CVBS
Matrix size	5 Mpx	5 Mpx	5 Mpx	5 Mpx	5 Mpx	2.1 Mpx	2.1 Mpx	2.1 Mpx	2.1 Mpx	2.1 Mpx	2.1 Mpx	2.1 Mpx	2.1 Mpx	2.1 Mpx	2.1 Mpx	2.1 Mpx	2.1 Mpx	2.1 Mpx	2.1 Mpx	2.1 Mpx	2.1 Mpx	2.1 Mpx	2.1 Mpx
Sensor	1/2.7 " Progressive Scan CMOS	1/3 " Progressive Scan CMOS	1/3 " Progressive Scan CMOS	1/2.7 " Progressive Scan CMOS	1/3 " Progressive Scan CMOS	1/2.7 " Progressive Scan CMOS	1/2.7 " Progressive Scan CMOS	Progressive Scan CMOS	Progressive Scan CMOS	Progressive Scan CMOS	Progressive Scan CMOS	Progressive Scan CMOS	1/2.7 " CMOS	1/2.7 " CMOS	Progressive Scan CMOS	1/2.8 " CMOS	1/2.8 " CMOS	" Progressive Scan CMOS	Progressive Scan CMOS	Progressive Scan CMOS	Progressive Scan CMOS	Progressive Scan CMOS	Progressive Scan CMOS
White light LED illuminator range	...	...	...	...	...	...	...	...	20 m	20 m	...	...	...	...	40 m	...	...	...	...	...	...	...	...
Resolution	• 2592 x 1944 - 5 Mpx @ AHD / HD-TVI @ 20 fps / 12.5 fps, • 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI @ 25 fps • 1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI @ 25 fps	• 2592 x 1944 - 5 Mpx @ AHD / HD-TVI @ 20 fps / 12.5 fps, • 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI @ 25, 30 fps, • 1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI @ 25, 30 fps	• 2592 x 1944 - 5 Mpx @ AHD / HD-TVI @ 20 fps / 12.5 fps, • 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI @ 25, 30 fps, • 1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI @ 25, 30 fps	• 2592 x 1944 - 5 Mpx @ AHD / HD-TVI @ 20 fps / 12.5 fps ; • 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI @ 25 fps, • 1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI @ 25 fps	• 2592 x 1944 - 5 Mpx @ AHD / HD-TVI @ 20 fps / 12.5 fps ; • 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI @ 25 fps, • 1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI @ 25 fps	1920 x 1080 - 1080p 1280 x 720 - 720p 960 x 576 - 960H, PAL	1920 x 1080 - 1080p 1280 x 720 - 720p 960 x 576 - 960H, PAL	1920 x 1080 - 1080p 1280 x 720 - 720p 960 x 576 - 960H	• 1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI @ 25 fps, • 960 x 576 - 960H @ PAL	1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI @ 25 fps , 960 x 576 - 960H @ PAL @ 25 fps	1920 x 1080 - 1080p 1280 x 720 - 720p 960 x 576 - 960H	1920 x 1080 - 1080p , 960 x 576 - 960H	1920 x 1080 - 1080p 1280 x 720 - 720p 960 x 576 - 960H	1920 x 1080 - 1080p 1280 x 720 - 720p 960 x 576 - 960H	1920 x 1080 - 1080p @ HD-CVI / HD-TVI / AHD @ 25 fps , 960 x 576 - 960H @ PAL @ 25 fps	1920 x 1080 - 1080p 960 x 576 - 960H	1920 x 1080 - 1080p 960 x 576 - 960H, PAL	1920 x 1080 - 1080p , 960 x 576 - 960H, PAL	1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI 960 x 576 @ PAL	1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI 960 x 576 @ PAL	1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI 960 x 576 - 960H @ PAL	1920 x 1080 - 1080p	1920 x 1080 - 1080p 960 x 576 - 960H, PAL
Lens	3.6 mm	2.8 mm	3.6 mm	2.8 mm	2.8 mm	3.6 mm	3.6 mm	2.8 mm	3.6 mm	3.6 mm	2.8 mm	3.6 mm	3.6 mm	3.6 mm	3.6 mm	3.6 mm	3.6 mm	3.6 mm	2.8 mm	2.8 mm	2.8 mm	2.8 mm	2.8 mm
S/N ratio	...	...	...	...	...	> 65 dB	...	> 65 dB	...	...	...	> 65 dB	> 65 dB	> 65 dB	...	> 65 dB	> 65 dB	> 65 dB	...	...	...	...	...
View angle	• 83 ° (manufacturer data) • 71 ° (our tests result)	• 95 ° (manufacturer data) • 86 ° (our tests result)	• 77 ° (manufacturer data) • 70 ° (our tests result)	• 95 ° (manufacturer data) • 103 ° (our tests result)	• 95 ° (manufacturer data) • 83 ° (our tests result)	• 93 ° (manufacturer data) • 90 ° (our tests result)	• 93 ° (manufacturer data) • 90 ° (our tests result)	102 °	• 83 ° (manufacturer data) • 82 ° (our tests result)	• 83 ° (manufacturer data) • 83 ° (our tests result)	• 101 ° (manufacturer data) • 104 ° (our tests result)	83 °	• 88 ° (manufacturer data) • 83 ° (our tests result)	• 88 ° (manufacturer data) • 86 ° (our tests result)	• 83 ° (manufacturer data) • 84 ° (our tests result)	• 86 ° (manufacturer data) • 81 ° (our tests result)	• 86 ° (manufacturer data) • 82 ° (our tests result)	• 86 ° (manufacturer data) • 83 ° (our tests result)	• 106 ° (manufacturer data) • 100 ° (our tests result)	• 106 ° (manufacturer data) • 101 ° (our tests result)	• 104 ° (manufacturer data) • 100 ° (our tests result)	• 104 ° (manufacturer data) • 97 ° (our tests result)	• 106 ° (manufacturer data) • 101 ° (our tests result)
Range of IR illumination	25 m	30 m	30 m	20 m	20 m	20 m	20 m	30 m	20 m	30 m	30 m	80 m	40 m	80 m	40 m	60 m	80 m	60 m	25 m	20 m	60 m	30 m	60 m
IR illuminator power adjustment	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic	...	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic
Mechanical protection class	...	...	...	...	...	...	...	—	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Video output	1 Vpp 75 Ω, AHD / HD-CVI / HD-TVI - selectable by switch	1 Vpp 75 Ω, AHD / HD-CVI / HD-TVI - selectable by switch	1 Vpp 75 Ω, AHD / HD-CVI / HD-TVI	1 Vpp 75 Ω, AHD / HD-CVI / HD-TVI - selectable by switch	1 Vpp 75 Ω, AHD / HD-CVI / HD-TVI - selectable by switch	AHD / HD-CVI / HD-TVI / PAL, 1 Vpp / 75 Ω	AHD / HD-CVI / HD-TVI / PAL, 1 Vpp / 75 Ω	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	AHD / HD-CVI / HD-TVI / PAL, 1 Vpp / 75 Ω	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	—	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	AHD / HD-CVI / HD-TVI / PAL - 1 Vpp / 75 Ω	1 Vpp / 75 Ω - AHD / HD-CVI / HD-TVI / PAL, BNC socket	1 Vpp / 75 Ω - AHD / HD-CVI / HD-TVI / PAL, BNC socket	1 Vpp / 75 Ω - AHD / HD-CVI / HD-TVI / PAL, BNC socket	1 Vpp / 75 Ω - AHD / HD-CVI / HD-TVI / CVBS, BNC socket
Audio	...	—	—	...	...	...	...	—	• Microphone built-in, • Audio support via coaxial cable - HD-CVI only	• Microphone built-in, • Audio support via coaxial cable - HD-CVI only	...	• Microphone built-in • Audio support via coaxial cable - HD-CVI only	—	Microphone built-in, HD-CVI only	• Microphone built-in, • Audio support via coaxial cable - HD-CVI only	Microphone built-in, HD-CVI only	Microphone built-in, HD-CVI only	Microphone built-in - Audio support via coaxial cable - HD-CVI only	...	...			
OSD menu	✔	✔	✔	✔	✔	OSD menu available via DAHUA recorder	OSD menu available via DAHUA recorder	✔	OSD menu available via DAHUA recorder	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	OSD menu available via Hikvision HD-TVI recorder	OSD menu available via Hikvision HD-TVI recorder	OSD menu available via Hikvision HD-TVI recorder
Main features	• D-WDR - Wide Dynamic Range • DNR - Digital Noise Reduction • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • BLC - Back Light Compensation • Day/Night mode (color/b&w/auto) • Auto White Balance • Sharpness - sharper image outlines	• D-WDR - Wide Dynamic Range • ICR - Movable InfraRed filter • DNR - Digital Noise Reduction • AGC - Automatic Gain Control • BLC - Back Light Compensation • Day/Night mode (color/b&w/auto) • Auto White Balance • Sharpness - sharper image outlines	• D-WDR - Wide Dynamic Range • ICR - Movable InfraRed filter • DNR - Digital Noise Reduction • AGC - Automatic Gain Control • BLC - Back Light Compensation • Day/Night mode (color/b&w/auto) • Auto White Balance • Sharpness - sharper image outlines	• D-WDR - Wide Dynamic Range • DNR - Digital Noise Reduction • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • BLC - Back Light Compensation • Day/Night mode (color/b&w/auto) • Auto White Balance • Sharpness - sharper image outlines	• D-WDR - Wide Dynamic Range • DNR - Digital Noise Reduction • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • BLC - Back Light Compensation • Day/Night mode (color/b&w/auto) • Auto White Balance • Sharpness - sharper image outlines	• D-WDR - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • Anti-Flicker - The technology eliminates the tiring eyes flickering image effect • ICR - Movable InfraRed filter • Mirror - Mirror image • Sharpness - sharper image outlines • AGC - Automatic Gain Control • Privacy zones • Auto White Balance	• D-WDR - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Privacy zones • Auto White Balance	• D-WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ICR - Movable InfraRed filter • Privacy zones	• Smart Dual Illumination technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality • D-WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Privacy zones - max. 8 • Mirror - Mirror image • Auto White Balance • Sharpness - sharper image outlines	• Smart Dual Illumination technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality • D-WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Privacy zones - max. 8 • Motion Detection • Auto White Balance	• D-WDR - Wide Dynamic Range • 2D-DNR (Defog) - Reduction of image noise caused by precipitation • BLC/HLC - Back Light / High Light Compensation • Day/night mode • ICR - Movable InfraRed filter • Auto White Balance • AGC - Automatic Gain Control • Mirror - Mirror image • Privacy zones - max. 8 • Sharpness - sharper image outlines	• D-WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • AGC - Automatic Gain Control • Auto White Balance • F-DNR (Defog) - Reduction of image noise caused by precipitation • Mirror - Mirror image • Privacy zones - max. 8 • Sharpness - sharper image outlines	• D-WDR - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Privacy zones • Auto White Balance	• D-WDR - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Privacy zones • Auto White Balance	• Smart Dual Illumination technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality • D-WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Privacy zones - max. 8 • Mirror - Mirror image • Auto White Balance • Sharpness - sharper image outlines	• WDR - 130 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Auto White Balance • Privacy zones - max. 8 • Mirror - Mirror image • Sharpness - sharper image outlines	• WDR - 130 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Auto White Balance • Privacy zones - max. 8 • Mirror - Mirror image • Sharpness - sharper image outlines	• WDR - 130 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Auto White Balance • Day/night mode • Sharpness - sharper image outlines	• D-WDR - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • IR illuminator optimization • Day/night mode • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Auto White Balance • Sharpness - sharper image outlines	• D-WDR - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • IR illuminator optimization • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Auto White Balance • Motion Detection - max. 4 zones • Privacy zones - max. 4 • Mirror - Mirror image • Sharpness - sharper image outlines	• WDR ≥ 130 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners • ICR - Movable InfraRed filter • BLC - Back Light Compensation • AGC - Automatic Gain Control • Auto White Balance • Motion Detection - max. 4 zones • Privacy zones - max. 4 • Mirror - Mirror image • Sharpness - sharper image outlines	• WDR - 130 dB - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • Day/night mode • ICR - Movable InfraRed filter • Mirror - Mirror image • AGC - Automatic Gain Control • Auto White Balance • Sharpness - sharper image outlines	• D-WDR - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • Day/night mode • ICR - Movable InfraRed filter • Mirror - Mirror image • AGC - Automatic Gain Control • Auto White Balance • Sharpness - sharper image outlines
Power supply	12 V DC / 400 mA	12 V DC / 220 mA	12 V DC / 220 mA	12 V DC / 300 mA	12 V DC / 220 mA	12 V DC / 220 mA	12 V DC / 220 mA	12 V DC / 235 mA	12 V DC / 220 mA	12 V DC / 220 mA	12 V DC / 275 mA	12 V DC / 410 mA	12 V DC / 250 mA	12 V DC / 440 mA	12 V DC / 340 mA	12 V DC / 430 mA	12 V DC / 430 mA	12 V DC / 640 mA	12 V DC / 250 mA	12 V DC / 180 mA	12 V DC / 280 mA	12 V DC / 280 mA	12 V DC / 330 mA
Power consumption	≤ 4.8 W	≤ 2.6 W	≤ 2.6 W	≤ 3.6 W	≤ 2.6 W	≤ 2.7 W	≤ 2.7 W	≤ 2.8 W	≤ 2.6 W	≤ 2.6 W	≤ 3.3 W	≤ 4.9 W	≤ 3 W	≤ 5.3 W	≤ 4.1 W	≤ 5.1 W	≤ 5.1 W	≤ 7.7 W	≤ 3.9 W	≤ 2.2 W	≤ 3.4 W	≤ 3.4 W	≤ 3.9 W
Housing	Compact - Aluminum	Compact - Aluminum	Compact - Aluminum	Compact - Plastic	Compact - Plastic	Compact, Plastic	Compact, Aluminum	Compact, Plastic	Compact, Plastic	Compact - Metal	Compact, Metal	Compact, Plastic + Metal	Compact, Plastic	Compact, Plastic / Metal	Compact Plastic + Metal	Compact, Plastic + Metal	Compact, Metal	Compact, Aluminum	Compact, Metal	Compact, Plastic	Compact, Metal	Compact, Metal	Compact - Metal + Plastic
Vandal-proof	...	...	...	...	...	...	...	...	—	—	...	...	...	...	—	...	...	...	...	...	...	...	...
Color	White	White	White	White + Black	White	White	White	White / Black	White + Black	White	White	White + Black	White	White	White	White	White	White	White	White	White + Black	White + Black	White + Black
"Index of Protection"	IP66	IP67	IP67	IP66	IP66	IP67	IP67	IP67	IP67	IP67	IP67	IP67	IP67	IP67	IP67	IP67	IP67	IP67	IP67	IP67	IP67	IP67	IP67
SAP Code	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	300511939	300511945	300511195	300511199	300512834
Operation temp	-10 °C ... 60 °C	-20 °C ... 60 °C	-20 °C ... 60 °C	-20 °C ... 60 °C	-20 °C ... 60 °C	-40 °C ... 60 °C	-40 °C ... 60 °C	-40 °C ... 60 °C	-40 °C ... 60 °C	-40 °C ... 60 °C	-40 °C ... 60 °C	-40 °C ... 60 °C	-40 °C ... 60 °C	-40 °C ... 60 °C	-40 °C ... 60 °C	-40 °C ... 60 °C	-40 °C ... 60 °C	-40 °C ... 60 °C	-40 °C ... 60 °C	-40 °C ... 60 °C	-40 °C ... 60 °C	-40 °C ... 60 °C	-40 °C ... 60 °C
Weight	0.3 kg	0.39 kg	0.39 kg	0.16 kg	0.19 kg	0.14 kg	0.25 kg	0.17 kg	0.18 kg	0.33 kg	0.34 kg	0.41 kg	0.22 kg	0.28 kg	0.3 kg	0.29 kg	0.65 kg	0.73 kg	0.26 kg	0.15 kg	0.56 kg	0.34 kg	0.33 kg
Dimensions	157 x 66 x 68 mm	172 x 73 x 73 mm	172 x 73 x 73 mm	162 x 70 x 70 mm	174 x 70 x 68 mm	149 x 70 x 70 mm	158 x 70 x 70 mm	161 x 70 x 70 mm	163 x 70 x 70 mm	167 x 70 x 70 mm	175 x 71 x 72 mm	91 x 90 x 241 mm	80 x 76 x 199 mm	80 x 75 x 199 mm	198 x 80 x 76 mm	198 x 80 x 76 mm	241 x 91 x 90 mm	245 x 90 x 90 mm	Ø 70 x 138 mm	Ø 70 x 138 mm	226 x 87 x 82 mm	Ø 70 x 163 mm	217 x 79 x 75 mm
Supported languages	English	Polish, English, French, Spanish, Portuguese, Russian, Italian	Polish, English, French, Spanish, Portuguese, Russian, Italian	Polish, English, French, Spanish, Portuguese, Russian, Italian	Polish, English	...	...	...	...	...	...	...	...	...	...	...	...	...	Polish, English	Polish, English	English	English	English
Manufacturer / Brand	APTI	APTI	APTI	APTI	APTI	DAHUA	DAHUA	DAHUA	DAHUA	DAHUA	DAHUA	DAHUA	DAHUA	DAHUA	DAHUA	DAHUA	DAHUA	DAHUA	Hikvision	Hikvision	Hikvision	Hikvision	Hikvision
Guarantee	2 years	2 years	2 years	2 years	2 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00