

	VIDEO DOORPHONE KIT ATLO-VD-D71KH1-TUYA	VIDEO DOORPHONE KIT ATLO-VD-D71KH2-TUYA	VIDEO DOORPHONE KIT ATLO-VD-K72KPF1-TUYA	VIDEO DOORPHONE KIT KTA02 DAHUA	VIDEO DOORPHONE KIT VDP-22A3
					
	145.41 EUR 145.41 EUR	274.84 EUR 274.84 EUR	222.25 EUR 222.25 EUR	192.67 EUR 192.67 EUR	166.91 EUR 166.91 EUR
Sensor	...	...	...	1.3 Mpx CMOS	1/3 " CCD
Standard	AHD	AHD	AHD	...	...
Camera view angle	92 °	92 °	92 °	70 °	~ 92 °
Relay output	1 pcs	1 pcs	...	...	...
IR illuminator	Built-in Infra-Red illuminator enables night monitoring	Built-in Infra-Red illuminator enables night monitoring	Built-in Infra-Red illuminator enables night monitoring	Built-in Infra-Red illuminator enables night monitoring	Built-in Infra-Red illuminator enables night monitoring
Video output	...	...	...	compatible with DAHUA analog video door-phone system	1 Vpp / 75 Ω
proximity reader built-in	—	—	Unique EM 125kHz	—	—
Audio inputs	1 - Microphone	1 - Microphone	1 - Microphone	1 - Microphone	...
Audio outputs	1 - Speaker	1 - Speaker	1 - Speaker	1 - Speaker	...
Mobile phones support	The Tuya Smart free application on Android The Tuya Smart free application on iOS	The Tuya Smart free application on Android The Tuya Smart free application on iOS	The Tuya Smart free application on Android The Tuya Smart free application on iOS	...	...
"Index of Protection"	...	...	...	IP66 - after additional sealing the housing connection with the mounting surface, e.g. with silicone	...
Packaging	...	2 pcs 2 pcs	...	...	...
INDOOR PANEL					
Shield	7 " TFT-LCD color matrix	7 " TFT-LCD color matrix	7 " TFT-LCD color matrix	7 " TFT-LCD color matrix	7 " TFT-LCD color matrix
Resolution	720p 1024 x 600	720p 1024 x 600	720p 1024 x 600	1024 x 600	480 x 234

Main features	• Rain cover included • 4-wire cable installation - 4.5 m included • The microSD - max. 64 GB cards support, • Ability to connect 2 additional analog cameras, • touch screen, • Selecting the ringer melody, • Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume, • Preview image from the door station with the possibility of turning on the sound and opening the gate, • Surface mount, • In the kit : Bracket	• Rain cover included • 4-wire cable installation - 3 x 4.5 m included • The microSD - max. 64 GB cards support, • Ability to connect 2 additional analog cameras, • touch screen, • Selecting the ringer melody, • Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume, • Preview image from the door station with the possibility of turning on the sound and opening the gate, • Surface mount, • In the kit : Bracket	• 5 keyfobs included - Open by using a card or PIN code - 1000 indexed users • Fingerprint reader built-in - 1000 indexed users • Rain cover included • Remote controlled • 4-wire cable installation - 4.5 m included • The microSD - max. 64 GB cards support, • Ability to connect 2 additional analog cameras, • touch screen, • Selecting the ringer melody, • Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume, • Preview image from the door station with the possibility of turning on the sound and opening the gate, • 4-wire cable installation, • Surface mount, • In the kit : Bracket	• D-WDR - Wide Dynamic Range • ICR - Movable InfraRed filter • Operation status LED indicator - green LED - power indicator • Doorbell button • Inputs : Exit button, Door status detection • Surface mount • Rain cover included • Touch control keys, • Operation status LED indicator - green LED - power indicator, • The maximum number of gate stations in the system : 2, • The maximum number of indoor panels in the system : 3, • Selecting the ringer melody, • Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume, • Preview image from the door station with the possibility of turning on the sound and opening the gate, • 4-wire cable installation, • Communication : compatible with DAHUA analog video door-phone system • Surface mount, • In the kit : Bracket	• Plug & Play, • A choice of 16 sounds, • Ultra-flat hands-free monitor, with speakerphone, • Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume, • Additional gate control, • 4-wire cable installation, • Door lock (strike) - 2-wire cable installation (not included), • Can be extended with additional monitor and camera, • Communication : via cable (duplex)
Power supply	15 V DC 15 V DC / 1.2 A - Monitor 15 V DC / 2 A (power adapter included)	15 V DC 15 V DC / 1.2 A - Monitor 15 V DC / 2 A (power adapter included)	15 V DC 15 V DC / 1.2 A - Monitor 15 V DC / 2 A (power adapter included)	12 V DC / 1 A (powered by indoor monitor) 12 V DC / 1 A - Monitor 12 V DC / 2 A (power adapter included)	12 V DC 12 V DC
Power consumption	≤ 12 W Operation ≤ 2 W Standby ≤ 5 W Operation ≤ 2 W Standby	≤ 12 W Operation ≤ 2 W Standby ≤ 5 W Operation ≤ 2 W Standby	≤ 12 W Operation ≤ 2 W Standby ≤ 5 W Operation ≤ 2 W Standby	≤ 3 W Operation ≤ 1 W Standby ≤ 5 W Operation ≤ 2 W Standby	< 5 W < 0.2 W Standby < 5 W Operation
Housing	Plastic + Zinc alloy Plastic (PC + ABS)	Plastic + Zinc alloy Plastic (PC + ABS)	Plastic Plastic (PC + ABS)	Plastic (PC + ABS) Plastic (PC + ABS)	Metal, Waterproof
Color	Gray + Black Gray + Black	Gray + Black Gray + Black	Black Gray + Black	Silver + Black White	Graphite
Supported languages	English, French, Spanish, German, Russian	English, French, Spanish, German, Russian	English, French, Spanish, German, Russian	...	...
Operation temp	-10 °C ... 50 °C -10 °C ... 50 °C	-10 °C ... 50 °C -10 °C ... 50 °C	-10 °C ... 50 °C -10 °C ... 50 °C	-30 °C ... 60 °C -10 °C ... 55 °C	-18 °C ... 50 °C 0 °C ... 30 °C
Weight	0.454 kg 0.358 kg	0.454 kg 0.358 kg	0.276 kg 0.358 kg	0.14 kg 0.25 kg	0.185 kg 0.47 kg
Dimensions	151 x 80 x 48 mm 205 x 140 x 23 mm	151 x 80 x 48 mm 205 x 140 x 23 mm	155 x 131 x 55 mm 205 x 140 x 23 mm	46 x 131 x 34 mm 183 x 134 x 18 mm	51 x 131 x 47 mm 240 x 160 x 17 mm
Manufacturer / Brand	ATLO	ATLO	ATLO	DAHUA	EURA
Guarantee	2 years	2 years	2 years	3 years	2 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00