	BRANCH JUNCTION BOX WITH CABLE GLANDS PK-80	BRANCH JUNCTION BOX WITH CABLE GLANDS PH-80X80X38/EPN IP55 Elektro-Plast	BRANCH JUNCTION BOX WITH CABLE GLANDS PH-80X80X38/EPN IP55 Elektro-Plast	BRANCH JUNCTION BOX WITH CABLE GLANDS PK-85X85	BRANCH JUNCTION BOX WITH CABLE GLANDS LUX-108X108/EPN IP55 Elektro-Plast	BRANCH JUNCTION BOX WITH CABLE GLANDS LUX-133X133/EPN IP55 Elektro-Plast	BRANCH JUNCTION BOX WITH CABLE GLANDS LUX-158X118/EPN IP55 Elektro-Plast	BRANCH JUNCTION BOX WITH CABLE GLANDS LUX-172X172/EPN IP55 Elektro-Plast	BRANCH JUNCTION BOX WITH CABLE GLANDS LUX-196X196/EPN IP55 Elektro-Plast	BRANCH JUNCTION BOX WITH CABLE GLANDS LUX-303X214/EPN IP55 Elektro-Plast
	0.62 EUR 0.62 EUR	1.39 EUR 1.39 EUR	1.36 EUR 1.36 EUR	1.52 EUR 1.52 EUR	2.84 EUR 2.84 EUR	3.09 EUR 3.09 EUR	4.83 EUR 4.83 EUR	5.85 EUR 5.85 EUR	10.76 EUR 10.76 EUR	14.85 EUR 14.85 EUR
Rated voltage										
Maximal current load										
Grounding										
Cable terminals										
Number of intakes	4 pcs Ø 23 mm	6 pcs Ø 19 mm	6 pcs Ø 19 mm	7 pcs Ø 21 mm	6 pcs Ø 23 mm	6 pcs Ø 29 mm	6 pcs Ø 29 mm	8 pcs Ø 29 mm	8 pcs Ø 29 mm	8 pcs Ø 29 mm
Socket type										
Voltage insulation							400 V	400 V	400 V	400 V
Protection shutter										
Assembly										
Internal dimensions							147 x 108 x 86 mm	163 x 163 x 55 mm	188 x 188 x 53 mm	287 x 200 x 112 mm
Main features					• Screwed cover with screws • There are cable glands in the housing	• Screwed cover with screws • There are cable glands in the housing	• 650 °C flammability index • Screwed cover with screws • There are cable glands in the housing • Possibility of sealing • Compliance with PN-IEC-60598-1:2006 standards	• 650 °C flammability index • Screwed cover with screws • There are cable glands in the housing • Possibility of sealing • Compliance with PN-IEC-60598-1:2006 standards	• 650 °C flammability index • Screwed cover with screws • There are cable glands in the housing • Possibility of sealing • Compliance with PN-IEC-60598-1:2006 standards	• 650 °C flammability index • Screwed cover with screws • There are cable glands in the housing • Possibility of sealing • Compliance with PN-IEC-60598-1:2006 standards
"Index of Protection"	IP55	IP55	IP55	IP55	IP55	IP55	IP55	IP55	IP55	IP55
Mechanical strength										
Material					Plastic	Plastic	Plastic - Polypropylene	Plastic - Polypropylene	Plastic - Polypropylene	Plastic (ABS)
Color					Black	Black	White (RAL 9003)	White (RAL 9003)	White (RAL 9003)	Gray (RAL 7035)
Weight										
Dimensions	Ø 86 x 62 mm	86 x 86 x 39 mm	86 x 86 x 39 mm	87 x 87 x 51 mm	108 x 108 x 60 mm	133 x 133 x 63 mm	158 x 118 x 94 mm	172 x 172 x 75 mm	196 x 196 x 78 mm	303 x 214 x 123 mm
Manufacturer / Brand		Elektro-Plast Nasielsk	Elektro-Plast Nasielsk		Elektro-Plast	Elektro-Plast	Elektro-Plast	Elektro-Plast	Elektro-Plast	Elektro-Plast
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years

	BRANCH JUNCTION BOX WITH CABLE GLANDS PK-100X100	BRANCH JUNCTION BOX WITH CABLE GLANDS PK-150X110	BRANCH JUNCTION BOX WITH CABLE GLANDS PK-150X150	BRANCH JUNCTION BOX WITH CABLE GLANDS PK-200X150	BRANCH JUNCTION BOX WITH CABLE GLANDS PK-200X155	BRANCH JUNCTION BOX WITH CABLE GLANDS PK-200X200	BRANCH JUNCTION BOX WITH CABLE GLANDS PK-255X200	BRANCH JUNCTION BOX WITH CABLE GLANDS PK-300X250	SINGLE SOCKET WITH JUNCTION BOX ZK/98X98/EN-2/0/EPN 230 V AC 16 A IP54 Elektro-Plast	BRANCH JUNCTION BOX WITH CABLE GLANDS PK-102K102	BRANCH JUNCTION BOX ZK/98X98/EPN IP55 / IP65 Elektro-Plast	BRANCH JUNCTION BOX INDUSTRIAL/200X230/EPN IP65 Elektro-Plast	BRANCH JUNCTION BOX PH-45X36/B/EPN IP55 Elektro-Plast	BRANCH JUNCTION BOX PH-75X75/B/EPN IP55 Elektro-Plast	BRANCH JUNCTION BOX PH-85X85/B/EPN IP55 Elektro-Plast	BRANCH JUNCTION BOX WITH CABLE GLANDS PK-105D	BRANCH JUNCTION BOX PK-24	BRANCH JUNCTION BOX WITH CABLE GLANDS PK-24D	BRANCH JUNCTION BOX PK-5 SIMET	BRANCH JUNCTION BOX WITH CABLE GLANDS PK-7 SIMET	BRANCH JUNCTION BOX WITH CABLE GLANDS PK-8 SIMET	BRANCH JUNCTION BOX WITH CABLE GLANDS PK-80MB	BRANCH JUNCTION BOX WITH CABLE GLANDS PK-92G
	2.67 EUR 2.67 EUR	1.81 EUR 1.81 EUR	4.92 EUR 4.92 EUR	5.72 EUR 5.72 EUR	6.48 EUR 6.48 EUR	8.39 EUR 8.39 EUR	8.01 EUR 8.01 EUR	16.41 EUR 16.41 EUR	6.72 EUR 6.72 EUR	1.98 EUR 1.98 EUR	4.85 EUR 4.85 EUR	41.45 EUR 41.45 EUR	0.92 EUR 0.92 EUR	0.98 EUR 0.98 EUR	0.98 EUR 0.98 EUR	8.81 EUR 8.81 EUR	1.40 EUR 1.40 EUR	1.98 EUR 1.98 EUR	1.72 EUR 1.72 EUR	1.90 EUR 1.90 EUR	2.43 EUR 2.43 EUR	2.43 EUR 2.43 EUR	6.07 EUR 6.07 EUR
Rated voltage									230 V AC													
Maximal current load									16 A													
Grounding									✓													
Cable terminals									screw terminals													
Number of intakes	7 pcs Ø 23 mm	10 pcs Ø 23 mm	8 pcs Ø 23 mm	8 pcs Ø 23 mm	10 pcs Ø 32 mm	12 pcs Ø 31 mm	12 pcs Ø 32 mm	12 pcs Ø 32 mm	4 pcs Ø 20 mm	4 pcs Ø 21 mm 4 pcs Ø 23 mm 4 pcs Ø 29 mm	6 pcs Ø 20 mm with flexible membranes	8 pcs Ø 40 mm / Ø 33 mm, 8 pcs Ø 25 mm / Ø 20 mm	10 pcs Ø 15 mm	7 pcs Ø 15 mm	12 pcs Ø 15 mm	6 pcs Ø 30 mm	7 pcs	7 pcs Ø 30 mm	8 pcs Ø 15 mm	12 pcs Ø 15 mm	12 pcs Ø 15 mm	8 pcs Ø 23 mm	4 pcs Ø 25 mm 2 pcs Ø 30 mm
Socket type									CEE 7/5, Surface-mounted													
Voltage insulation												600 V							– 400 V			
Protection shutter									✓													
Assembly									Mounting screws													
Internal dimensions																	125 x 125 x 50 mm	125 x 125 x 50 mm	75 x 35 x 33 mm			
Main features									• Hermetic casing • PN-EN 60670-22:2021 compliance		• Cover mounting with screws • Included: 5 x 2.5 mm^2 clamps	• Hermetic • Box casing designed to wall mounting • Hinged top cover • 650 °C flammability index • Possibility to mount N+PE cassette • Compliance with PN-IEC-60598-1:2006 standards	• 650 °C flammability index • Latching closure	• 650 °C flammability index • Latching closure	• 650 °C flammability index • Latching closure							
"Index of Protection"	IP65	IP65	IP65	IP65	IP65	IP65	IP65	IP65	IP54	IP65	IP55 / IP65	IP65	IP55	IP55	IP55	IP55	IP67	IP67	IP54	IP54	IP54	IP65	IP54
Mechanical strength												–											
Material											Plastic	Self-extinguishing ABS	Non-halogen plastic	Non-halogen plastic	Non-halogen plastic								
Color									Gray		White	Gray RAL7035	Black	Black	Black								
Weight									0.13 kg			1.73 kg											
Dimensions	108 x 108 x 67 mm	159 x 118 x 74 mm	154 x 154 x 74 mm	209 x 109 x 68 mm	200 x 155 x 78 mm	203 x 203 x 76 mm	255 x 200 x 77 mm	305 x 253 x 118 mm	120 x 99 x 57 mm	103 x 103 x 57 mm	88 x 88 x 38 mm - Internal dimensions 98 x 98 x 46 mm - External dimensions	440 x 186 x 120 mm - Internal dimensions 506 x 230 x 130 mm - External dimensions	90 x 45 x 39 mm	75 x 75 x 39 mm	85 x 85 x 39 mm	235 x 150 x 75 mm			85 x 44 x 40 mm	85 x 85 x 40 mm	100 x 100 x 41 mm	88 x 88 x 48 mm	185 x 165 x 123 mm
Manufacturer / Brand									Elektro-Plast		Elektro-Plast	Elektro-Plast Nasielsk	Elektro-Plast	Elektro-Plast	Elektro-Plast				SIMET	SIMET	SIMET		
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00