






	INDOOR PANEL IP DS-KH6320-TE1 Hikvision	INDOOR PANEL Wi-Fi / IP DS-KH6320-WTE1-W Hikvision	INDOOR PANEL Wi-Fi / IP DS-KH6320-WTE1/EU Hikvision	INDOOR PANEL Wi-Fi / IP DS-KH8350-WTE1/EU Hikvision	INDOOR PANEL Wi-Fi / IP DS-KH9510-WTE1(B) Hikvision
					
	235.48 EUR 235.48 EUR	253.41 EUR 253.41 EUR	253.41 EUR 253.41 EUR	388.48 EUR 388.48 EUR	496.53 EUR 496.53 EUR
Compatibility	Hikvision IP Video Doorphones	Hikvision IP Video Doorphones	Hikvision IP Video Doorphones	Hikvision IP Video Doorphones	Hikvision IP Video Doorphones
Shield	7 " - capacitive touch screen	7 " - capacitive touch screen	7 " - capacitive touch screen	7 " - capacitive touch screen IPS	10.1 " IPS - capacitive touch screen
Resolution	1024 x 600	1024 x 600	1024 x 600	1024 x 600	1024 x 600
Internal memory	128 MB (built-in)	128 MB (built-in)	128 MB (built-in)	128 MB (built-in)	8 GB eMMC (built-in)
Main features	<ul style="list-style-type: none"> • Microphone built-in, • Speakers built-in, • Bidirectional communication, • Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume, • Automatically capture and save photos if there is no response to the bell button, • IP Hikvision cameras support, • The ability of direct communication between two or more panels, • Register a short voice message if there is no response to the bell button • Support for capturing a photo during video calls • The microSD cards support max. 32 GB (not included) • The device is fully configurable via the iVMS4200 software. • In addition, the device has the ability to work with the Hik-Connect application on mobile devices 	<ul style="list-style-type: none"> • Wi-Fi module - IEEE 802.11 b/g/n, • Microphone built-in, • Speakers built-in, • Bidirectional communication, • Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume, • Automatically capture and save photos if there is no response to the bell button, • IP Hikvision cameras support, • The ability of direct communication between two or more panels, • Register a short voice message if there is no response to the bell button • Support for capturing a photo during video calls • The microSD cards support max. 32 GB (not included) • The device is fully configurable via the iVMS4200 software. • In addition, the device has the ability to work with the Hik-Connect application on mobile devices 	<ul style="list-style-type: none"> • Wi-Fi module - IEEE 802.11 b/g/n, • Microphone built-in, • Speakers built-in, • Bidirectional communication, • Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume, • Automatically capture and save photos if there is no response to the bell button, • IP Hikvision cameras support, • The ability of direct communication between two or more panels, • Register a short voice message if there is no response to the bell button • Support for capturing a photo during video calls • The microSD cards support max. 32 GB (not included) • The device is fully configurable via the iVMS4200 software. • In addition, the device has the ability to work with the Hik-Connect application on mobile devices 	<ul style="list-style-type: none"> • Wi-Fi module - IEEE 802.11 b/g/n, • Remote opening via a mobile client or software, • Support for capturing a photo during video calls, • Microphone built-in, • Speakers built-in, • Bidirectional communication, • Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume, • Automatically capture and save photos if there is no response to the bell button, • IP Hikvision cameras support, • The ability of direct communication between two or more panels, • Register a short voice message if there is no response to the bell button, • Support for capturing a photo during video calls, • User-friendly graphical interface, • The microSD cards support (not included) • The device is fully configurable via the iVMS4200 software. • In addition, the device has the ability to work with the Hik-Connect application on mobile devices 	<ul style="list-style-type: none"> • Wi-Fi module - IEEE 802.11 b/g/n, • Microphone built-in, • Speakers built-in, • Bidirectional communication, • Echo suppression and reduction / digital noise reduction, • Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume, • Automatically capture and save photos if there is no response to the bell button, • IP Hikvision cameras support, • The ability of direct communication between two or more panels, • Register a short voice message if there is no response to the bell button, • Support for capturing a photo during video calls, • User-friendly graphical interface, • The microSD cards support (not included) • The device is fully configurable via the iVMS4200 software. • In addition, the device has the ability to work with the Hik-Connect application on mobile devices
Controlling	capacitive touch screen	capacitive touch screen	capacitive touch screen	Touch control keys + capacitive touch screen	capacitive touch screen
Default administrator password	— The administrator password should be set at the first start	— The administrator password should be set at the first start	— The administrator password should be set at the first start	— The administrator password should be set at the first start	—
Default password for securing the zone	—	—	—	—	—
Alarm inputs	8	8	8	8	8
Alarm outputs	—	2	2	2	2
Power supply	• 12 V DC, • IEEE 802.3af	• 12 V DC, • IEEE 802.3af	• 12 V DC, • IEEE 802.3af	• PoE (802.3af), • 12 V DC	• 12 V DC, • PoE (802.3af)
Power consumption	≤ 6 W	≤ 6 W	≤ 6 W	≤ 7 W	≤ 8 W

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Housing	Aluminum	...
Color	Black + Silver	White	Black + Silver	Silver + Black	White
Operation temp	-10 °C ... 55 °C	-10 °C ... 55 °C	-10 °C ... 55 °C	-10 °C ... 55 °C	-10 °C ... 50 °C
Weight	0.33 kg	0.34 kg	0.36 kg	0.35 kg	0.86 kg
Dimensions	200 x 140 x 25 mm	200 x 140 x 25 mm	200 x 140 x 25 mm	180 x 140 x 23 mm	254 x 166 x 27 mm
Supported languages	Polish, English, Bulgarian, Croatian, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Romanian, Serbian, Hungarian, Italian	Polish, English, Bulgarian, Croatian, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Romanian, Serbian, Hungarian, Italian	Polish, English, Bulgarian, Croatian, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Romanian, Serbian, Hungarian, Italian	Polish, English, Bulgarian, Croatian, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Romanian, Serbian, Hungarian, Italian	Polish, English, Bulgarian, Czech, French, Spanish, Dutch, German, Portuguese, Russian, Romanian, Turkish, Ukrainian, Hungarian, Italian
Manufacturer / Brand	Hikvision	Hikvision	Hikvision	Hikvision	Hikvision
SAP Code	305301486	305301796	305301487	305301482	305303100
Guarantee	3 years	3 years	3 years	3 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00