

	SWITCH DS-KAD706Y FOR HIKVISION 2-WIRE VIDEO DOORPHONE SYSTEMS	VIDEO DOORPHONE DS-KD8003Y-IME2 Hikvision	INDOOR PANEL DS-KH6320-WTE2 Hikvision	INDOOR PANEL DS-KH6320Y-WTE2 Hikvision	INDOOR PANEL DS-KH6320Y-WTE2/WHITE Hikvision	VIDEO DOORPHONE KIT DS-KIS702Y Hikvision
						
	143.51 EUR 143.51 EUR	187.76 EUR 187.76 EUR	191.11 EUR 191.11 EUR	253.54 EUR 253.54 EUR	253.54 EUR 253.54 EUR	549.89 EUR 549.89 EUR
Doorbell button	...	1 pcs	...	...	...	1 pcs
Sensor	...	2.1 Mpx CMOS	...	...	...	2.1 Mpx CMOS
Camera resolution	...	1920 x 1080 - 1080p	...	...	...	1920 x 1080 - 1080p
Camera view angle	...	146 °	...	...	...	146 °
Image compression method	...	H.264	...	...	...	H.264
IR illuminator	...	✓	...	...	...	✓
Network protocols	...	...	...	...	...	TCP/IP, RTSP, SIP
Relay outputs	...	2 x NO/NC	...	...	...	2 x NO/NC
"Index of Protection"	...	IP65	...	...	...	IP65
Shield	...	...	7 " - capacitive touch screen	7 " - capacitive touch screen	7 " - capacitive touch screen	7 " - capacitive touch screen
Resolution	...	...	1024 x 600	1024 x 600	1024 x 600	1024 x 600
Internal memory	...	...	128 MB (built-in)	128 MB (built-in)	128 MB (built-in)	128 MB (built-in)
Main features	...	...	• Wi-Fi module - IEEE 802.11 b/g/n, • Microphone built-in, • Speakers built-in, • Bidirectional communication, • Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume, • Automatically capture and save photos if there is no response to the bell button, • IP Hikvision cameras support, • The ability of direct communication between two or more panels, • Register a short voice message if there is no response to the bell button • Support for capturing a photo during video calls • The microSD cards support max. 32 GB (not included) • The device is fully configurable via the iVMS4200 software. • In addition, the device has the ability to work with the Hik-Connect application on mobile devices	• Wi-Fi module - IEEE 802.11 b/g/n, • Microphone built-in, • Speakers built-in, • Bidirectional communication, • Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume, • Automatically capture and save photos if there is no response to the bell button, • IP Hikvision cameras support, • The ability of direct communication between two or more panels, • Register a short voice message if there is no response to the bell button • Support for capturing a photo during video calls • The microSD cards support max. 128 GB (not included) • The device is fully configurable via the iVMS4200 software. • In addition, the device has the ability to work with the Hik-Connect application on mobile devices	• Wi-Fi module - IEEE 802.11 b/g/n, • Microphone built-in, • Speakers built-in, • Bidirectional communication, • Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume, • Automatically capture and save photos if there is no response to the bell button, • IP Hikvision cameras support, • The ability of direct communication between two or more panels, • Register a short voice message if there is no response to the bell button • Support for capturing a photo during video calls • The microSD cards support max. 128 GB (not included) • The device is fully configurable via the iVMS4200 software. • In addition, the device has the ability to work with the Hik-Connect application on mobile devices	• Wi-Fi module - IEEE 802.11 b/g/n, • Microphone built-in, • Speakers built-in, • Bidirectional communication, • Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume, • Automatically capture and save photos if there is no response to the bell button, • IP Hikvision cameras support, • The ability of direct communication between two or more panels, • Register a short voice message if there is no response to the bell button • Support for capturing a photo during video calls • The microSD - max. 128 GB cards support - 16 GB included, • The device is fully configurable via the iVMS4200 software. • In addition, the device has the ability to work with the Hik-Connect application on mobile devices
Controlling	...	...	capacitive touch screen	capacitive touch screen	capacitive touch screen	capacitive touch screen
Default administrator password	...	...	— The administrator password should be set at the first start	— The administrator password should be set at the first start	— The administrator password should be set at the first start	— The administrator password should be set at the first start
Default password for securing the zone	...	...	—	—	—	—
Alarm inputs	...	4 pcs	8	8	8	4 pcs 8
Alarm outputs	...	...	2	2	2	2
Power consumption	< 6 W - CH1 ... CH5 < 16 W - CH6	< 4 W	≤ 6 W	≤ 4 W	≤ 4 W	< 4 W ≤ 4 W
Number of mounted modules	...	...	...	...	...	1 pcs
Material	...	...	...	...	...	Aluminum
Color	...	Black	Black + Silver	Black + Silver	White	Black Black + Silver Graphite

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

External dimensions	...	...	...	...	...	117 x 107 x 37 mm
Number of ports	6 x HIKVISION 2-wire (1 x max. 16 W) , 2 x HIKVISION 2-wire - Uplink 1 x RJ-45	...	...	...	...	6 x HIKVISION 2-wire (4 x device, 2 x Possibility to connecting in cascade) , 1 x RJ-45
Compatibility	HIKVISION 2-wire - Y series	HIKVISION 2-wire - Y series	Hikvision 2-wire modular video doorphones	HIKVISION 2-wire - Y series	HIKVISION 2-wire - Y series	HIKVISION 2-wire - Y series HIKVISION 2-wire - Y series
Main features	• Possibility to connecting in cascade • DIN, TS-35 rail mounting	• Bidirectional communication, • Microphone built-in, • Speakers built-in, • Noise suppression and echo cancellation, • Tamper detection - removing from mounting surface, • Installation of DS-KD-xx series modules takes place in dedicated DS-KD-ACF series housings (flush-mounted housings) and DS-KD-ACW series housings (surface-mounted housings)	...	...	...	• True WDR - Wide Dynamic Range, • DNR - Digital Noise Reduction, • BLC - Back Light Compensation, • Motion Detection, • Bidirectional communication, • Microphone built-in, • Speakers built-in, • Noise suppression and echo cancellation, • Tamper detection - removing from mounting surface - DIN, TS-35 rail mounting
Power supply	24 V DC	• 24 V DC - HIKVISION 2-wire	24 V DC - HIKVISION 2-wire	24 V DC - HIKVISION 2-wire - Y series	24 V DC - HIKVISION 2-wire - Y series	• 24 V DC - HIKVISION 2-wire 24 V DC - HIKVISION 2-wire
Housing	Plastic	Metal	...	...	...	Metal + Plastic Plastic
Operation temp	-10 °C ... 55 °C	-40 °C ... 60 °C	-10 °C ... 50 °C	-10 °C ... 50 °C	-10 °C ... 50 °C	-40 °C ... 60 °C -10 °C ... 50 °C -10 °C ... 55 °C
Weight	0.27 kg	0.38 kg	0.33 kg	0.32 kg	0.32 kg	0.38 kg 0.32 kg 0.22 kg 0.25 kg
Dimensions	144 x 90 x 66 mm	100 x 98 x 44 mm	200 x 140 x 25 mm	200 x 140 x 25 mm	200 x 140 x 25 mm	100 x 98 x 44 mm 200 x 140 x 25 mm 144 x 90 x 66 mm
Supported languages	...	Polish, English, Bulgarian, Croatian, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Romanian, Serbian, Hungarian, Italian	Polish, English, Bulgarian, Croatian, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Romanian, Serbian, Hungarian, Italian	Polish, English, Bulgarian, Croatian, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Romanian, Serbian, Hungarian, Italian	Polish, English, Bulgarian, Croatian, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Romanian, Serbian, Hungarian, Italian	Polish, English, Bulgarian, Croatian, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Romanian, Serbian, Hungarian, Italian
Manufacturer / Brand	Hikvision	Hikvision	Hikvision	Hikvision	Hikvision	Hikvision
SAP Code	305303644	305303988	305301758	305303991	305304183	305303992
Guarantee	3 years	3 years	3 years	3 years	3 years	3 years