

	VIDEO DOORPHONE KIT DS-KIS602(B)(O-STD) Hikvision	VIDEO DOORPHONE KIT DS-KIS604-S(C) Hikvision
		
	552.42 EUR 552.42 EUR	379.41 EUR 379.41 EUR
Doorbell button	1 pcs	1 pcs
proximity reader built-in	...	13.56 MHz S50
Sensor	2.1 Mpx CMOS	2 Mpx
Camera resolution	1920 x 1080 - 1080p	1920 x 1080 - 1080p
Camera view angle	146 °	124 °
Image compression method	H.264	H.264
Ethernet	10/100 Mb/s	...
Supported audio formats	...	G.711
IR illuminator	✓	✓
Network interface	...	• 10 / 100 Mbps Ethernet • WiFi
Wireless transmission range	...	The range limited only by the availability of the Wi-Fi network
Wi-Fi standard	...	IEEE 802.11b / IEEE 802.11g / IEEE 802.11n
Network protocols	TCP/IP, RTSP	TCP/IP, RTSP
Relay outputs	2 x NO/NC	2 x NO/NC
RS-485	...	✓

Main features	• Bidirectional communication, • Microphone built-in, • Speakers built-in, • Noise suppression and echo cancellation, • Tamper detection - removing from mounting surface, • Installation of DS-KD-xx series modules takes place in dedicated DS-KD-ACF series housings (flush-mounted housings) and DS-KD-ACW series housings (surface-mounted housings) • Power output : 12 V DC / 500 mA (max)	• Bidirectional communication, • Microphone built-in, • Speakers built-in, • Noise suppression and echo cancellation, • Tamper detection - removing from mounting surface, • True WDR - Wide Dynamic Range • BLC - Back Light Compensation • DNR - Digital Noise Reduction • Full support via network : WiFi / LAN • Video Doorphone is mounted in a surface housing • The device has the ability to work with the Hik-Connect application for mobile devices, without the use of an internal panel
Housing	Metal	Aluminum + Plastic, Protects against weather conditions
Vandal-proof	...	IK08
"Index of Protection"	IP65	IP65
Compatibility	IP Hikvision video doorphones II generation IP Hikvision modular video doorphones	IP Hikvision video doorphones II generation IP Hikvision modular video doorphones
Shield	7 " - capacitive touch screen	7 " - capacitive touch screen
Resolution	1024 x 600	1024 x 600
Internal memory	128 MB (built-in)	128 MB (built-in)

Main features	• Wi-Fi module - IEEE 802.11 b/g/n, • Microphone built-in, • Speakers built-in, • Bidirectional communication, • Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume, • Automatically capture and save photos if there is no response to the bell button, • IP Hikvision cameras support, • The ability of direct communication between two or more panels, • Register a short voice message if there is no response to the bell button • Support for capturing a photo during video calls • The microSD cards support max. 32 GB, 16 GB included • The device is fully configurable via the iVMS4200 software. • In addition, the device has the ability to work with the Hik-Connect application on mobile devices	• Wi-Fi module - IEEE 802.11 b/g/n, • Microphone built-in, • Speakers built-in, • Bidirectional communication, • Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume, • Automatically capture and save photos if there is no response to the bell button, • IP Hikvision cameras support, • The ability of direct communication between two or more panels, • Register a short voice message if there is no response to the bell button • Support for capturing a photo during video calls • The microSD cards support max. 32 GB, 16 GB included • The device is fully configurable via the iVMS4200 software. • In addition, the device has the ability to work with the Hik-Connect application on mobile devices
Controlling	capacitive touch screen	capacitive touch screen
Default administrator password	— The administrator password should be set at the first start	— The administrator password should be set at the first start
Default password for securing the zone	—	—
Alarm inputs	4 pcs 8	4 pcs 8
Alarm outputs	2	2
Power consumption	≤ 5 W ≤ 6 W	≤ 10 W (operation) ≤ 6 W
Number of mounted modules	1 pcs	1 pcs
Material	Aluminum	Plastic

Color	Black Black + Silver Graphite	Black + Gray Black + Silver Black
External dimensions	117 x 107 x 37 mm	174 x 91 x 19 mm
Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3af	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3af, IEEE 802.3at
LAN ports	• 1 x RJ45 100 Base-T - Uplink, • 4 x 10/100 Base-T (4 x PoE (802.3af))	• 1 x RJ45 100 Base-T - Uplink, • 4 x 10/100 Base-T (4 x PoE (802.3af/at)) • 1, 2 - High priority ports
LED diodes	Power, PoE, Link/Act	Power, PoE Max, Link/Act, PoE
Transmission speed	10 / 100 Mbps : 1 Port LAN + 4 LAN & PoE ports	10 / 100 Mbps : 1 Port LAN + 4 LAN & PoE ports
Management	—	—
Maximal output power	15 W / port PoE	30 W / port PoE
Maximal total power	38 W	35 W
MAC addresses table	1k - Auto update of MAC addresses table	1k
Operation modes	• Extend On : 250 m, 10 Mbps @ UTP cat. 5e, 6 - 1 ... 4 ports • Extend Off : 100 m, 100 Mbps @ UTP cat. 5e, 6	• Extend On : 300 m, 10 Mbps @ UTP cat. 5e, 6 - 1 ... 4 ports • Extend Off : 100 m, 100 Mbps @ UTP cat. 5e, 6
Operation temp	-40 °C ... 60 °C -10 °C ... 55 °C 0 °C ... 40 °C	-40 °C ... 53 °C -10 °C ... 55 °C -10 °C ... 55 °C
Power supply	• PoE (802.3af), • 12 V DC • PoE (802.3af), • 12 V DC 48 V DC / 800 mA (power adapter included)	• PoE (802.3af), • 12 V DC / 830 mA (max) • PoE (802.3af), • 12 V DC 48 V DC / 800 mA (power adapter included)
Weight	0.38 kg 0.34 kg 0.32 kg 0.2 kg	0.34 kg 0.33 kg 0.03 kg 0.2 kg
Dimensions	100 x 98 x 44 mm 200 x 140 x 25 mm 132 x 95 x 28 mm	174 x 91 x 30 mm 200 x 140 x 25 mm 105 x 86 x 28 mm

Supported languages	Polish, English, Bulgarian, Croatian, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Romanian, Serbian, Hungarian, Italian	Polish, English, Bulgarian, Croatian, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Romanian, Serbian, Hungarian, Italian
Manufacturer / Brand	Hikvision	Hikvision
SAP Code	305303906	305303810
Guarantee	3 years	3 years

