

	LASER RANGEFINDER LM-100 UNI-T	LASER RANGEFINDER LM-100A UNI-T	LASER RANGEFINDER LM-120 UNI-T	LASER RANGEFINDER LM-120A UNI-T	LASER RANGEFINDER LM-40 UNI-T	LASER RANGEFINDER LM-50A UNI-T	LASER RANGEFINDER LM-50D UNI-T	LASER RANGEFINDER LM-70A UNI-T	LASER RANGEFINDER LM-80 UNI-T	LASER RANGEFINDER & TAPE MEASURE LM-40T UNI-T
										
	55.76 EUR 55.76 EUR	44.98 EUR 44.98 EUR	92.94 EUR 92.94 EUR	57.25 EUR 57.25 EUR	27.15 EUR 27.15 EUR	27.14 EUR 27.14 EUR	84.01 EUR 84.01 EUR	33.46 EUR 33.46 EUR	46.48 EUR 46.48 EUR	41.64 EUR 41.64 EUR
Measurement range	100 m ± (2mm+5x10 ⁻³)	100 m ± (2mm+5x10 ⁻³)	120 m ± (2mm+5x10 ⁻³)	120 m ± (2mm+5x10 ⁻³)	40 m ± (2mm+5x10 ⁻³)	50 m ± (2mm+5x10 ⁻³)	50 m ± (2mm+5x10 ⁻³)	70 m ± (2mm+5x10 ⁻³)	80 m ± (2mm+5x10 ⁻³)	40 m ± (2mm+5x10 ⁻³) - Laser Rangefinder, * 5 m - Tape Rule
Continuous measurement	✓	✓	✓	✓	✓	✓	✓	✓	✓	—
Area measurement	✓	✓	✓	✓	✓	✓	✓	✓	✓	—
Volume measurement	✓	✓	✓	✓	✓	✓	✓	✓	✓	—
Triangular area measurement	—	—	—	—	—	—	✓	—	—	—
Measurement of the calottes	—	✓	—	✓	✓	✓	✓	✓	✓	—
Measurements using the Pythagorean theorem	✓	✓	✓	✓	✓	✓	✓	✓	✓	—
Section measurement	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Angle measurement	✓	—	✓	—	—	—	—	—	—	—
Measurement of deviation from the level	✓	—	✓	—	—	—	✓	—	✓	—
Measurement of deviation from the vertical	✓	—	✓	—	—	—	—	—	✓	—
Add/subtract function	✓	✓	✓	✓	✓	✓	✓	✓	✓	—
Save measurements	20 groups	99 groups	20 groups	99 groups	20 groups	99 groups	20 groups	99 groups	20 groups	—
Measurement unit	meters / feet / inches	meters / feet / inches	meters / feet / inches	meters / feet / inches	meters / feet / inches	meters / feet / inches	meters / feet / inches	meters / feet / inches	meters / feet / inches	meters / feet / inches - Laser Rangefinder * meters / inches - Tape Rule
Main features	• Reference point: front or back of the device • LCD display 2 " - White backlight • Battery charge indicator • Laser 630-670nm, <1mW • Automatically turns off the laser after 30 s • Automatically turns off the device after 3 min • Buzzer • Built-in mini spirit level	• Reference point: front or back of the device • LCD display 2 " - White backlight • Battery charge indicator • Laser 630-670nm, <1mW • Automatically turns off the laser after 20 s • Automatically turns off the device after 3 min • Buzzer • Built-in mini spirit level - vertical/horizontal • The set includes a practical case	• Reference point: front or back of the device • LCD display 2 " - White backlight • Battery charge indicator • Self-calibration function • Laser 630-670nm, <1mW • Automatically turns off the laser after 20 s • Automatically turns off the device after 3 min • Buzzer • Built-in mini spirit level - vertical/horizontal • The set includes a practical case	• Reference point: front or back of the device • EBTN display • Battery charge indicator • Laser 630-670nm, <1mW • Automatically turns off the laser after 30 s • Automatically turns off the device after 3 min • Buzzer • Built-in mini spirit level	• Reference point: front or back of the device • LCD display 2 " - White backlight • EBTN display • Self-calibration function • Laser 630-670nm, <1mW • Automatically turns off the laser after 20 s • Automatically turns off the devices after 3 min • Buzzer • Built-in mini spirit level - vertical/horizontal • The set includes a practical case	• Reference point: front or back of the device • LCD display 2 " - White backlight • Battery charge indicator • Self-calibration function • Laser 630-670nm, <1mW • Automatically turns off the laser after 20 s • Automatically turns off the devices after 3 min • Buzzer • Built-in mini spirit level - vertical/horizontal • The set includes a practical case	• Measure the distance with the roller on the corner of the device, • Voice prompts in English or Chinese, • Reference point: front, back, or tripod, • EBTN display, • Battery charge indicator, • Laser 630-670nm, <1mW, • Automatically turns off the laser after 30 s, • Automatically turns off the device after 3 min, • Buzzer, • Built-in mini spirit level	• Reference point: front or back of the device • LCD display 2 " - White backlight • Battery charge indicator • Self-calibration function • Laser 630-670nm, <1mW • Automatically turns off the laser after 20 s • Automatically turns off the device after 3 min • Buzzer • Built-in mini spirit level - vertical/horizontal • The set includes a practical case	• Reference point: front or back of the device • LCD display 2 " - White backlight • Battery charge indicator • Laser 630-670nm, <1mW • Automatically turns off the laser after 30 s • Automatically turns off the device after 3 min • Buzzer • Built-in mini spirit level	• Reference point: front or back of the device • EBTN display • Battery charge indicator • Laser 630-670nm, <1mW • Automatically turns off the laser after 30 s • Automatically turns off the device after 3 min • Buzzer • Built-in mini spirit level
Power supply	Alkaline batteries AAA, 2 pcs (included)	Alkaline batteries AAA, 2 pcs (included)	Alkaline batteries AAA, 2 pcs (included)	Alkaline batteries AAA, 2 pcs (included)	Alkaline batteries AAA, 2 pcs (included)	Alkaline batteries AAA, 2 pcs (included)	Alkaline batteries AAA, 2 pcs (included)	Alkaline batteries AAA, 2 pcs (included)	Alkaline batteries AAA, 2 pcs (included)	Alkaline batteries AAA, 2 pcs (included)
Operation temp	0 °C ... 40 °C	0 °C ... 40 °C	0 °C ... 40 °C	0 °C ... 40 °C	0 °C ... 40 °C	0 °C ... 40 °C	0 °C ... 40 °C	0 °C ... 40 °C	0 °C ... 40 °C	0 °C ... 40 °C
Weight	0.11 kg	0.09 kg	0.11 kg	0.09 kg	0.11 kg	0.09 kg	0.13 kg	0.09 kg	0.11 kg	0.28 kg
Dimensions	122 x 52 x 30 mm	112 x 50 x 25 mm	122 x 52 x 30 mm	112 x 50 x 25 mm	122 x 53 x 30 mm	112 x 50 x 25 mm	137 x 55 x 26 mm	112 x 50 x 25 mm	122 x 53 x 30 mm	86 x 80 x 50 mm
Manufacturer / Brand	UNI-T	UNI-T	UNI-T	UNI-T	UNI-T	UNI-T	UNI-T	UNI-T	UNI-T	UNI-T
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00