

	BALLAST TANK FOR MOUNTING SOLAR PANELS 5 GRAM BOX	CRIMPING TOOL LV-2546B TN-400 FOR SOLAR PANELS 30 mm	END CLAMP PV-KK/30-50/B FOR SOLAR PANELS 30 mm	END CLAMP PV-KK/30-50/S FOR SOLAR PANELS 30 mm	END CLAMP PV-KK/35-50/B FOR SOLAR PANELS 35 mm	END CLAMP PV-KK/35-50/S FOR SOLAR PANELS 35 mm	END CLAMP PV-KK/40-50/B FOR SOLAR PANELS 40 mm	END CLAMP PV-KK/40-50/S FOR SOLAR PANELS 40 mm	UNIVERSAL MIDDLE CLAMP PV-KS/50/B FOR SOLAR PANELS	UNIVERSAL MIDDLE CLAMP PV-KS/50/S FOR SOLAR PANELS	UNIVERSAL MIDDLE CLAMP PV-KSU/50/B FOR SOLAR PANELS	SLIDING GROOVE WITH BALL PV-WPZK	ALLEN SCREW SL-M8x25/K1-8.8	ALLEN SCREW SL-M8x30/K1-8.8	ALLEN SCREW SL-M8x35/K1-8.8	ALLEN SCREW SL-M8x40/K1-8.8	HEX HEAD SCREW SS-M8x20/K1-8.8	HEX HEAD SCREW SS-M8x30/K1-8.8	HEX HEAD SCREW SS-M8x40/K1-8.8	HEX HEAD SCREW SS-M8x50/K1-8.8	UNIVERSAL MIDDLE CLAMP USE-KW-35 FOR SOLAR PANELS	END CLAMP USE-KZ-30 FOR SOLAR PANELS 30 mm	MOUNTING PROFILE USE-SM-1100 FOR SOLAR PANELS	MOUNTING PROFILE USE-SM-1650 FOR SOLAR PANELS	POLE MOUNT USE-SUN-340 FOR SOLAR PANELS	REAR SUPPORT FOR THE MOUNTING PROFILE USE-TN-400 FOR SOLAR PANELS	REAR SUPPORT FOR THE MOUNTING PROFILE USE-TN-600 FOR SOLAR PANELS	WALL MOUNTING KIT USE-U30 FOR SOLAR PANELS	FRONT MOUNTING BASE USE-UDMK-F FOR SOLAR PANELS	REAR MOUNTING BASE USE-UDMK-T FOR SOLAR PANELS	CABLE FOR SOLAR INSTALLATIONS H17222-K134.00B	CABLE FOR SOLAR INSTALLATIONS H17222-K134.00B	CONNECTOR FOR SOLAR INSTALLATIONS MC4ZAC-F3	
																																		
Size	103.08 EUR	18.12 EUR	0.71 EUR	0.39 EUR	0.62 EUR	0.40 EUR	0.55 EUR	0.40 EUR	0.74 EUR	0.39 EUR	0.91 EUR	0.21 EUR	0.13 EUR	0.18 EUR	0.20 EUR	0.23 EUR	0.10 EUR	0.17 EUR	0.15 EUR	0.19 EUR	0.48 EUR	0.24 EUR	13.74 EUR	27.06 EUR	147.71 EUR	3.87 EUR	6.44 EUR	23.57 EUR	6.66 EUR	7.30 EUR	0.90 EUR	0.90 EUR	4.03 EUR	
Thread type												M8	M8	M8	M8	M8	M8	M8	M8	M8														
Material			Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Steel galvanized	Steel galvanized	Steel galvanized	Steel galvanized	Steel galvanized	Steel galvanized	Steel galvanized	Steel galvanized	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum				
Tank capacity	60 l																																	
Height			30 mm	30 mm	35 mm	35 mm	40 mm	40 mm	21.5 mm	21.5 mm	21.5 mm																							
Strength class													8.8	8.8	8.8	8.8	8.8	8.8	8.8	8.8														
The inclination of the panel surface relative to the ground	21 °																																	
Hole diameter			9 mm	9 mm	9 mm	9 mm	9 mm	9 mm	9 mm	9 mm	9 mm																							
Tilt angle adjustment:																																		
Maximum pole diameter																																		
Mounting profile length																																		
In package																																		
Maximum inclination of the mounting surface	10 °																																	
mounting screw																																		
Wrench size													6 mm	6 mm	6 mm	6 mm	13 mm	13 mm	13 mm	13 mm	M8 x 45 (included)													
Connector type																																		
Inner conductor																																		
Thread length													25 mm	30 mm	35 mm		20 mm	30 mm	40 mm	50 mm														
Application			MC4 connector, Wire gauge : 2.5 mm² ... 6 mm² (AWG 13 ... AWG 10)																															
Rated current																																		
Thread/pin length																																		
Rated voltage																																		
Material	Plastic	Metal / PET																																
Color			Black	Silver	Black	Silver	Black	Silver	Black	Silver	Black																							
Outer coating																																		