

	INDOOR PANEL VTH4262GW-W IP / Wi-Fi / 2-Wire DAHUA	INDOOR PANEL VTH5422HB-W IP / 2-Wire DAHUA	INDOOR PANEL VTH5422HB-W IP / Wi-Fi / 2- Wire DAHUA	INDOOR PANEL VTH5422HW-W IP / Wi-Fi / 2- Wire DAHUA	VIDEO DOORPHONE KIT KT010F DAHUA	VIDEO DOORPHONE KIT KT01-S2F DAHUA	VIDEO DOORPHONE KIT KT02F DAHUA	SWITCH VTNS1001B-2-A DAHUA 2-wire	SWITCH VTNS2003B-2 DAHUA 2-wire	VIDEO DOORPHONE VT0202F-P-S2 DAHUA	VIDEO DOORPHONE VT0312Q-P DAHUA	VIDEO DOORPHONE VT04202F-P-S2 DAHUA	VIDEO DOORPHONE VT04202F-P-S2 DAHUA
													
	252.54 EUR 252.54 EUR	339.76 EUR 339.76 EUR	339.76 EUR 339.76 EUR	339.76 EUR 339.76 EUR	752.58 EUR 752.58 EUR	547.85 EUR 547.85 EUR	577.89 EUR 577.89 EUR	203.28 EUR 203.28 EUR	177.33 EUR 177.33 EUR	277.77 EUR 277.77 EUR	391.91 EUR 391.91 EUR	295.07 EUR 295.07 EUR	358.03 EUR 358.03 EUR
Sensor	---	---	---	---	2 Mpx CMOS	2 Mpx CMOS	2 Mpx CMOS	---	---	2 Mpx CMOS	2 Mpx CMOS	2 Mpx CMOS	2 Mpx CMOS
Lens	---	---	---	---	1.95 mm	1.95 mm	1.9 mm	---	---	1.95 mm	1.9 mm	1.9 mm	1.9 mm
View angle	---	---	---	---	168 °	168 °	169 °	---	---	168 °	125 °	160 °	169 °
proximity reader built-in	---	---	---	---	---	---	---	---	---	---	Access control cards - 13.56 MHz S50, Memory of 3000 RFID cards	---	---
Image compression method	---	---	---	---	H.265	H.265	H.265, H.264	---	---	H.265	H.265 / H.264	H.265	H.265
LED illuminator	---	---	---	---	---	---	---	---	---	---	---	---	---
UTP category	---	---	---	---	UTP cat. 5e	UTP cat. 5e	---	---	---	---	---	---	---
IR illuminator	---	---	---	---	✓	✓	✓	---	---	✓	✓	✓	✓
RS-485	---	---	---	---	✓	✓	✓	---	---	✓	✓	✓	✓
Mobile phones support	---	---	---	---	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS	---	---	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS
Shield	7" capacitive touch screen	7" capacitive touch screen	7" capacitive touch screen	7" capacitive touch screen	7" capacitive touch screen	7" capacitive touch screen	7" capacitive touch screen	---	---	---	---	---	---
Resolution	1024 x 600	1024 x 600	1024 x 600	1024 x 600	1024 x 600	1024 x 600	1024 x 600	---	---	---	---	---	---
Internal memory	---	---	---	---	---	---	---	---	---	---	---	---	---
Memory card slot	---	Micro SD memory cards up to 64GB support (possible local recording)	Micro SD memory cards up to 64GB support (possible local recording)	Micro SD memory cards up to 64GB support (possible local recording)	Micro SD memory cards up to 64GB support (possible local recording)	Micro SD memory cards up to 64GB support (possible local recording)	---	---	---	---	---	---	---
"Index of Protection"	---	---	---	---	IP65 - after additional sealing the housing connection with the mounting surface, e.g. with silicone	IP65 - after additional sealing the housing connection with the mounting surface, e.g. with silicone	IP65	---	---	IP65 - after additional sealing the housing connection with the mounting surface, e.g. with silicone	IP65	IP65 - after additional sealing the housing connection with the mounting surface, e.g. with silicone	IP65 - after additional sealing the housing connection with the mounting surface, e.g. with silicone
IK rating	---	---	---	---	IK07	IK07	IK07	---	---	IK07	IK08	IK07	IK07
Main features	• Wi-Fi module - 2.4 GHz IEEE 802.11 b/g/n, • Protections : WEP 64/128-bit, WPA/WPA2, WPA-PSK/WPA2-PSK, • Echo suppression and reduction / digital noise reduction, • DND mode, • SOS support, • Microphone built-in, • Speakers built-in, • Bidirectional communication, • Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume, • The ability to automatically take and save photos if you do not answer to the bell button, • The ability to record a short video message in the absence of a response to the bell button, • IP Dahua cameras support	• Microphone built-in, • Speakers built-in, • Bidirectional communication, • Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume, • The ability to automatically take and save photos if you do not answer to the bell button, • The ability to record a short video message in the absence of a response to the bell button, • IP Dahua cameras support	• Wi-Fi module - 2.4 GHz IEEE 802.11 b/g/n, • Protections : WEP 64/128-bit, WPA/WPA2, WPA-PSK/WPA2-PSK, • Microphone built-in, • Speakers built-in, • Bidirectional communication, • Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume, • The ability to automatically take and save photos if you do not answer to the bell button, • The ability to record a short video message in the absence of a response to the bell button, • IP Dahua cameras support	• Wi-Fi module - 2.4 GHz IEEE 802.11 b/g/n, • Protections : WEP 64/128-bit, WPA/WPA2, WPA-PSK/WPA2-PSK, • Microphone built-in, • Speakers built-in, • Bidirectional communication, • Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume, • The ability to automatically take and save photos if you do not answer to the bell button, • The ability to record a short video message in the absence of a response to the bell button, • IP Dahua cameras support	• Microphone built-in, • Speakers built-in, • Bidirectional communication, • Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume, • The ability to automatically take and save photos if you do not answer to the bell button, • The ability to record a short video message in the absence of a response to the bell button, • IP Dahua cameras support	• Microphone built-in, • Speakers built-in, • Bidirectional communication, • Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume, • The ability to automatically take and save photos if you do not answer to the bell button, • The ability to record a short video message in the absence of a response to the bell button, • IP Dahua cameras support	• Wi-Fi module - 2.4 GHz IEEE 802.11 b/g/n, • Protections : WPA/WPA2, WPA-PSK/WPA2-PSK, • SOS support, • Microphone built-in, • Speakers built-in, • Bidirectional communication, • Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume, • Receive and view the published information from the management center, • DND mode	---	---	---	---	---	
Controlling	capacitive touch screen	capacitive touch screen	capacitive touch screen	capacitive touch screen	capacitive touch screen	capacitive touch screen	capacitive touch screen	---	---	---	---	---	---
Alarm inputs	6 (1 - as a bell)	6 (1 - as a bell)	6 (1 - as a bell)	6 (1 - as a bell)	6	6	6 (1 - as a bell)	---	---	---	---	---	---
Alarm outputs	1	1	1	1	1	1	1	---	---	---	---	---	---
Number of ports	---	---	---	---	1 x DAHUA 2-wire , 2 x DAHUA 2-wire - Uplink 2 x RJ-45	1 x DAHUA 2-wire , 1 x RJ-45	---	1 x DAHUA 2-wire , 1 x RJ-45	1 x DAHUA 2-wire - Uplink 2 x RJ-45	---	---	---	---
Compatibility	DAHUA	DAHUA	DAHUA	DAHUA	DAHUA DAHUA 2-wire doorphone installation DAHUA	DAHUA DAHUA 2-wire doorphone installation DAHUA	DAHUA	2-wire doorphone installation DAHUA	2-wire doorphone installation DAHUA	DAHUA	DAHUA	DAHUA	DAHUA
Material	---	---	---	---	Aluminum	Aluminum	Aluminum	---	---	---	---	---	---
Color	White	Black	Black	White	Silver White Silver	Silver White Silver	Silver White Silver	---	---	Silver	Graphite	Silver	Graphite
Main features	---	---	---	---	• SD memory cards up to 32GB support (possible local recording), • Doorbell button, • LED diodes, • Monitoring the status of individual doors, • WDR - 120 dB - Wide Dynamic Range, • 3D-DNR - Digital Noise Reduction, • Bidirectional communication, • Microphone built-in, • Speakers built-in, • Tamper detection - removing from mounting surface, • Possibility to connecting in cascade • Possibility to mount on a wall, or on the DIN TS-35 rail	• SD memory cards up to 32GB support (possible local recording), • LED diodes, • Door status detection, • WDR - 120 dB - Wide Dynamic Range, • 3D-DNR - Digital Noise Reduction, • Day/night mode, • Bidirectional communication, • Microphone built-in, • Speakers built-in, • Echo suppression and reduction / digital noise reduction, • Tamper detection - removing from mounting surface • SOS support ,	• LED indication • Possibility to connecting in cascade • Possibility to mount on a wall, or on the DIN TS-35 rail	• Possibility to connecting in cascade • Possibility to mount on a wall, or on the DIN TS-35 rail	• SD memory cards up to 32GB support (possible local recording), • Doorbell button, • LED diodes, • Monitoring the status of individual doors, • WDR - 120 dB - Wide Dynamic Range, • 3D-DNR - Digital Noise Reduction, • Bidirectional communication, • Microphone built-in, • Speakers built-in, • Noise suppression and echo cancellation, • Tamper detection - removing from mounting surface, • Power output 12 V DC / 100 mA	• The function of the monitor with the ability to open the door can be a smartphone, tablet or the VTH indoor panel, • Micro SD memory cards up to 256GB support (possible local recording), • Support up to 4 subscriber numbers, • Monitoring the status of individual doors, • WDR - 120 dB - Wide Dynamic Range, • 2D-DNR, 3D-DNR - Digital Noise Reduction, • Day/Night mode (color/b&w/aut), • ICR - Movable InfraRed filter, • Bidirectional communication, • Microphone built-in, • Speakers built-in, • Tamper detection - removing from mounting surface	• Bidirectional communication, • Microphone built-in, • Speakers built-in, • WDR - 120 dB - Wide Dynamic Range, • 3D-DNR - Digital Noise Reduction, • Power output : 12 V DC / 100 mA, • Tamper detection - removing from mounting surface ,	• Bidirectional communication, • Microphone built-in, • Speakers built-in, • WDR - 120 dB - Wide Dynamic Range, • 3D-DNR - Digital Noise Reduction, • Power output : 12 V DC / 100 mA, • Tamper detection - removing from mounting surface ,	
Internal dimensions	---	---	---	---	---	---	124 x 90 x 25 mm	---	---	---	---	---	---
Power supply	• 2-Wire IP interface • 48 V / 1.25 A	• PoE (802.3af), • 2-Wire IP interface	• 2-Wire IP interface, • 48 V DC / 1.25 A	• 2-Wire IP interface, • 48 V DC / 1.25 A	• PoE (802.3af), • 2-Wire IP interface • PoE (802.3af), • 2-Wire IP interface 48 V / 1 ... 3 A DC	• PoE (802.3af), • 2-Wire IP interface • PoE (802.3af), • 2-Wire IP interface 48 V DC / 1 ... 3 A	• 2-Wire interface • 48 V / 1.25 A • 2-Wire interface • 48 V / 1.25 A	48 V DC / 1.25 A (power adapter included)	48 V / 1 ... 3 A DC	• PoE (802.3af), • 2-Wire IP interface	• 48 V / 1 A, • PoE (802.3af), • 2-Wire IP interface	• PoE (802.3af), • 2-Wire IP interface	• PoE (802.3af), • 2-Wire IP interface

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Power consumption	≤ 6 W (operation) ≤ 2 W (standby)	≤ 6 W (operation) ≤ 2 W (standby)	• ≤ 6 W (operation) • ≤ 2 W (standby)	• ≤ 6 W (operation) • ≤ 2 W (standby)	≤ 12 W ≤ 6 W (operation) ≤ 2 W (standby) max. 144 W (at full load)	≤ 12 W ≤ 6 W (operation) ≤ 2 W (standby) max. 15 W (at full load)	≤ 6 W ≤ 6 W (operation) ≤ 2 W (standby)	max. 15 W (at full load)	max. 144 W (at full load)	≤ 12 W	≤ 4 W (Standby mode) ≤ 8 W (operation)	≤ 12 W	≤ 12 W
External dimensions	...	...	...	...	129 x 163 x 40 mm	129 x 163 x 40 mm	163 x 129 x 40 mm	...	...	...	...	...	...
Operation temp	-10 °C ... 55 °C	-10 °C ... 55 °C	-10 °C ... 55 °C	-10 °C ... 55 °C	-30 °C ... 60 °C -10 °C ... 55 °C -10 °C ... 55 °C	-30 °C ... 60 °C -10 °C ... 55 °C -10 °C ... 55 °C	-30 °C ... 60 °C -10 °C ... 55 °C	-10 °C ... 55 °C	-10 °C ... 55 °C	-30 °C ... 60 °C	-40 °C ... 60 °C	-30 °C ... 60 °C	-30 °C ... 60 °C
Input voltage	...	...	...	...	...	...	100 ... 240 V AC	...	...	...	...	...	...
AC input frequency	...	...	...	...	...	...	50 / 60 Hz	...	...	...	...	...	...
Output voltage	...	...	...	...	...	...	48.0 V DC	...	...	...	...	...	...
Output current	...	...	...	...	...	...	1.25 A	...	...	...	...	...	...
Output power	...	...	...	...	...	...	60.0 W	...	...	...	...	...	...
Connector	...	...	...	...	...	...	2.1/5.5 mm plug on the cable	...	...	...	...	...	...
LED indicators	...	...	...	...	...	...	—	...	...	...	...	...	...
Housing	...	...	...	...	Aluminum Metal	Aluminum Plastic (PC + ABS)	Aluminum Plastic (PC + ABS) Plastic	Plastic (PC + ABS)	Metal	Aluminum	Aluminum	Aluminum	Aluminum
Weight	0.33 kg	0.36 kg	0.36 kg	0.36 kg	0.33 kg 0.36 kg 0.5 kg 0.242 kg	0.33 kg 0.36 kg 0.5 kg 0.24 kg	0.33 kg 0.34 kg 0.5 kg 0.25 kg	0.24 kg	0.242 kg	0.33 kg	0.6 kg	0.28 kg	0.31 kg
Dimensions	190 x 135 x 26 mm	189 x 130 x 26 mm	189 x 130 x 26 mm	189 x 130 x 26 mm	130 x 96 x 28.5 mm 189 x 130 x 26 mm 131 x 103 x 40 mm	130 x 96 x 28.5 mm 189 x 130 x 26 mm 131 x 103 x 40 mm	130 x 96 x 40.5 mm 190 x 135 x 26 mm 125 x 47 x 32 mm	131 x 103 x 40 mm	131 x 103 x 40 mm	130 x 96 x 28.5 mm	• 188 x 107 x 30 mm (without cover) • 191 x 112 x 44 mm (with cover)	100 x 100 x 49.3 mm	100 x 100 x 49.3 mm
Supported languages	Polish, English	Polish, English	Polish, English	Polish, English	Polish, English Polish, English English, Bulgarian, Czech, Finnish, Polish, Slovenian, Slovak, Hungarian	Polish, English Polish, English English, Bulgarian, Czech, Finnish, Polish, Slovenian, Slovak, Hungarian	Polish, English	...	...	Polish, English	Polish, English	Polish, English	Polish, English
Manufacturer / Brand	DAHUA	DAHUA	DAHUA	DAHUA	DAHUA	DAHUA	DAHUA	DAHUA	DAHUA	DAHUA	DAHUA	DAHUA	DAHUA
Guarantee	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years