

	ANGLE TYPE BRACKET D5-B VIDEOS	ANGLE TYPE BRACKET D5-S VIDEOS	SWITCHING ADAPTER WITH SEPARATOR M- SEP/HD8-30-24 VIDEOS	SWITCHING ADAPTER P12-1118 VIDEOS	REMOTE CONTROL PL12 VIDOS	DESK STAND P100 VIDEOS	UNIVERSAL CONTROL MODULE 24V B5 VIDEOS	MULTIFUNCTIONAL MODULE M-3F VIDEOS	LAN COMMUNICATION MODULE M-LAN VIDEOS	MODULE M-SM1 VIDEOS DUO
										
	14.42 EUR 14.42 EUR	14.42 EUR 14.42 EUR	45.67 EUR 45.67 EUR	11.54 EUR 11.54 EUR	24.04 EUR 24.04 EUR	16.83 EUR 16.83 EUR	26.44 EUR 26.44 EUR	76.92 EUR 76.92 EUR	110.57 EUR 110.57 EUR	29.33 EUR 29.33 EUR
Number of relay outputs	...	...	...	...	...	...	1	...	...	...
Support	...	...	...	...	...	...	...	VIDOS DUO 2-wire Video Doorphones	...	VIDOS DUO 2-wire Video Doorphones
Material	Aluminum - powder painted	Aluminum - powder painted	...	...	...	Acrylic glass (plexiglass)	...	...	...	...
Adapter type	...	...	Switching	Switching	...	...	...	...	...	...
Interface	...	...	...	...	...	...	...	2-wire	...	2-wire
Compatibility	...	...	VIDOS DUO	...	...	...	...	...	VIDOS DUO - G24	...
Operation state indication	...	...	...	...	...	...	...	LED indication	...	LED indication
Relay maximal load	...	...	...	...	...	...	2 A / 24 V DC	...	...	...
Power voltage	...	...	85 ... 264 V AC	110 V ... 240 V AC	...	...	...	...	...	...
Assembly	...	...	...	...	...	...	...	DIN, TS-35 rail mounting	DIN, TS-35 rail mounting	DIN, TS-35 rail mounting
Output	...	...	...	...	...	...	1 x NO/NC	...	...	...
Output voltage	...	...	24 V DC	11 ... 16 V DC	...	240 x 136 x 111 mm	...	...	...	...
External dimensions	128 x 48 x 28 mm	128 x 48 x 28 mm	...	...	...	...	...	...	...	...
Output voltage adjustment	...	...	21.6 ... 29 V	✓	...	...	...	...	...	...
Application	S6 product series	S6 product series	...	...	S561A, S562A, S601A-2, S603A-2, S561Z, S601Z-2, ZS16, ZS600A	Internal VIDEOS video doorphone panels	...	...	...	...
Maximal load	...	...	1.5 A	950 mA	...	...	...	...	...	...
Output power	...	...	36 W	15 W	...	...	...	...	...	...
Number of outputs	...	...	4 pcs	1 pcs	...	...	...	...	...	...
Main features	...	...	...	...	...	...	• Wiring - 2 wires without polarity • Electric lock supply: 12V DC / max. 300mA • DIP SWITCH for configuration and addressing • Operation status LED indicator • Output for the additional lock release button or lighting control button • Possibility to mount on a wall, or on the DIN TS-35 rail	...	• The maximum number of modules in the system : 199 • The maximum number of gate stations in the system : 199 • The maximum number of subscribers in the system : 6368 • Possibility to mount on a wall, or on the DIN TS-35 rail	...
Housing type	...	...	DIN	DIN	...	...	...	...	...	...
Vibration resistance	...	...	✓	...	...	...	...	...	...	...
Protections	...	...	• Short-circuit • Overload • Overvoltage	...	...	...	...	...	...	...
Keyfob features	...	...	...	...	• Operation with proximity readers • Operation with fingerprint readers • Adding the users • Removing the users • Setting the opening time of the lock • Programming the Master card	...	...	...	...	...
Main features	...	...	...	...	...	...	• Repeater - Increasing the transmission range up to 300m • Router - Connecting more users : max. 32 / M-3F module, max. 8 max. 8 modules - max. 256 users (total) • Gateway - Possibility to connect a MASTER gate station	...	...	...
Color	Black	Silver	...	...	Black	Transparent	...	...	...	...
Power supply	...	...	...	...	2 x Battery type AAA - 1.5 V (included)	...	24 V DC	24 V DC	24 V DC	24 V DC
Power consumption	...	...	...	...	...	...	...	• 0.32 W (Standby mode) • 3.7 W (operation)	...	...
Weight	0.1 kg	0.1 kg	0.33 kg	0.06 kg	0.046 kg	0.232 kg	0.13 kg	0.2 kg	0.18 kg	0.13 kg
Dimensions	...	...	70 x 98 x 99 mm	18 x 90 x 58 mm	110 x 55 x 15 mm	...	89 x 71 x 45 mm	90 x 72 x 60 mm	90 x 72 x 61 mm	89 x 72 x 45 mm
Operation temp	...	...	10 °C ... 50 °C	...	...	...	...	10 ... 55 °C	...	...
Manufacturer / Brand	VIDOS	VIDOS	VIDOS	VIDOS	VIDOS	VIDOS	VIDOS	VIDOS	VIDOS	VIDOS DUO
Guarantee	3 years	3 years	2 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years