

	MULTIPLIER DC-915L TERRA	MULTIPLIER ZA-104MS	MULTIPLIER ZA-106AMS AMS	MULTIPLIER ZA-106MS AMS	MULTIPLIER ZA-112MS AMS	MULTIPLIER ZA-204MS AMS	MULTIPLIER ZA-F10 DIPOL	MULTIPLIER ZW-12A	MULTIPLIER ZWR-210DC	MULTIPLIER ZWR- TV/CORAB CORAB
										
	19.31 EUR 19.31 EUR	10.40 EUR 10.40 EUR	9.76 EUR 9.76 EUR	9.76 EUR 9.76 EUR	11.05 EUR 11.05 EUR	12.80 EUR 12.80 EUR	4.42 EUR 4.42 EUR	7.92 EUR 7.92 EUR	10.36 EUR 10.36 EUR	2.31 EUR 2.31 EUR
Isolation between inputs	...	...	...	...	...	...	...	...	...	> 20 dB
Input	• FM / VHF (III) : 47 ... 108 MHz - F socket, • VHF (III) : 174 ... 230 MHz - F socket • UHF : 470 ... 790 MHz + DC - F socket	• 1 - FM : 87 ... 110 MHz, • 2 - VHF : 174 ... 230 MHz, • 3 - UHF : 471 ... 694 MHz + DC	• FM : 87 ... 110 MHz - F socket, • VHF/UHF : 174 ... 694 MHz + DC - F socket	• VHF : 87 ... 230 MHz - F socket, • UHF : 471 ... 790 MHz + DC - F socket	• 1 - UHF : 471 ... 790 MHz + DC, • 2 - UHF : 471 ... 790 MHz, • 3 - VHF : 87 ... 230 MHz	• 1 - FM : 87 ... 110 MHz + DC, • 2 - VHF : 174 ... 230 MHz + DC, • 3 - UHF : 471 ... 790 MHz + DC	• 1 - FM / VHF : 5 ... 230 MHz, • 2 - UHF : 470 ... 790 MHz + DC	• 1 @ FM : 1 ... 5 + DC • 2 @ Channels : 6 ... 60 + DC	• FM / VHF : 5 ... 230 MHz + DC - F socket, • UHF : 470 ... 790 MHz + DC - F socket	• VHF : 47 ... 230 MHz - F socket, • UHF : 470 ... 790 MHz + DC - F socket
Impedance	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω @ UHF 300 Ω @ FM / VHF	75 Ω	75 Ω	75 Ω
Return loss	< 1 dB @ FM / VHF (III) < 1 dB @ VHF (III) < 2 dB @ UHF	≥ 40 dB	≥ 40 dB	≥ 40 dB	≥ 40 dB	≥ 40 dB	≥ 40 dB	> -20 dB	...	...
Insertion loss	< 1 dB @ FM / VHF (III) < 1 dB @ VHF (III) < 2 dB @ UHF	1 dB	1 dB	1 dB	1 dB @ VHF 4.5 dB @ UHF	1 dB	1.5 dB	1.5 dB	1 dB	< 1 dB
DC-transition	24 V / 250 mA	...	max. 24 V / 250 mA	...	...	...	...	...	12 V / 100 mA	30 V / 400 mA
Main features	• Built-in LTE filter • Isolation VHF, UHF > 20 dB • high screening efficiency	...	Built-in >700 MHz filter	...	...	...	...	...	It is possible to disable DC pass for each path using jumpers	Splash-proof casing
Housing	die-cast housing mounted inside compact plastic enclosure	Metal / PET	Metal - Shielded + Plastic	Metal / PET	Metal / PET	Metal / PET	---	PET	Metal / PET	Plastic (ABS)
Mount	The device housing can be easily installed to the walls using the screws and to the masts with a tie	To the mast	To the mast	To the mast	To the mast	To the mast	In antenna box	To the mast / from wall	To the mast	To the mast
Operation temp	-20 °C ... 50 °C	...	...	...	...	...	...	...	...	...
Weight	0.18 kg	0.1 kg	0.09 kg	0.09 kg	0.09 kg	0.09 kg	0.01 kg	...	0.110 kg	0.15 kg
Dimensions	107 x 89 x 43 mm	90 x 54 x 35 mm	90 x 54 x 34 mm	90 x 34 x 54 mm	90 x 34 x 54 mm	90 x 34 x 54 mm	42 x 42 x 12 mm	...	104 x 85 x 28 mm	114 x 85 x 45 mm
Manufacturer / Brand	TERRA	...	AMS	AMS	AMS	AMS	DIPOL	DELTA	...	CORAB
Guarantee	2 years	2 years	3 years	2 years	2 years	2 years	2 years	3 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00