

	OUTDOOR IR ILLUMINATOR IRL-30/120	OUTDOOR IR ILLUMINATOR IRL-30/90	OUTDOOR IR ILLUMINATOR IRL-50/90	OUTDOOR IR ILLUMINATOR IRL-60/90	OUTDOOR IR ILLUMINATOR IRL-CA32 IR LAB	OUTDOOR IR ILLUMINATOR IRL-CB32 IR LAB	OUTDOOR IR ILLUMINATOR IRL-CS32 IR LAB	OUTDOOR IR ILLUMINATOR 3N-80/60S2	OUTDOOR IR ILLUMINATOR 3N-130/60S2	OUTDOOR IR ILLUMINATOR IRL-CC88 IR LAB	OUTDOOR IR ILLUMINATOR IRL-IB88 IR LAB	OUTDOOR IR ILLUMINATOR IRL-IC88 IR LAB	OUTDOOR IR ILLUMINATOR IRL-IS88 IR LAB
													
	30.14 EUR 30.14 EUR	16.02 EUR 16.02 EUR	23.65 EUR 23.65 EUR	30.14 EUR 30.14 EUR	57.23 EUR 57.23 EUR	57.23 EUR 57.23 EUR	57.23 EUR 57.23 EUR	51.51 EUR 51.51 EUR	70.58 EUR 70.58 EUR	146.68 EUR 146.68 EUR	146.68 EUR 146.68 EUR	158.60 EUR 158.60 EUR	154.63 EUR 154.63 EUR
Range	30 m	30 m	50 m	60 m	45 m	55 m	25 m	80 m	130 m	110 m	120 m	180 m	60 m
Illumination angle	120 °	90 °	90 °	90 °	80 °	80 °	120 °	80 °	80 °	45 °	60 °	40 °	130 °
Housing	Aluminum	Aluminum	Aluminum, Color : Light gray	Aluminum	Aluminum - powder painted	Aluminum - powder painted	Aluminum - powder painted	Metal	Metal	Metal	Metal	Metal	Metal
Twilight switch	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Power supply	12 V DC / 1.67 A	12 V DC / 670 mA	12 V DC / 1.25 A	12 V DC / 1.67 A (power adapter not included)	• 12 V DC / 0.41 A • 24 V AC / 0.32 A	• 12 V DC / 0.41 A • 24 V AC / 0.32 A	• 12 V DC / 410 mA • 24 V AC / 320 mA	12 V DC / 1.1 A	12 V DC / 2.38 A	• 12 V DC / 1400 mA • 24 V AC / 1250 mA	• 12 V DC / 1.2 A • 24 V AC / 950 mA	• 12 V DC / 1.2 A • 24 V AC / 950 mA	• 12 V DC / 1.5 A • 24 V AC / 650 mA
Optical wavelength	850 nm	850 nm	850 nm	850 nm	850 nm	850 nm	850 nm	850 nm	850 nm	850 nm	850 nm	850 nm	850 nm
"Index of Protection"	IP65	IP65	IP65	IP65	IP66	IP66	IP66	IP66	IP66	IP66	IP66	IP66	IP66
Operation temp	-20 °C ... 70 °C	-20 °C ... 70 °C	-20 °C ... 70 °C	-20 °C ... 70 °C	-30 °C ... 40 °C	-30 °C ... 40 °C	-30 °C ... 40 °C	-20 °C ... 50 °C	-20 °C ... 50 °C	-30 °C ... 40 °C	-30 °C ... 40 °C	-30 °C ... 40 °C	-30 °C ... 40 °C
Weight	0.75 kg	0.39 kg	0.786 kg	0.806 kg	0.7 kg	0.7 kg	0.69 kg	0.69 kg	0.960 kg	2.03 kg	1.97 kg	2.0 kg	1.97 kg
Dimensions	180 x 140 x 94	114 x 85 x 74	180 x 140 x 94	180 x 140 x 94	205 x 90 x 77 mm	205 x 90 x 77 mm	205 x 90 x 37	150 x 105 x 197 mm	200 x 130 x 200 mm	Ø 157 x 228 mm	Ø 157 x 228 mm	Ø 157 x 228 mm	Ø 157 x 228 mm
Manufacturer / Brand	...	...	...	...	IR LAB	IR LAB	IR LAB	...	...	IR LAB	IR LAB	IR LAB	IR LAB
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years