

	CABLE CROSS-BNC/0.3M 0.3 m	CABLE CROSS-BNC/0.3MT 0.3 m	CABLE CROSS-BNC/0.3M- T*P50 0.3 m	CABLE CROSS- BNC/0.3M*P50 0.3 m	CABLE CROSS-BNC/0.8M 0.8 m	CABLE CROSS-BNC/0.8M- T*P10 0.8 m	CABLE CROSS- BNC/0.8M*P20 0.8 m	CABLE CROSS-BNC/1.5M 1.5 m	CABLE CROSS- BNC/1.5M*P20 1.5 m	CABLE CROSS-BNC/1.5MT 1.5 m	CABLE CROSS-BNC/1.5M- T*P10 1.5 m	CABLE CROSS-BNC/3M 3 m	CABLE CROSS-BNC/3M*P10 3.0 m	CABLE CROSS-BNC/5M 5 m	CABLE CROSS-BNC/5M*P10 5.0 m	CABLE CROSS-BNC/10M 10.0 m	CABLE CROSS-COMBO/10M 10.0 m	CABLE CROSS-COMBO/20M 20 m	CABLE CROSS-COMBO/5M 5.0 m	CABLE LINK-BNC/1.5M 1.5 m
																				
	0.95 EUR 0.95 EUR	1.09 EUR 1.09 EUR	49.26 EUR 49.26 EUR	42.70 EUR 42.70 EUR	1.18 EUR 1.18 EUR	11.33 EUR 11.33 EUR	21.23 EUR 21.23 EUR	1.58 EUR 1.58 EUR	28.53 EUR 28.53 EUR	1.36 EUR 1.36 EUR	12.24 EUR 12.24 EUR	1.78 EUR 1.78 EUR	16.01 EUR 16.01 EUR	2.48 EUR 2.48 EUR	22.33 EUR 22.33 EUR	5.61 EUR 5.61 EUR	9.64 EUR 9.64 EUR	8.01 EUR 8.01 EUR	6.63 EUR 6.63 EUR	1.09 EUR 1.09 EUR
In package	...	...	50 pcs The price for package	50 pcs The price for package	...	10 pcs The price for package	20 pcs The price for package	...	20 pcs The price for package	...	10 pcs The price for package	...	10 pcs The price for package	...	10 pcs The price for package	...	...	...	...	...
Supported standards	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	AHD / HD-CVI / HD-TVI - 8.3 Mpx 4K UHD (max), PAL	...	PAL	...
Coaxial cable																				
Cable	BNC plug / BNC plug	BNC plug / BNC plug	BNC plug / BNC plug	BNC plug / BNC plug	BNC Plug / BNC Plug	BNC plug / BNC plug	BNC Plug / BNC Plug	BNC plug / BNC plug	BNC Plug / BNC Plug	BNC plug / BNC plug	BNC plug / BNC plug	BNC Plug / BNC Plug	BNC Plug / BNC Plug	BNC Plug / BNC Plug	BNC Plug / BNC Plug	BNC Plug / BNC Plug	BNC Plug / BNC Plug	BNC plug / BNC socket	BNC plug / BNC plug	BNC Plug / BNC Socket
Power supply cable	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	2 x 0.35 mm² , 2.1/5.5 mm plug / 2.1/5.5 mm socket	2 x 0.35 mm² , 2.1/5.5 mm plug / 2.1/5.5 mm socket	2 x 0.35 mm² , 2.1/5.5 mm plug / 2.1/5.5 mm socket	...
Impedance	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω
Length of the cable	0.3 m	0.3 m	0.3 m	0.3 m	0.8 m	0.8 m	0.8 m	1.5 m	1.5 m	1.5 m	1.5 m	3 m	3.0 m	5 m	5.0 m	10.0 m	10.0 m	20 m	5.0 m	1.5 m
Main features	• Very easy and quick assembly • Very flexible, ideal for RACK cabinets usage	• Highly flexible, with a sheath diameter of only 3 mm, ideal for RACK cabinets usage • Very easy and quick assembly	• Highly flexible, with a sheath diameter of only 3 mm, ideal for RACK cabinets usage • Very easy and quick assembly	• Very easy and quick assembly • Very flexible, ideal for RACK cabinets usage	Very easy and quick assembly	• Highly flexible, with a sheath diameter of only 3 mm, ideal for RACK cabinets usage • Very easy and quick assembly	Very easy and quick assembly	• Very easy and quick assembly • Very flexible, ideal for RACK cabinets usage	• Very easy and quick assembly • Very flexible, ideal for RACK cabinets usage	• Highly flexible, with a sheath diameter of only 3 mm, ideal for RACK cabinets usage • Very easy and quick assembly	• Highly flexible, with a sheath diameter of only 3 mm, ideal for RACK cabinets usage • Very easy and quick assembly	Very easy and quick assembly	• Very easy and quick assembly • Very flexible, ideal for RACK cabinets usage	Very easy and quick assembly	• Very easy and quick assembly • Very flexible, ideal for RACK cabinets usage	• Very easy and quick assembly • Very flexible, ideal for RACK cabinets usage	• Very easy and quick assembly • Corrosion resistance • Very flexible, ideal for small CCTV installations • Designed for cameras with current consumption below 450mA At this current consumption, the power voltage for this length of the cable is lowered to 11V	• Very easy and quick assembly • Corrosion resistance • Very flexible, ideal for small CCTV installations • Designed for cameras with current consumption below 150mA At this current consumption, the power voltage for this length of the cable is lowered to 11V	• Very easy and quick assembly • Corrosion resistance • Very flexible, ideal for small CCTV installations • Designed for cameras with current consumption below 900mA At this current consumption, the power voltage for this length of the cable is lowered to 11V	• Very easy and quick assembly • Very flexible
Weight	0.02 kg	0.02 kg	0.02 kg	0.02 kg	0.03 kg	0.03 kg	0.03 kg	0.06 kg	0.032 kg	0.04 kg	0.04 kg	0.110 kg	0.11 kg	0.09 kg	0.13 kg	0.160 kg	0.334 kg	0.4 kg	0.190 kg	0.040 kg
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years