

	CONVERTER AV/HDMI	CONVERTER HDMI/AV	ADAPTER DP-W/HDMI-G	ADAPTER DP-W/HDMI-W-1.8M	ADAPTER DVI-W/HDMI-W-2.0M UNITEK	CONVERTER HDMI/VGA+AU-ECO	CONVERTER HDMI/VGA+AU-ECO-3	ADAPTER MDP-W/HDMI-G	ADAPTER USB-C/HDMI	CONVERTER VGA+AU/HDMI-ECO
										
	8.80 EUR 8.80 EUR	8.03 EUR 8.03 EUR	5.26 EUR 5.26 EUR	5.91 EUR 5.91 EUR	5.51 EUR 5.51 EUR	6.62 EUR 6.62 EUR	6.48 EUR 6.48 EUR	5.25 EUR 5.25 EUR	18.74 EUR 18.74 EUR	8.11 EUR 8.11 EUR
Connectors	...	...	...	...	DVI - plug HDMI - plug	...	...	...	...	...
Inputs	Composite Video (CVBS) - 1 pcs CINCH Audio - 2 pcs Cinch (L/R)	1 pcs HDMI	DisplayPort - plug	DisplayPort - plug	...	HDMI	HDMI	Mini DisplayPort plug	USB-C - plug	• VGA, • Audio (Jack stereo socket)
Outputs	1 pcs HDMI	Composite Video (CVBS) - 1 pcs CINCH Audio - 2 pcs Cinch (L/R)	HDMI - socket	HDMI - plug	...	• VGA, • Audio (Jack stereo socket)	• VGA, • Audio (Jack stereo socket)	HDMI socket	HDMI - socket	HDMI
Supported HDMI input resolutions	...	...	...	...	...	720p 1080p	480p 576p 720p 1080p	...	...	...
DisplayPort standard	...	...	1.2	1.2	...	...	...	1.1a	...	...
Bandwidth	...	...	...	...	...	...	...	max. 225 MHz	...	...
Bitrate	...	...	≤ 17.28 Gb/s Video ≤ 21.6 Gb/s TDMs	≤ 17.28 Gb/s Video ≤ 21.6 Gb/s TDMs	≤ 18 Gb/s Video	...	...	≤ 6.75 Gb/s Video ≤ 10.8 Gb/s TDMs	...	...
Number of displayed colors	...	...	48 bpp	48 bpp	...	...	...	36 bpp	...	...
Supported VGA output resolutions	...	...	...	...	...	1600 x 1200 1920 x 1080	640 x 480 800 x 600 1024 x 768 1280 x 720 1280 x 800 1280 x 1024 1400 x 1050 1440 x 900 1600 x 1200 1680 x 1050 1920 x 1080	...	...	...
Audio support	...	...	8 Channels / 768 kHz / 24 bit	8 Channels / 768 kHz / 24 bit	...	...	...	8 Channels / 192 kHz / 24 bit	✓	...
Manufacturer / Brand	...	...	...	...	UNITEK	...	...	...	...	...
Main features	...	...	• Plug & Play • Standby mode detection • Standby mode enter into sleep mode automatically	• Plug & Play • Standby mode detection • Standby mode enter into sleep mode automatically	...	...	...	• Plug & Play • Standby mode detection • Standby mode enter into sleep mode automatically	• Plug & Play, • Operation modes : Mirror, Extend, • HDR support	...
Color	...	...	...	...	...	...	Device is available in two versions depending on delivery (it is not subject to selection) : Black or White	...	...	...
Supported resolutions	• PAL / NTSC - Composite Video (CVBS) • 720p @ 60, 1080p @ 60 HDMI	• HDMI : 3840 x 2160 4K @ 30 Hz, 2560 x 1440 @ 30 Hz, 1920 x 1080 @ 50/60 Hz, 1600 x 1200 @ 60 Hz, 1280 x 1024 @ 60 Hz, 1360 x 768 @ 50/60 Hz, 1024 x 768 @ 60 Hz, 1280 x 720 @ 50/60 Hz • Composite Video (CVBS) : PAL / NTSC	max. 4K UHD	max. 4K UHD	max. 4K UHD - DVI to HDMI conversion max. 1080p - HDMI to DVI conversion	...	480i 480p 576i 576p 720p 1080p	max. 4K UHD @ 60 Hz	...	...
Supported VGA input resolutions	...	...	...	...	...	...	...	...	...	1024 x 768 @ 60 / 70 / 75 / 85 Hz 1152 x 864 @ 75 Hz 1280 x 720 @ 60 Hz 1280 x 768 @ 60 Hz 1280 x 800 @ 60 Hz 1280 x 960 @ 60 Hz 1280 x 1024 @ 60 Hz 1360 x 768 @ 60 Hz 1440 x 900 @ 60 Hz 1600 x 1200 @ 60 Hz 1680 x 1050 @ 60 Hz 1920 x 1080 @ 60 Hz
Supported HDMI output resolutions	...	...	...	...	...	...	...	...	...	1024 x 768 @ 60 / 70 / 75 / 85 Hz 1152 x 864 @ 75 Hz 1280 x 720 @ 60 Hz 1280 x 768 @ 60 Hz 1280 x 800 @ 60 Hz 1280 x 960 @ 60 Hz 1280 x 1024 @ 60 Hz 1360 x 768 @ 60 Hz 1440 x 900 @ 60 Hz 1440 x 1050 @ 60 Hz 1680 x 1050 @ 60 Hz 1600 x 1200 @ 60 Hz 1920 x 1080 @ 60 Hz
HDCP	---	---	---	---	---	---	---	---	---	---
Maximal range of HDMI transmission	...	...	...	...	...	...	...	...	...	15 m
Power supply	5 V DC from USB port	5 V DC from USB port (optional)	5 V DC - from HDMI port	5 V DC - from HDMI port	...	5 V DC (power adapter not included)	5 V DC - from HDMI port	5 V DC - from HDMI port	5 V DC - from USB-C port	5 V DC - mini USB socket (power adapter not included)
Weight	0.04 kg	0.04 kg	0.026 kg	0.06 kg	0.150 kg	0.01 kg	0.036 kg	0.024 kg	0.012 kg	0.085 kg
Dimensions	68 x 56 x 20 mm	68 x 56 x 20 mm	49 x 20 x 12 mm - DisplayPort plug 45 x 22 x 12 mm - HDMI socket ~ 15 cm (cable length)	49 x 20 x 12 mm - DisplayPort plug 55 x 22 x 12 mm - HDMI socket ~ 180 cm (cable length)	53 x 39 x 14 mm - DVI plug 47 x 18 x 12 mm - HDMI plug ~ 200 cm (cable length)	55 x 25 x 17 mm	45 x 45 x 15 mm	45 x 45 x 15 mm ~ 18 cm (cable length)	69 x 26 x 16 mm	64 x 55 x 20 mm
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00