

	POWER DISTRIBUTION UNIT L19BVP	POWER DISTRIBUTION UNIT PD-6-ERACK	POWER DISTRIBUTION UNIT L19B7E	POWER DISTRIBUTION UNIT PD-6E	POWER DISTRIBUTION UNIT PD-6R-1P 1.8 m	POWER DISTRIBUTION UNIT PD-6R-2P 1.8 m	POWER DISTRIBUTION UNIT PD-6R-OP	POWER DISTRIBUTION UNIT PD-6R-SPD-1L	POWER DISTRIBUTION UNIT PD-6R-SPD-3L	POWER DISTRIBUTION UNIT PD-6R-USB	POWER DISTRIBUTION UNIT PD-6R-VA	POWER DISTRIBUTION UNIT PD-7RACK	POWER DISTRIBUTION UNIT PD-8R	POWER DISTRIBUTION UNIT PD-8R-IEC 1.8 m	POWER DISTRIBUTION UNIT PD-8R/IEC-N 1.8 m	POWER DISTRIBUTION UNIT PD-9R	POWER DISTRIBUTION UNIT PD-9R-IEC 1.8 m	POWER DISTRIBUTION UNIT L19B	POWER DISTRIBUTION UNIT PD-7R-N 1.8 m	POWER DISTRIBUTION UNIT PD-8RACK-N	POWER DISTRIBUTION UNIT PD-4R1P	POWER DISTRIBUTION UNIT PD-4R10R 1.8 m	POWER DISTRIBUTION UNIT PD-7RACKIEC	POWER DISTRIBUTION UNIT PD-8RACK	POWER DISTRIBUTION UNIT PD-8RACKIEC	POWER DISTRIBUTION UNIT PD-7RACK	POWER DISTRIBUTION UNIT PD-8RACK	POWER DISTRIBUTION UNIT PD-8RACK	
																													
Rated voltage	19.44 EUR 230 V AC / 50 Hz	16.51 EUR 230 V AC / 50 Hz	22.11 EUR 230 V AC / 50 Hz	16.01 EUR 230 V AC / 50 Hz	18.68 EUR 230 V AC / 50 Hz	22.49 EUR 230 V AC / 50 Hz	17.54 EUR 230 V AC / 50 Hz	18.68 EUR 230 V AC / 50 Hz	21.35 EUR 230 V AC / 50 Hz	24.78 EUR 230 V AC / 50 Hz	49.18 EUR 230 V AC / 50 Hz	17.50 EUR 230 V AC / 50 Hz	17.54 EUR 230 V AC / 50 Hz	17.54 EUR 230 V AC / 50 Hz	20.59 EUR 230 V AC / 50 Hz	17.16 EUR 230 V AC / 50 Hz	17.92 EUR 230 V AC / 50 Hz	20.59 EUR 230 V AC / 50 Hz	19.04 EUR 230 V AC / 50 Hz	16.78 EUR 230 V AC / 50 Hz	14.28 EUR 230 V AC / 50 Hz	15.25 EUR 230 V AC / 50 Hz	18.78 EUR 230 V AC / 50 Hz	22.73 EUR 230 V AC / 50 Hz	20.40 EUR 230 V AC / 50 Hz	19.83 EUR 230 V AC / 50 Hz	22.21 EUR 230 V AC / 50 Hz	28.44 EUR 230 V AC / 50 Hz	
Total maximal current	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	10 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A
Maximal total load	3500 W	3680 W	3500 W	3680 W	3680 W	3680 W	3680 W	3680 W	3680 W	3680 W	3680 W	3680 W	3680 W	3680 W	2500 W	3680 W	3680 W	3500 W	4000 W	4000 W	3500 W	3680 W	3680 W	3680 W	3680 W	3680 W	3680 W	3680 W	
Number of outlets	6 for universal plug 230 V (Schuko)	6 for universal plug 230 V (DIN 49441)	7 for universal plug 230 V (Schuko)	6 x CEE 7/5	6 x CEE 7/5	6 x CEE 7/5	6 x CEE 7/5	6 x CEE 7/5	6 x CEE 7/5	6 x CEE 7/5	6 x CEE 7/5	7 x CEE 7/5	8 x CEE 7/5	8 x CEE 7/5	8 x CEE 7/5	9 x CEE 7/5	9 x CEE 7/5	8 for universal plug 230 V (Schuko)	7 x CEE 7/5	8 for universal plug 230 V (Schuko)	4 x CEE 7/5	7 x CEE 7/5	8 for universal plug 230 V (DIN 49441)	7 x CEE 7/5	8 for universal plug 230 V (DIN 49441)	7 x CEE 7/5	8 for universal plug 230 V (DIN 49441)	9 for universal plug 230 V (DIN 49441)	
Assembly	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets
Length of the power cable	1.8 m	2.15 m	1.8 m	1.8 m cable with power connector CEE 7/7	1.8 m cable with power connector CEE 7/7	1.8 m, cable with power connector CEE 7/7	1.8 m cable with power connector CEE 7/7	1.8 m cable with power connector CEE 7/7	1.8 m cable with power connector CEE 7/7	1.8 m cable with power connector CEE 7/7	1.8 m cable with power connector CEE 7/7	2 m	1.8 m cable with power connector CEE 7/7	1.8 m - cable with power connector IEC320 C14	1.8 m - cable with power connector IEC320 C14	1.8 m cable with power connector CEE 7/7	1.8 m - cable with power connector IEC320 C14	1.8 m	1.8 m - cable with power connector CEE 7/7	1.8 m	1.8 m	1.8 m - cable with power connector CEE 7/7	2 m - cable with power connector IEC320 C14	2 m	2 m - cable with power connector IEC320 C14	2 m	2 m	3 m	
Nominal voltage of surge suppressor	—	—	—	—	—	—	250 V / 50 Hz	250 V / 50 Hz	250 V / 50 Hz	—	—	250 V / 50 Hz	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	250 V / 50 Hz	
Protection level of surge suppressor	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	≤ 1.3 kV (L/N)	
Housing type	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U Rack 10"	1 U Rack 10"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	
Switch	Yes (with built-in LED indicator)	two-way, with light indication	Yes (with built-in LED indicator)	two-way, with light indication	—	—	two-way, with light indication	two-way, with light indication	two-way, with light indication	two-way, with light indication	two-way, with light indication	two-way, with light indication	two-way, with light indication	two-way, with light indication	—	—	two-way, with light indication	Yes (with built-in LED indicator and protected by a cover)	Yes (with built-in LED indicator and protected by a cover)	Yes (with built-in LED indicator and protected by a cover)	Yes (with built-in LED indicator)	Yes (with built-in LED indicator)	—	Yes (with built-in LED indicator)	—	Yes (with built-in LED indicator)	Yes (with built-in LED indicator)	—	
Main features	• Overvoltage protection • LED indicators displaying the device's operating status	—	Overload protection	—	Circuit Breaker : 16 A, C type, 1P	Circuit Breaker, 16 A, C type, 2P	Overvoltage protection - Switch disconnecter with fuse	• Overvoltage protection	• Signaling a lack of grounding • Overvoltage protection • AC input voltage presence indication	2 x USB socket : 5 V / 3 A	• Supply voltage measurement, • Supply current measurement	—	—	—	—	—	—	—	—	—	—	• Current paths shutters	—	—	—	—	—	—	
Weight	0.75 kg	0.830 kg	0.8 kg	0.74 kg	0.83 kg	0.91 kg	0.76 kg	0.76 kg	0.78 kg	0.68 kg	0.78 kg	0.72 kg	0.78 kg	0.75 kg	0.75 kg	0.77 kg	0.75 kg	0.74 kg	0.74 kg	0.72 kg	0.510 kg	0.52 kg	0.69 kg	0.830 kg	0.700 kg	0.35 kg	0.830 kg	0.85 kg	
Dimensions	482 x 45 x 54 mm	530 x 75 x 55 mm	484 x 45 x 56 mm	483 x 45 x 50 mm	483 x 44 x 84 mm	483 x 45 x 85 mm	483 x 45 x 54 mm	483 x 44 x 54 mm	483 x 45 x 54 mm	483 x 45 x 55 mm	483 x 45 x 54 mm	483 x 44 x 54 mm	483 x 45 x 44 mm	483 x 45 x 54 mm	481 x 45 x 45 mm	483 x 44 x 45 mm	483 x 45 x 44 mm	484 x 45 x 57 mm	480 x 45 x 51 mm	484 x 46 x 51 mm	257 x 45 x 55 mm	482 x 46 x 44 mm	530 x 75 x 55 mm	482 x 46 x 44 mm	450 x 45 x 44 mm	450 x 45 x 44 mm	450 x 45 x 44 mm	448 x 45 x 45 mm	
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	