

	CRIMP PLUG BNC-WZAC- H155	CRIMP PLUG BNC-WZAC- RG58	CRIMP PLUG BNC- W/CBIMP-RG59*P10	CRIMP PLUG BNC- W/RIMP-RG59*P100	CRIMP PLUG BNC-WZAC- RG59*P25	CRIMP PLUG BNC-WZAC- RG6*P10	CRIMP PLUG BNC-WZAC- RG6*P100	CRIMP PLUG BNC- W75ZAC-RG59*P10	CRIMP PLUG BNC- W75ZAC-RG59*P100	RUBBER BUSH BNC-WP*P10
	0.76 EUR 0.76 EUR	0.67 EUR 0.67 EUR	4.21 EUR 4.21 EUR	33.67 EUR 33.67 EUR	7.21 EUR 7.21 EUR	2.87 EUR 2.87 EUR	22.96 EUR 22.96 EUR	3.67 EUR 3.67 EUR	29.34 EUR 29.34 EUR	1.10 EUR 1.10 EUR
In package	...	...	10 pcs The price for package	100 pcs The price for package	25 pcs The price for package	10 pcs The price for package	100 pcs The price for package	10 pcs The price for package	100 pcs The price for package	10 pcs The price for package
Type	BNC Straight plug	BNC Straight plug	BNC Straight plug	BNC Straight plug	BNC Straight plug	BNC Straight plug	BNC Straight plug	BNC Straight plug	BNC Straight plug	Bush
Connector type	BNC Straight plug	BNC Straight plug	BNC Straight plug	BNC Straight plug	BNC Straight plug	BNC Straight plug	BNC Straight plug	BNC Straight plug	BNC Straight plug	...
Attachment of connector elements	Crimping	Crimping	Crimping	Crimping	Crimping	Crimping	Crimping	Crimping	Crimping	Pressed
Shield fastening	Crimping	Crimping	Crimping	Crimping	Crimping	Crimping	Crimping	Crimping	Crimping	...
Wire mounting	Crimping	Crimping	Pressing	Pressing	Crimping / Soldering	Crimping	Crimping	Crimping - Gold-plated connector prevents the oxidation of contacts	Crimping - Gold-plated connector prevents the oxidation of contacts	...
Application	Coaxial cable	Coaxial cable	Coaxial cable	Coaxial cable	Coaxial cable	Coaxial cable	Coaxial cable	Coaxial cable	Coaxial cable	Coaxial cable
Cable diameter	max. 6.1 mm	max. 5.0 mm	max. 7.0 mm	max. 7.0 mm	max. 5.9 mm	max. 7.0 mm	max. 7.0 mm	max. 5.9 mm	max. 5.9 mm	max. 7.2 mm
Impedance	50 Ω	50 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	...
Material	Metal	Metal	Metal	Metal	Metal	Metal	Metal	Metal	Metal	Rubber
Example of application	• TRI-LAN/100 • H-155	• RG58	• RG59 • YWDX	• RG59 • YWDX	• RG59 • YWDX	• RG6 • HFEK • Triset113	• RG6 • HFEK • Triset113	• RG59 • YWDX	• RG59 • YWDX	...
Main features	• Wide frequency range • Corrosion resistance • To crimp use the crimping tool HT-301C	• Wide frequency range • Corrosion resistance • To crimp use the crimping tool HT-301C	• Wide frequency range • Corrosion resistance	• Wide frequency range • Corrosion resistance	• Wide frequency range • Corrosion resistance	• Wide frequency range • Corrosion resistance	• Wide frequency range • Corrosion resistance	• Wide frequency range • Corrosion resistance	• Wide frequency range • Corrosion resistance	Protects against weather conditions
Weight	0.010 kg	0.010 kg	0.007 kg	0.007 kg	0.007 kg	0.007 kg	0.007 kg	0.007 kg	0.007 kg	0.002 kg
Dimensions	Ø 14 mm x 30 mm	Ø 14 mm x 30 mm	Ø 14 mm x 30 mm	Ø 14 mm x 30 mm	Ø 14 mm x 28 mm	Ø 14 mm x 30 mm	Ø 14 mm x 30 mm	Ø 14 mm x 30 mm	Ø 14 mm x 30 mm	Ø 11 mm x 44 mm
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00