	POWER SUPPLY ADAPTER 12V/0.5A/TRF	SWITCHING ADAPTER 12V/1A/5.5	SWITCHING ADAPTER 12V/1A/5.5*P100	SWITCHING ADAPTER 12V/300MA/J-ESPE	SWITCHING ADAPTER ADS-12FG-12N Hikvision	SWITCHING ADAPTER TT-12V/4A FOR TELMOR MULTISWITCHES	POWER SUPPLY ADAPTER 12V/1.25A/5.5	POWER SUPPLY ADAPTER 12V/1.5A/5.5	POWER SUPPLY ADAPTER 12V/1.5A/5.5*P100	POWER SUPPLY ADAPTER 12V/2A/5.5	POWER SUPPLY ADAPTER 12V/2A/5.5*P100	POWER SUPPLY ADAPTER PFM320D-EN DAHUA	POWER SUPPLY ADAPTER PFM321D-EN DAHUA	SWITCHING ADAPTER 3-12V/1.2A/BL	SWITCHING ADAPTER 3-12V/2.5A/TAY	SWITCHING ADAPTER 3-12V/2A/BL USB	POWER SUPPLY ADAPTER 12V/3A/5.5	POWER SUPPLY ADAPTER 12V/3A/5.5*P100	POWER SUPPLY ADAPTER 12V/4A/5.5	POWER SUPPLY ADAPTER AI-9/PS FOR AI-9 FIBER FUSION SPLICER	POWER SUPPLY ADAPTER 12V/5A/5.5	POWER SUPPLY ADAPTER 12V/5A/5.5*P50	POWER SUPPLY ADAPTER 12V/10A/5.5-TAY
																							
	6.32 EUR 6.32 EUR	4.02 EUR 4.02 EUR	361.49 EUR 361.49 EUR	5.74 EUR 5.74 EUR	7.90 EUR 7.90 EUR	26.66 EUR 26.66 EUR	3.89 EUR 3.89 EUR	5.02 EUR 5.02 EUR	452.22 EUR 452.22 EUR	5.08 EUR 5.08 EUR	456.77 EUR 456.77 EUR	18.19 EUR 18.19 EUR	10.53 EUR 10.53 EUR	8.13 EUR 8.13 EUR	7.97 EUR 7.97 EUR	10.91 EUR 10.91 EUR	8.31 EUR 8.31 EUR	748.11 EUR 748.11 EUR	8.77 EUR 8.77 EUR	37.00 EUR 37.00 EUR	11.41 EUR 11.41 EUR	513.62 EUR 513.62 EUR	33.93 EUR 33.93 EUR
In package	..	..	**100 pcs The price for package**	..	..	..	..	..	**100 pcs The price for package**	..	**100 pcs The price for package**	..	..	..	..	..	..	**100 pcs The price for package**	..	..	..	**50 pcs The price for package**	..
Model identifier	12V/0.5A/TRF	12V/1A/5.5	12V/1A/5.5*P100	12V/300MA/J-ESPE	ADS-12FG-12N	TT-12V/4A	12V/1.25A/5.5	12V/1.5A/5.5	12V/1.5A/5.5*P100	12V/2A/5.5	12V/2A/5.5*P100	PFM320D-EN	PFM321D-EN	3-12V/1.2A/BL	3-12V/2.5A/TAY	3-12V/2A/BL	12V/3A/5.5	12V/3A/5.5*P100	12V/4A/5.5	AI-9/PS	12V/5A/5.5	12V/5A/5.5*P50	12V/10A/5.5-TAY
Input voltage	200 - 240 V AC	100 - 240 V AC	100 - 240 V AC	100 - 240 V AC	100 - 240 V AC	100 - 240 V AC	100 - 240 V AC	100 - 240 V AC	100 - 240 V AC	100 - 240 V AC	100 - 240 V AC	100 - 230 V AC	100 - 240 V AC	100 ... 240 V AC	100 ... 240 V AC	100 ... 240 V AC	100 - 240 V AC	100 - 240 V AC	100 - 240 V AC	100 - 240 V AC	100 - 240 V AC	100 - 240 V AC	230 V AC
AC input frequency	50 Hz	50 / 60 Hz	50 / 60 Hz	47 ... 63 Hz	47 ... 63 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	47 ... 63 Hz
Output voltage	12.0 V DC	12.0 V DC	12.0 V DC	12.0 V DC	12.0 V DC	12 V DC	12.0 V DC	12.0 V DC	12.0 V DC	12.0 V DC	12.0 V DC	12.0 V DC	12.0 V DC	3.0 V, 4.5 V, 6.0 V, 7.5 V, 9.0 V, 12.0 V DC	3.0 V, 4.5 V, 6.0 V, 7.5 V, 9.0 V, 12.0 V DC	3.0 V, 4.5 V, 5.0 V, 6.0 V, 7.5 V, 9.0 V, 12.0 V DC	12.0 V DC	12.0 V DC	12.0 V DC	13.5 V DC	12.0 V DC	12.0 V DC	12.0 V DC
Average efficiency during work	78.9 %	83.0 %	83.0 %	75.6 %	82.96 %	..	84.1 %	85.0 %	85.0 %	86.2 %	86.2 %	..	..	..	..	..	87.4 %	87.4 %	87.8 %	..	88.0 %	88.0 %	..
Efficiency at low load (10%)	20.4 %	67.1 %	67.1 %	..	..	..	65.2 %	74.7 %	74.7 %	66.8 %	66.8 %	..	..	..	..	..	81.0 %	81.0 %	84.5 %	..	84.1 %	84.1 %	..
No-load power consumption	< 0.10 W	< 0.10 W	< 0.10 W	0.1 W	< 0.10 W	..	< 0.10 W	< 0.10 W	< 0.1 W	< 0.10 W	< 0.10 W	..	..	..	..	..	< 0.10 W	< 0.10 W	< 0.10 W	..	< 0.21 W	< 0.21 W	..
Output current	0.5 A	1.0 A	1.0 A	0.3 A	1.0 A	4 A	1.25 A	1.5 A	1.5 A	2.0 A	2.0 A	2.0 A	1.0 A	max. 1.2 A	max. 2.5 A	max. 2.0 A @ DC , max. 1.2 A @ USB	3.0 A	3.0 A	4.0 A	4.8 A	5.0 A	5.0 A	10.0 A
Output power	6.0 W	12.0 W	12.0 W	3.6 W	12.0 W	48 W	15.0 W	18.0 W	18.0 W	24.0 W	24.0 W	24.0 W	12.0 W	15.0 W	30.0 W	30.0 W	36.0 W	36.0 W	48.0 W	65 W	60.0 W	60.0 W	120.0 W
Adapter type	Transforming	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching
Output voltage adjustment	–	–	–	–	–	–	–	–	–	–	–	–	–	✓	✓	✓	–	–	–	–	–	–	–
Protections	..	Overload	Overload	• Short-circuit • Overcurrent (overload) - automatic return to normal operation after the failure has ceased • Overvoltage	Overload	..	Overload	Overload	Overload	Overload	Overload	..	..	Overvoltage	..	Overvoltage	Overload	Overload	Overload	Overload	Overload	Overload	..
SAP Code	..	..	..	..	101701320	..	..	..	..	..	..	..	..	..	..	..	..	..	..	..	..	..	..
Number of outputs	1 pcs	1 pcs	1 pcs	1 pcs	1 pcs	1 pcs	1 pcs	1 pcs	1 pcs	1 pcs	1 pcs	1 pcs	1 pcs	1 pcs	1 pcs	1 pcs	1 pcs	1 pcs	1 pcs	1 pcs	1 pcs	1 pcs	1 pcs
Manufacturer / Brand	..	..	..	..	Hikvision	TELMOR	..	..	..	..	..	DAHUA	DAHUA	..	..	..	..	..	..	..	..	..	..
Power connectors type	• 230 V Plug • 12 V - 2.1/5.5 mm Straight plug	• 230 V Plug • 12 V - 2.1/5.5 mm Straight plug	• 230 V Plug • 12 V - 2.1/5.5 mm Straight plug	• 230 V Plug • 12 V - Jack 3.5 mm - Angular plug	• 230 V Plug • 12 V - 2.1/5.5 mm Straight plug	• 230 V : Plug • 12 V - 2.1/5.5 mm plug on the cable	• 230 V Plug • 12 V - 2.1/5.5 mm Straight plug	• 230 V Plug • 12 V - 2.1/5.5 mm Straight plug	• 230 V Plug • 12 V - 2.1/5.5 mm Straight plug	• 230 V CEE 7/16 • 12 V - 2.1/5.5 mm Straight plug	• 230 V CEE 7/16 • 12 V - 2.1/5.5 mm Straight plug	• 230 V CEE 7/16 • 12 V - 2.1/5.5 mm Straight plug	• 230 V CEE 7/16 • 12 V - 2.1/5.5 mm Straight plug	• AC : 230 V CEE 7/16 • DC - Angular plug : Replaceable plug tips - 7 pcs (2.5/0.7mm, 3.0/1.0mm, 3.5/1.3mm, 4.0/1.7mm, 5.0/1.7mm, 5.5/2.1mm, 5.5/2.5mm) The possibility of changing the polarity by inserting the plug appropriately	• AC : 230 V CEE 7/16 • DC - Angular plug : Replaceable plug tips - 6 pcs (2.5/0.7mm, 3.5mm, 3.5/1.3mm, 4.0/1.7mm, 5.5/2.5mm, 6.3/3.0mm)	• AC : 230 V CEE 7/16 • DC - Angular plug : Replaceable plug tips - 7 pcs (2.5/0.7mm, 3.0/1.0mm, 3.5/1.3mm, 4.0/1.7mm, 5.0/1.7mm, 5.5/2.1mm, 5.5/2.5mm) The possibility of changing the polarity by inserting the plug appropriately • USB-A : 5 V / 1.2 A	• 230 V CEE 7/16 • 12 V - 2.1/5.5 mm Straight plug	• 230 V CEE 7/16 • 12 V - 2.1/5.5 mm Straight plug	• 230 V CEE 7/16 • 12 V - 2.1/5.5 mm Straight plug	• 230 V IEC C14 • 13.5 V - 2.1/5.5 mm Straight plug	• 230 V CEE 7/16 • 12 V - 2.1/5.5 mm Straight plug	• 230 V CEE 7/16 • 12 V - 2.1/5.5 mm Straight plug	12 V - 2.1/5.5 mm Straight plug
Housing type	Desktop	Casing with plug	Casing with plug	Casing with plug	Casing with plug	Casing with plug	Casing with plug	Casing with plug	Casing with plug	Desktop	Desktop	Desktop	Desktop	Casing with plug	Casing with plug	Casing with plug	Desktop	Desktop	Desktop	Desktop	Desktop	Desktop	Desktop
Length of the cable	..	1 m	1 m	1.45 m	1 m	1.5 m	1 m	1 m	1 m	..	..	..	..	1.2 m	0.65 m	1.2 m	..	..	..	..	..	..	..
Weight	0.480 kg	0.125 kg	0.125 kg	0.06 kg	0.08 kg	0.16 kg	0.12 kg	0.14 kg	0.14 kg	0.172 kg	0.172 kg	0.17 kg	0.1 kg	0.092 kg	0.092 kg	0.128 kg	0.26 kg	0.26 kg	0.31 kg	0.21 kg	0.34 kg	0.34 kg	0.49 kg
Dimensions	85 x 58 x 50 mm	80 x 55 x 75 mm	80 x 55 x 75 mm	60 x 39 x 64 mm	31 x 68 x 78 mm	83 x 49 x 70 mm	..	..	..	91 x 53 x 31 mm	91 x 53 x 31 mm	..	..	83 x 55 x 70 mm	85 x 50 x 70 mm	85 x 50 x 72 mm	110 x 50 x 30 mm	110 x 50 x 30 mm	120 x 55 x 38 mm	120 x 55 x 38 mm	121 x 57 x 36 mm	121 x 57 x 36 mm	..
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	3 years	3 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00