

	POWER SUPPLY ADAPTER RACK 15-PSD1018U 12 V DC 10 A	POWER SUPPLY ADAPTER RACK 15-PSD2018U 12 V DC 20 A	POWER SUPPLY ADAPTER RACK ZR12-100 12 V DC 8.5 A	POWER SUPPLY ADAPTER RACK ZR12-100I2-8P 12 V DC 8.5 A	POWER SUPPLY ADAPTER RACK ZR12-100X2 2 x 12 V DC 2 x 8.5 A	POWER SUPPLY ADAPTER RACK ZR12-150 12 V DC 12.5 A	POWER SUPPLY ADAPTER RACK ZR12-150I2 12 V DC 12.5 A	POWER SUPPLY ADAPTER RACK ZR12-150I2-12 12 V DC 12.5 A	POWER SUPPLY ADAPTER RACK ZR12-150I2-16/POL 12 V DC 12.5 A	POWER SUPPLY ADAPTER RACK ZR12-150/R10 12 V DC 12.5 A	POWER SUPPLY ADAPTER RACK ZR12-150X2 2 x 12 V DC 2 x 12.5 A	POWER SUPPLY ADAPTER RACK ZR12-100G-8UHD 12 V DC 8.5 A	PATCH PANEL POE-16/R10	PATCH PANEL POE-8/R	PATCH PANEL POE-8/R10	PATCH PANEL POE-8/R10
																
	148.01 EUR 148.01 EUR	157.68 EUR 157.68 EUR	52.86 EUR 52.86 EUR	66.24 EUR 66.24 EUR	76.51 EUR 76.51 EUR	57.01 EUR 57.01 EUR	71.42 EUR 71.42 EUR	81.24 EUR 81.24 EUR	77.73 EUR 77.73 EUR	50.80 EUR 50.80 EUR	82.75 EUR 82.75 EUR	73.71 EUR 73.71 EUR	66.71 EUR 66.71 EUR	27.56 EUR 27.56 EUR	37.02 EUR 37.02 EUR	43.31 EUR 43.31 EUR
Number of inputs	...	...	...	...	...	...	...	...	...	...	...	...	16 pcs (RJ-45)	8 pcs (RJ-45)	8 pcs (RJ-45)	8 pcs (RJ-45)
Adapter type	Switching	Switching	Switching	Switching	Switching - 2 pcs	Switching	Switching	Switching	Switching	Switching	Switching - 2 pcs	Switching	550 mA / Output	550 mA / Output	550 mA / Output	550 mA / Output
Maximal output current	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Power voltage	230 V AC	230 V AC	selectable by switch • 90 V ... 132 V AC, • 180 V ... 264 V AC	selectable by switch • 90 V ... 132 V AC, • 180 V ... 264 V AC	selectable by switch • 90 V ... 132 V AC, • 180 V ... 264 V AC	selectable by switch • 90 V ... 132 V AC, • 180 V ... 264 V AC	selectable by switch • 90 V ... 132 V AC, • 180 V ... 264 V AC	selectable by switch • 90 V ... 132 V AC, • 180 V ... 264 V AC	selectable by switch • 90 V ... 132 V AC, • 180 V ... 264 V AC	selectable by switch • 90 V ... 132 V AC, • 180 V ... 264 V AC	selectable by switch • 90 V ... 132 V AC, • 180 V ... 264 V AC	selectable by switch • 90 V ... 132 V AC, • 180 V ... 264 V AC	...	...	...	...
Protection type	18 PTC polymer fuses : 18x 1.1 A (max)	18 PTC polymer fuses : 18x 2 A (max)	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Voltage frequency range	...	...	47 ... 63 Hz	47 ... 63 Hz	47 ... 63 Hz	47 ... 63 Hz	47 ... 63 Hz	47 ... 63 Hz	47 ... 63 Hz	47 ... 63 Hz	47 ... 63 Hz	47 ... 63 Hz	...	...	...	...
Output	18 pcs terminals	18 pcs screw terminals	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Maximal current for single output	...	...	...	...	...	...	...	...	...	...	...	1 A	...	...	...	...
Output power	120 W	240 W	102 W	102 W	2 x 102 W	150 W	150 W	150 W	150 W	150 W	2 x 150 W	102 W	...	...	...	...
Operation temp	10 ... 45 °C	10 ... 45 °C	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Output voltage	12 V DC	12 V DC	12 V DC	12 V DC (typical)	2 x 12 V DC	12 V DC (typical)	12 V DC (typical)	12 V DC (typical)	12 V DC (typical)	12 V DC	2 x 12 V DC	12 V DC	max. 60 V	max. 60 V	max. 60 V	max. 60 V
Output voltage adjustment	...	...	11.4 V ... 13.2 V DC	11.4 V ... 13.2 V DC	11.4 V ... 13.2 V DC	11.4 V ... 13.2 V DC	11.4 V ... 13.5 V DC	11.4 V ... 13.5 V DC	11.4 V ... 13.5 V DC	11.4 V ... 13.2 V DC	11.4 V ... 13.2 V DC	11.4 ... 13.2 V	...	...	...	...
Maximal load	10 A	20 A	8.5 A	8.5 A	2 x 8.5 A	12.5 A	12.5 A	12.5 A	12.5 A	12.5 A	2 x 12.5 A	8.5 A	...	...	...	...
LED indicators	...	...	...	...	...	...	...	...	...	...	...	...	Power supply	Power supply	Power supply	Power supply
Number of video outputs	...	...	...	...	...	...	...	...	...	...	...	8 pcs BNC socket	...	...	...	...
Number of video inputs	...	...	...	...	...	...	...	...	...	...	...	8 pcs screw terminals	...	...	...	...
Efficiency	...	...	89 %	89 %	89 %	89 %	89 %	89 %	89 %	89 %	89 %	...	...	...	...	...
Number of power outputs	...	...	...	...	...	...	...	...	...	...	...	8 pcs Cable terminals	...	...	...	...
MTRF (Mean Time Between Failure)	...	...	> 700000 h - Telcordia SR-332	> 700000 h - Telcordia SR-332	> 700000 h - Telcordia SR-332	> 700000 h - Telcordia SR-332	> 700000 h - Telcordia SR-332	> 700000 h - Telcordia SR-332	> 700000 h - Telcordia SR-332	> 700000 h - Telcordia SR-332	> 700000 h - Telcordia SR-332	> 700000 h	...	...	...	...
Number of outputs	...	...	...	8 pcs - two-terminal elements	...	...	12 pcs - two-terminal elements	12 pcs - Rear panel, two- terminal elements	16 pcs - two-terminal elements	...	...	...	16 pcs (RJ-45)	8 pcs (RJ-45)	8 pcs (RJ-45)	8 pcs (RJ-45)
Standard	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Type of fuses	...	...	...	...	...	...	...	...	...	...	...	...	8 x 1A/250V, 5/20mm, delayed	...	...	...
Protections	...	...	• Overvoltage • Short-circuit • Overload	• Short-circuit • Overload • Overvoltage • 12 x 1 A - 5/20mm delayed fuse	• Overvoltage • Short-circuit • Overload	• Overvoltage • Short-circuit • Overload	• Overvoltage • Short-circuit • Overload • 12 x 1 A - 5/20mm delayed fuse	• Overvoltage • Short-circuit • Overload • 16 x 0.75 A - Polymer fuse	• Overvoltage • Short-circuit • Overload • Overvoltage • Short-circuit • Overload	• Overvoltage • Short-circuit • Overload	• Overvoltage • Short-circuit • Overload	• Short-circuit • Overload • Temperature	• Short-circuit • Overload	• Short-circuit • Overload	• Short-circuit • Overload	• Short-circuit • Overload
LEDs application	...	...	...	...	...	...	...	...	...	...	...	• red "POWER" - indicates the power voltage (DC IN) • green "PWR LED" - indicates the fuse blown (if there is no light means the fuse blown)	...	...	...	...
Main features	...	...	...	LED indication - Input voltage, Output voltage	...	...	LED indication - Input voltage, Output voltage	LED indication - Input voltage, Output voltage	LED indication - Input voltage, Output voltage	...	...	...	Pin numbers for RJ-45 connector • DATA 1, 2 and 3, 6 • Power supply 4, 5 (+) and 7, 8 (-) • Supported data rates 10 / 100 Mbps • Maximal load for single port 550 mA • Mounting with self- adhesive bases The self- adhesive distance elements allow to easy PCB assembly.	Pin numbers for RJ-45 connector • DATA 1, 2 and 3, 6 • Power supply 4, 5 (+) and 7, 8 (-) • Supported data rates 10 / 100 Mbps • Maximal load for single port 550 mA	Pin numbers for RJ-45 connector • DATA 1, 2 and 3, 6 • Power supply 4, 5 (+) and 7, 8 (-) • Supported data rates 10 / 100 Mbps • Maximal load for single port 550 mA	Pin numbers for RJ-45 connector • DATA 1, 2 and 3, 6 • Power supply 4, 5 (+) and 7, 8 (-) • Supported data rates 10 / 100 Mbps • Maximal load for single port 550 mA
Max. current	...	...	...	...	...	...	...	...	...	...	...	• 150mA camera - 98 meters (R=3.40hm/100m) • 150mA camera - 60 meters (R=5.50hm/100m) • 650mA camera + thermostat - 22 meters (R=3.40hm/100m) • 650mA camera + thermostat - 14 meters (R=5.50hm/100m)	...	...	...	...
Assembly	...	...	...	...	...	...	...	...	...	...	...	...	Rack 19"	...	...	...
Housing	...	...	...	...	...	...	...	...	...	...	...	...	Metal	1 U Rack 19"	1 U Rack 19"	1 U Rack 19"
Color	...	...	...	...	...	...	...	...	...	...	...	...	Black	...	...	...
Housing type	1.5 U Rack 19"	1.5 U Rack 19"	1 U Rack 19"	1 U Rack 19"	1 U Rack 19"	1 U Rack 19"	1 U Rack 19"	1 U Rack 19"	1 U Rack 19"	1 U Rack 10"	1 U Rack 19"	...	...	...	...	...
Manufacturer / Brand	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA
Operation temp. / Relative humidity	...	...	10 °C ... 70 °C / 10 % ... 95 %	10 °C ... 70 °C / 10 % ... 95 %	10 °C ... 70 °C / 10 % ... 95 %	10 °C ... 70 °C / 10 % ... 95 %	10 °C ... 70 °C / 10 % ... 95 %	10 °C ... 70 °C / 10 % ... 95 %	10 °C ... 70 °C / 10 % ... 95 %	10 °C ... 70 °C / 10 % ... 95 %	10 °C ... 70 °C / 10 % ... 95 %	10 °C ... 70 °C / 10 % ... 95 %	10 °C ... 55 °C / < 95 %	10 °C ... 55 °C / < 95 %	10 °C ... 55 °C / < 95 %	10 °C ... 55 °C / < 95 %
Weight	2.44 kg	2.99 kg	0.602 kg	0.645 kg	0.96 kg	0.59 kg	0.8 kg	0.82 kg	0.805 kg	0.59 kg	1.17 kg	0.69 kg	0.34 kg	0.078 kg	0.175 kg	0.29 kg
Dimensions	483 x 210 x 67 mm	483 x 210 x 67 mm	482 x 45 x 100 mm	482 x 45 x 100 mm	483 x 45 x 100 mm	482 x 44 x 100 mm	483 x 44 x 105 mm	483 x 44 x 105 mm	483 x 44 x 105 mm	256 x 45 x 100 mm	483 x 44 x 100 mm	483 x 44 x 122 mm	483 x 44 x 36 mm	220 x 44 x 25 mm	256 x 44 x 35 mm	483 x 44 x 36 mm
Guarantee	2 years	2 years	5 years	5 years	5 years	5 years	5 years	5 years	5 years	5 years	5 years	5 years	3 years	3 years	3 years	3 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00