

	POWER SUPPLY DISTRIBUTOR LZ-10/POL/R	POWER SUPPLY DISTRIBUTOR LZ-10/POL/R10	POWER SUPPLY DISTRIBUTOR LZ-12/R	POWER SUPPLY DISTRIBUTOR LZ-16/R10	POWER SUPPLY DISTRIBUTOR LZ-8P/R19	POWER SUPPLY DISTRIBUTOR LZ-10/POL/R19	POWER SUPPLY DISTRIBUTOR LZ-12/R19	POWER SUPPLY DISTRIBUTOR LZ-12C/R19	POWER SUPPLY DISTRIBUTOR LZ-12C/POL/R	POWER SUPPLY DISTRIBUTOR LZ-16/R	POWER SUPPLY DISTRIBUTOR LZ-16/R19	POWER SUPPLY DISTRIBUTOR LZ-16P/R19	POWER SUPPLY DISTRIBUTOR LZ-16P/R19	POWER SUPPLY DISTRIBUTOR LZ-16P/POL/R19	POWER SUPPLY DISTRIBUTOR LZ-20/POL/R19	POWER SUPPLY DISTRIBUTOR LZ-24/R19	POWER SUPPLY DISTRIBUTOR LZ-32/R19	POWER SUPPLY DISTRIBUTOR LZ-32/POL/R19
																		
	15.94 EUR 15.94 EUR	25.72 EUR 25.72 EUR	16.72 EUR 16.72 EUR	19.55 EUR 19.55 EUR	30.92 EUR 30.92 EUR	28.94 EUR 28.94 EUR	32.09 EUR 32.09 EUR	36.91 EUR 36.91 EUR	20.09 EUR 20.09 EUR	10.83 EUR 10.83 EUR	28.04 EUR 28.04 EUR	43.16 EUR 43.16 EUR	39.02 EUR 39.02 EUR	42.16 EUR 42.16 EUR	47.25 EUR 47.25 EUR	32.37 EUR 32.37 EUR	57.39 EUR 57.39 EUR	57.39 EUR 57.39 EUR
Number of power outputs	10 (2 x 5 outputs)	10 (2 x 5 outputs)	12 (2 x 6 outputs)	16 (2 x 8 outputs)	8	10 (2 x 5 outputs)	12 (2 x 6 outputs)	12 (2 x 6 outputs)	16 (2 x 8 outputs)	16 (2 x 8 outputs)	16 (2 x 8 outputs)	16 (2 x 8 outputs)	16 (2 x 8 outputs)	16 (2 x 8 outputs)	20 (4 x 5 outputs)	24 (4 x 6 outputs)	32 (4 x 8 outputs)	32 (4 x 8 outputs)
Number of power inputs	2 (one per each 5-outputs terminal)	2 (one per each 5-outputs terminal)	2 (one per each 6-outputs terminal)	2 (one per each 8-outputs terminal)	1	2 (one per each 5-outputs terminal)	2 (one per each 6-outputs terminal)	2 (one per each 6-outputs terminal)	2 (one per each 8-outputs terminal)	2 (one per each 8-outputs terminal)	2 (one per each 8-outputs terminal)	2 (one per each 8-outputs terminal)	2 (one per each 8-outputs terminal)	2 (one per each 8-outputs terminal)	4 (one per each 5-outputs terminal)	4 (one per each 6-outputs terminal)	4 (one per each 8-outputs terminal)	4 (one per each 8-outputs terminal)
Maximal power voltage	15 V DC (typical 12V)	15 V DC (typical 12V)	24 V DC (typical 12V)	24 V DC (typical 12V)	24 V DC (typical 12V)	15 V DC (typical 12V)	24 V DC (typical 12V)	24 V DC (typical 12V)	24 V DC (typical 12V)	24 V DC (typical 12V)	24 V DC (typical 12V)	24 V DC (typical 12V)	24 V DC (typical 12V)	24 V DC (typical 12V)	15 V DC (typical 12V)	24 V DC (typical 12V)	24 V DC (typical 12V)	24 V DC (typical 12V)
Maximal power supply current	12.5 A (for single terminal)	12.5 A (for single terminal)	5 A (for single terminal)	5 A (for single terminal)	8 A	12.5 A (for single terminal)	5 A (for single terminal)	5 A (for single terminal)	5 A (for single terminal)	5 A (for single terminal)	5 A (for single terminal)	8 A (for single terminal)	6 A (for single terminal)	12.5 A (for single terminal)	5 A (for single terminal)	5 A (for single terminal)	5 A (for single terminal)	5 A (for single terminal)
Max. output current for single output	2.5 A	2.5 A	1 A	1 A	1 A	2.5 A	1 A	1 A	0.75 A	1 A	1 A	1 A	0.75 A	2.5 A	1 A	1 A	0.75 A	0.75 A
Protection type	10 x 2.5 A - Polymer fuse	10 x 2.5 A - Polymer fuse	12 x 1 A 5/20mm delayed fuse	...	8 x 1 A 5/20mm delayed fuse	10 x 2.5 A - Polymer fuse	12 x 1 A 5/20mm delayed fuse	12 x 1 A 5/20mm delayed fuse	16 x 0.75 A - Polymer fuse	...	...	16 x 1 A 5/20mm delayed fuse	16 x 0.75 A - Polymer fuse	20 x 2.5 A - Polymer fuse	24 x 1 A - 5/20mm delayed fuse	...	32 x 0.75 A - Polymer fuse	32 x 0.75 A - Polymer fuse
Power connectors type	Input : Cable terminals Output : Cable terminals	Input : Cable terminals Output : Cable terminals	Input : Cable terminals Output : Cable terminals	Input : Cable terminals Output : Cable terminals	Input : Cable terminals Output : Cable terminals	Input : Cable terminals Output : Cable terminals	Input : Cable terminals Output : Cable terminals	Input : Cable terminals Output : Cable terminals	Input : Cable terminals Output : Cable terminals	Input : Cable terminals Output : Cable terminals	Input : Cable terminals Output : Cable terminals	Input : Cable terminals Output : Cable terminals	Input : Cable terminals Output : Cable terminals	Input : Cable terminals Output : Cable terminals	Input : Cable terminals Output : Cable terminals	Input : Cable terminals Output : Cable terminals	Input : Cable terminals Output : Cable terminals	Input : Cable terminals Output : Cable terminals
Operation temp	-50 °C ... 55 °C	-50 °C ... 55 °C	-50 °C ... 55 °C	-50 °C ... 55 °C	-50 °C ... 55 °C	-50 °C ... 55 °C	-50 °C ... 55 °C	-50 °C ... 55 °C	-50 °C ... 55 °C	-50 °C ... 55 °C	-50 °C ... 55 °C	-50 °C ... 55 °C	-50 °C ... 55 °C	-50 °C ... 55 °C	-50 °C ... 55 °C	-50 °C ... 55 °C	-50 °C ... 55 °C	-50 °C ... 55 °C
Permissible relative humidity	< 95 %	< 95 %	< 95 %	< 95 %	< 95 %	< 95 %	< 95 %	< 95 %	< 95 %	< 95 %	< 95 %	< 95 %	< 95 %	< 95 %	< 95 %	< 95 %	< 95 %	< 95 %
Housing type	PCB	Rack 10"	PCB	Rack 10"	Rack 19", 1 U	RACK 19", 1U	RACK 19", 1U	RACK 19", 1U	PCB	PCB	Rack 19"	Rack 19", 1 U	Rack 19"	1 U Rack 19"	1 U Rack 19"	1 U Rack 19"	1 U Rack 19"	1 U Rack 19"
Weight	0.08 kg	0.170 kg	0.1 kg	0.19 kg	0.28 kg	0.280 kg	0.3 kg	0.34 kg	0.1 kg	0.1 kg	0.3 kg	0.325 kg	0.3 kg	0.34 kg	0.35 kg	0.380 kg	0.380 kg	0.38 kg
Dimensions	216 x 40 x 20 mm	255 x 41 x 40 mm	216 x 40 x 20 mm	255 x 41 x 40 mm	483 x 44 x 33 mm	482 x 41 x 40 mm	482 x 45 x 39 mm	482 x 45 x 64 mm	216 x 40 x 18 mm	216 x 40 x 20 mm	482 x 41 x 40 mm	483 x 44 x 33 mm	482 x 44 x 36 mm	484 x 44 x 35 mm	484 x 44 x 33 mm	483 x 44 x 24 mm	484 x 44 x 35 mm	484 x 44 x 35 mm
Manufacturer / Brand	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA
Guarantee	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years