

Code: PFS3211-8GT-120-V2

SWITCH POE **PFS3211-8GT-120-V2** 8-PORT SFP DAHUA

Net: **169.92 EUR** Gross: **169.92 EUR**



The PFS3211-8GT-120-V2 PoE Switch is an industrial type device enabling fluent network transmission at rates 10 / 100 / 1000 Mbps.

Attention! The SFP port requires the SFP module, which is available in our offer.

SPECIFICATION

LAN ports:	• 8 x RJ45 (10/100/1000 Base-T, 6 PoE (802.3af/at) + 2 PoE (802.3bt) / Hi-PoE / PoE (802.3af/at)) • 2 x Uplink (port SFP - 1000 Base-X) • 1 x Uplink (RJ45 - 10/100/1000 Base-T)
Management:	—
Transmission speed:	• Ethernet - 10 Mbps Full Duplex • Fast Ethernet - 100 Mbps Full Duplex • Gigabit Ethernet - 1000 Mbps Full Duplex
Maximal output power:	• 30 W / port PoE 802.3af/at • 90 W / port PoE 802.3bt
Maximal total power:	120 W
Operation modes:	• Extend On : 250 m, 10 Mbps • Extend Off : 100 m, 100 / 1000 Mbps
Main features:	• DIN, TS-35 rail mounting • Data Flow Control • protection against lightning discharges and voltage differences and strokes between devices • Industrial wide temperature design. • Intelligent management of Power Supply Unit power's output stage • PoE (802.3af), PoE (802.3at), Hi-PoE, PoE (802.3bt) • PoE Watchdog / PD Alive mode - monitoring of the ports that power PoE devices and automatic restart by cutting off the power supply when an unresponsive device is detected • The ability to connect two power adapters - redundant power supply • The device supports 8-pin power supply
LED diodes:	Power, Link/Act, PoE
Certificates:	CE

Power supply:	48 ... 57 V DC (power adapter included)
Housing type:	DIN
Operation temp:	-30 °C ... 65 °C
Weight:	0.68 kg
Dimensions:	150 x 110 x 42 mm
Manufacturer / Brand:	DAHUA
Guarantee:	5 years

PRESENTATION

Front view:



Top view:



Mounting side view:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------