

Code: PFS3110-8ET1GT1GF-96

## SWITCH POE **PFS3110-8ET1GT1GF-96** 8-PORT SFP DAHUA

Net: **204.62 EUR** Gross: **204.62 EUR**

The device is perfect to build a network of IP cameras with power supply in the PoE 802.3af / 802.3at standard.



### SPECIFICATION

|                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| LAN ports:            | <ul style="list-style-type: none"><li>• 8 x RJ45 10/100 Base-T ( 1 x Hi-PoE (802.3bt) + 7 x PoE (802.3af/at) ),</li><li>• 1 x RJ45 10/100/1000 Base-T - Uplink,</li><li>• 1 x Port SFP 1000 Base-X - Uplink</li></ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Management:           | —                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| LED diodes:           | Power, PoE, Link/Act, Uplink 1, Uplink 2                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Transmission speed:   | 10 / 100 Mbps : 8 LAN & PoE ports ,<br>10 / 100 / 1000 Mbps : 1 Port RJ45 (Uplink) ,<br>1000 Mbps : 1 Port SFP (Uplink)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Maximal output power: | <ul style="list-style-type: none"><li>• 90 W / port Hi-PoE / PoE 802.3bt - Port 1</li><li>• 30 W / port PoE 802.3af/at - 2 ... 8 ports</li></ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Maximal total power:  | 96 W                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| MAC addresses table:  | 8k                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Operation modes:      | <ul style="list-style-type: none"><li>• Extend On : 250 m, 10 Mbps</li><li>• Extend Off : 100 m, 100 Mbps</li><li>• PD Alive</li></ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Main features:        | <ul style="list-style-type: none"><li>• PoE power mode - The device supports 8-pin power supply</li><li>• Ports marked in red support IEEE802.3af, IEEE802.3at, IEEE802.3bt and Hi-PoE standards with a maximum output power of 90 W per port - designed to power high power devices</li><li>• Intelligent PoE power management - the device controls power consumption on individual ports</li><li>• PoE Watchdog / PD Alive mode - monitoring of the ports that power PoE devices and automatic restart by cutting off the power supply when an unresponsive device is detected</li><li>• protection against lightning discharges and voltage differences and strokes between devices</li><li>• Industrial wide temperature design.</li></ul> |
| Certificates:         | CE, FCC                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Housing:              | Desktop, Metal                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Power supply:         | 53 V DC / 1.81 A (power adapter included)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Operation temp:       | -10 °C ... 55 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Weight:               | 0.58 kg                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Dimensions:           | 240 x 105 x 28 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

|                       |         |
|-----------------------|---------|
| Manufacturer / Brand: | DAHUA   |
| Guarantee:            | 5 years |

PRESENTATION

Front view:



- 1 - LAN + Hi-PoE (802.3bt)
- 2 - LAN + PoE
- 3 - Port RJ45 (Uplink)
- 4 - Port SFP (Uplink)

Rear view:



In the kit:



PACKAGE

|                                  |                    |
|----------------------------------|--------------------|
| Dimensions (L x W x H): 0x0x0 mm | Gross Weight: 0 kg |
|----------------------------------|--------------------|