

Code: EXPERT-POE/OTD-8G2GSFP

EXTERNAL CAMERA DISTRIBUTION POINT **EXPERT-POE/OTD-8G2GSFP 8** PoE + 2 x SFP

Net: **402.15 EUR** Gross: **402.15 EUR**

The EXPERT-POE/OTD-8G2GSFP set consists of 8-port PoE switch, additionally equipped with 2 SFP Uplink ports, integrated with an optical fiber tray, as well as an air breaker and lightning arrester enclosed in an IP55 rated outdoor enclosure.



SPECIFICATION

LAN ports:	• 8 x RJ45 10/100/1000 Base-T (8 x PoE (802.3af/at)), • 2 x SFP (Uplink) 1000 Base-X
Management:	—
LED diodes:	Power, Link/Act, PoE
Transmission speed:	• 10 / 100 / 1000 Mbps : 8 LAN & PoE ports, • 1000 Mbps : 2 SFP (Uplink) ports
Maximal output power:	30 W @ PoE (802.3af/at) - 1 ... 8 ports
Maximal total power:	115 W
MAC addresses table:	16k
Operation modes:	• E - EXTEND mode - ports 1, 2, 3, 4, 5, 6, 7, 8 support transmission up to 250 m • V - VLAN mode, 1 ... 8 ports are isolated from each other and separately work with the 9, 10 ports • P - PoE Auto-check mode - monitoring of the ports that power PoE devices and automatic restart by cutting off the power supply when an unresponsive device is detected

Fiber Optic Distribution Box:

Number of line cables:	2
Number of splice cassettes:	1
Splice capacity:	8
Connector type:	SC / PC Single-Mode (SM)
Number of adapters:	4
Number of pigtails:	4 Single-Mode (SM)

Housing:

Material:	Metal
-----------	-------

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Color:	Gray
"Index of Protection":	IP55
Cable entries:	3 pcs from the bottom Ø 39 mm
Main features:	• The door is closed with a lock • Fan cooler built-in
Maximum pole diameter:	350 mm
External dimensions:	280 x 260 x 210

General information:

Certificates:	CE, RoHS
Protections:	• Protection against electrostatic discharge - Contact/Air (ESD/EMP) : 6 / 8 kV • Circuit Breaker : C10, protected lines L+N • Lightning protection : - Maximal voltage : 385 V AC - Nominal stroke current : 20 kA (8/20µs) - Maximum stroke current : 40 kA (8/20µs)
Power supply:	100 ... 240 V AC, 50 / 60 Hz - Screw terminals
Operation temp:	-20 °C ... 65 °C
Weight:	5.65 kg
Dimensions:	280 x 260 x 205 mm
Guarantee:	2 years

PRESENTATION

Internal view of the housing:



Fiber Optic Distribution Box:



Mounting side view:



Example of application:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------