

Code: PFS3009-8ET-96

INDUSTRIAL POE SWITCH **PFS3009-8ET-96** 9-PORT DAHUA

Net: 51.90 EUR Gross: 51.90 EUR

The PFS3009-8ET-96 Switch is an industrial type device enabling fluent network transmission at rates 10 / 100 Mbps. Devices of this type can be used in installations realized in industrial facilities in harsh environmental conditions like high or low temperature.  
Attention! The SFP port requires the SFP module, which is available in our offer.



SPECIFICATION

|                       |                                                                                                                                                                                                                         |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| LAN ports:            | <ul style="list-style-type: none"><li>• 1 x RJ45 10/100 Base-T - Port Uplink,</li><li>• 1 x RJ45 10/100 Base-T + Hi-PoE</li><li>• 7 x RJ45 10/100 Base-T + PoE (802.3af/at)</li></ul>                                   |
| Management:           | —                                                                                                                                                                                                                       |
| Transmission speed:   | <ul style="list-style-type: none"><li>• 10 / 100 Mbps - 8 LAN &amp; PoE ports</li><li>• 10 / 100 Mbps - 1 Port Uplink</li></ul>                                                                                         |
| Maximal output power: | 30 W / port PoE<br>60 W / port Hi-PoE                                                                                                                                                                                   |
| Maximal total power:  | 96 W                                                                                                                                                                                                                    |
| MAC addresses table:  | 2k                                                                                                                                                                                                                      |
| Main features:        | <ul style="list-style-type: none"><li>• Data Flow Control</li><li>• protection against lightning discharges and voltage differences and strokes between devices</li><li>• Industrial wide temperature design.</li></ul> |
| LED diodes:           | Power, Link/Act, PoE                                                                                                                                                                                                    |
| Certificates:         | CE                                                                                                                                                                                                                      |
| Power supply:         | 48 ... 57 V DC / 2.0 A (power adapter included)                                                                                                                                                                         |
| Operation temp:       | -30 °C ... 65 °C                                                                                                                                                                                                        |
| Weight:               | 0.47 kg                                                                                                                                                                                                                 |
| Dimensions:           | 190 x 100 x 30 mm                                                                                                                                                                                                       |
| Manufacturer / Brand: | DAHUA                                                                                                                                                                                                                   |
| Guarantee:            | 3 years                                                                                                                                                                                                                 |

PRESENTATION

Front panel:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60



Mounting side view:



Power connector:



In the kit:



**PACKAGE**

|                                  |                    |
|----------------------------------|--------------------|
| Dimensions (L x W x H): 0x0x0 mm | Gross Weight: 0 kg |
|----------------------------------|--------------------|