

Code: S4101-16ET2GF-240-C

INDUSTRIAL POE SWITCH **S4101-16ET2GF-240-C** 16-PORT SFP DAHUA

Net: **504.12 EUR** Gross: **504.12 EUR**

The S4101-16ET2GF-240-C PoE Switch is an industrial type device enabling fluent network transmission at rates 10 / 100 Mbps. 16 ports support Power over Ethernet (PoE) function.

Switch is managed through the web and the cloud (DoLink Care application).

Attention! The SFP port requires the SFP module, which is available in our offer.



SPECIFICATION

LAN ports:	• 16 x RJ45 10/100 Base-T (2 x Hi-PoE (802.3bt) + 14 x PoE (802.3af/at)), • 2 x port Combo: SFP (1000 Base-X) / RJ45 (10/100/1000 Base-T) - Uplink
Management:	✓
LED diodes:	Link, PoE, Power, System, 50 % Power, 80 % Power, 100 % Power
Transmission speed:	• 10 / 100 Mbps : 16 LAN & PoE ports, • 10 / 100 / 1000 : 2 RJ45 (Uplink) ports, • 1000 : 2 SFP (Uplink) ports
Maximal output power:	• 90 W / port Hi-PoE / PoE 802.3bt - 1, 2 ports • 30 W / port PoE 802.3af/at - 3 ... 16 ports
Maximal total power:	240 W
MAC addresses table:	16k
Operation modes:	Extend On : 250 m, 10 Mbps @ UTP cat. 5e, 6
Main features:	• Switch is managed through the web and the cloud (DoLink Care application) • PoE power mode : The device supports 8-pin power supply • Intelligent management of Power Supply Unit power's output stage • protection against lightning discharges and voltage differences and strokes between devices • Watchdog PoE • Compliance with the LLDP protocol • View topology and network status • RESET button • Can be mounted in a Rack 19" cabinet
Certificates:	CE, FCC
Protections:	• Protection against lightning discharges (common/differential) : 4 / 2 kV • Protection against electrostatic discharge - Contact/Air (ESD/EMP) : 6 / 8 kV
Housing:	Metal
Power supply:	100 ... 240 V AC @ 50 / 60 Hz
Power consumption:	max. 240 W
Operation temp:	-10 °C ... 55 °C
Weight:	3.15 kg
Dimensions:	440 x 300 x 44 mm, RACK 19", 1U
Manufacturer / Brand:	DAHUA
Guarantee:	5 years

PRESENTATION

Front view:



1. LAN + Hi-PoE (802.3bt)
2. LAN + PoE
3. Combo: RJ45/SFP - Uplink

Rear view:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------