

Code: GT-DA71-4H4F

# AHD, PAL, TCP/IP DVR **GT-DA71-4H4F** 4 CHANNELS GEMINI TECHNOLOGY

Net: **37.87 EUR** Gross: **37.87 EUR**

The GT-DA71-4H4F digital recorder with AHD (Analog High Definition) / TCP/IP and PAL interface is a professional device applicable in surveillance systems. The AHD interface allows to transmission of analog video signal via coaxial cable in 1080p resolution. The menu options layout has been designed for all users, even beginners can easy navigate and change parameters in DVR settings without any problem.



## SPECIFICATION

|                                     |                                                                                                                                                                          |
|-------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Standard:                           | AHD, PAL, TCP/IP                                                                                                                                                         |
| Video inputs:                       | 4 pcs BNC - AHD, CVBS                                                                                                                                                    |
| Video outputs:                      | 1 pcs HDMI<br>1 pcs VGA                                                                                                                                                  |
| Audio inputs:                       | 4 pcs CINCH                                                                                                                                                              |
| Audio outputs:                      | 1 pcs CINCH<br>1 pcs from HDMI port                                                                                                                                      |
| Image compression method:           | H.264                                                                                                                                                                    |
| Number of compression levels:       | 6                                                                                                                                                                        |
| Image records resolutions:          | AHD-H (1920 x 1080)<br>AHD-M (1280 x 720)<br>AHD-L / PAL (960 x 576)<br>PAL (704 x 576)<br>IP (1920 x 1080)                                                              |
| Maximal total frame rate:           | AHD : 60 fps @ 1920 x 1080 px,<br>AHD : 100 fps @ 1280 x 720 px,<br>AHD, PAL : 100 fps @ 960 x 576 px,<br>PAL : 100 fps @ 704 x 576 px,<br>IP : 100 fps @ 1920 x 1080 px |
| Recording speed adjustment:         | 1 ... 15 fps @ 1920 x 1080 px<br>1 ... 25 fps @ 1280 x 720 px<br>1 ... 25 fps @ 960 x 576 px<br>1 ... 25 fps @ 704 x 576 px<br>for each channel                          |
| Operation modes:                    | <ul style="list-style-type: none"><li>• 4 x AHD-H / AHD-M / AHD-L / PAL - Work in any configuration</li><li>• 4 x AHD-H / AHD-M / AHD-L / PAL + 4 x IP 1080p</li></ul>   |
| Recording modes:                    | Manual, Sensor, Motion detection, Schedule                                                                                                                               |
| Supported hard drives:              | 2 x 8 TB SATA                                                                                                                                                            |
| External storage devices backup:    | Records backup at (.avi) format to USB (pendrive)                                                                                                                        |
| Searching and playback the records: | Records searching: by time and events type. Records playback: forward, backward, fast, slow                                                                              |

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

|                                  |                                                                                                                                                            |
|----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Network functions:               | Network client and browser software IE, Firefox, Opera, Chrome: live view, playback and backup of the records and configuration of the recorder parameters |
| Mobile phones support:           | Port no.: 5800 or access by a cloud (P2P)<br>• Android: Free application <a href="#">Fseye</a><br>• iOS: Free application <a href="#">Fseye</a>            |
| Alarm inputs / outputs:          | 4 / 1                                                                                                                                                      |
| PTZ control:                     | RS-485 - PELCO-D/P                                                                                                                                         |
| Motion Detection:                | Split the screen into zones : 22 x 18 motion zones                                                                                                         |
| Mouse support:                   | ✓                                                                                                                                                          |
| IR remote controller in the set: | —                                                                                                                                                          |
| Power supply:                    | 12 V DC / 4 A (power adapter included)                                                                                                                     |
| Color:                           | Black                                                                                                                                                      |
| Weight:                          | 1.504 kg                                                                                                                                                   |
| Dimensions:                      | 360 x 275 x 54 mm                                                                                                                                          |
| Supported languages:             | English, Polish                                                                                                                                            |
| Manufacturer / Brand:            | GEMINI TECHNOLOGY                                                                                                                                          |
| Country of origin:               | China                                                                                                                                                      |
| Guarantee:                       | 2 years                                                                                                                                                    |

## PRESENTATION

Front view:



Rear view:



In the kit:



Package:



**PACKAGE**

|                                  |                    |
|----------------------------------|--------------------|
| Dimensions (L x W x H): 0x0x0 mm | Gross Weight: 0 kg |
|----------------------------------|--------------------|