

Code: GT-DA42-16H16F

AHD, PAL, TCP/IP DVR **GT-DA42-16H16F** 16 CHANNELS GEMINI TECHNOLOGY

Net: **110.64 EUR** Gross: **110.64 EUR**

The GT-DA42-16H16F digital recorder with AHD (Analog High Definition) / TCP/IP and PAL interface is a professional device applicable in surveillance systems. The AHD interface allows to transmission of analog video signal via coaxial cable in 1080p resolution. The menu options layout has been designed for all users, even beginners can easy navigate and change parameters in DVR settings without any problem.



SPECIFICATION

Standard:	AHD, PAL, TCP/IP
Video inputs:	16 pcs BNC - AHD, CVBS
Video outputs:	1 pcs HDMI 1 pcs VGA
Audio inputs:	4 pcs CINCH
Audio outputs:	1 pcs CINCH
Image compression method:	H.264
Number of compression levels:	6
Image records resolutions:	AHD-H (1920 x 1080) AHD-M (1280 x 720) AHD-L / PAL (960 x 576) PAL (704 x 576) IP (1920 x 1080)
Maximal total frame rate:	AHD : 240 fps @ 1920 x 1080 px, AHD : 400 fps @ 1280 x 720 px, AHD, PAL : 400 fps @ 960 x 576 px, PAL : 400 fps @ 704 x 576 px, IP : 400 fps @ 1920 x 1080 px
Recording speed adjustment:	1 ... 15 fps @ 1920 x 1080 px 1 ... 25 fps @ 1280 x 720 px 1 ... 25 fps @ 960 x 576 px 1 ... 25 fps @ 704 x 576 px for each channel
Operation modes:	• 16 x AHD-H / AHD-M / AHD-L / PAL - Work in any configuration • 16 x AHD-H / AHD-M / AHD-L / PAL + 16 x IP 1080p
Recording modes:	Manual, Sensor, Motion detection, Schedule
Supported hard drives:	2 x 8 TB SATA
External storage devices backup:	Records backup at (.avi) format to USB (pendrive)
Searching and playback the records:	Records searching: by time and events type. Records playback: forward, backward, fast, slow
Network functions:	Network client and browser software IE, Firefox, Opera, Chrome: live view, playback and backup of the records and configuration of the recorder parameters

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Mobile phones support:	Port no.: 5800 or access by a cloud (P2P) • Android: Free application Fseye • iOS: Free application Fseye
Alarm inputs / outputs:	8 / 2
PTZ control:	RS-485 - PELCO-D/P
Motion Detection:	Split the screen into zones : 22 x 18 motion zones
Mouse support:	✓
IR remote controller in the set:	—
Power supply:	12 V DC / 5 A (power adapter included)
Color:	Black
Weight:	1.714 kg
Dimensions:	360 x 275 x 54 mm
Supported languages:	English, Polish
Manufacturer / Brand:	GEMINI TECHNOLOGY
Country of origin:	China
Guarantee:	2 years

PRESENTATION

Front view:



Rear view:



In the kit:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Package:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------