

Code: HAC-HFW1509TLM-A-LED-0360B-S2

AHD, HD-CVI, HD-TVI, CVBS CAMERA **HAC-HFW1509TLM-A-LED-0360B-S2** Full-Color - 5 Mpx 3.6 mm DAHUA

Net: **111.89 EUR** Gross: **111.89 EUR**

Megapixel camera with 1/2.7" CMOS sensor and AHD / HD-CVI / HD-TVI / CVBS.

The AHD / HD-CVI / HD-TVI interface allows to transmission of analog video signal via coaxial cable in max. 8 Mpx (4K UHD) resolution. During transmission there are no delays and is maintained the original, high quality image.

In the case of video transmission using a twisted pair cable and matching transformers (balun), be aware of the possibility of signal reflections and interfering signals.

Camera is according to IP67 Index of Protection norm.

Attention! The camera of the Full-color series does not have a black and white mode. Thanks to fit the camera in a very sensitive sensor and the LED illuminator emitting visible light in white, the device allows to obtain a clear, colorful image in all lighting conditions.



SPECIFICATION

Standard:	AHD, HD-CVI, HD-TVI, CVBS
Sensor:	1/2.7 " Progressive Scan CMOS
Matrix size:	5 Mpx
Resolution:	• 2592 x 1944 - 5 Mpx @ AHD / HD-CVI / HD-TVI @ 20 fps - Aspect Ratio 16 : 9, • 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI @ 25 fps, • 1920 x 1080 - 1080p @ HD-CVI @ 25 fps, • 960 x 576 - 960H @ PAL
Lens:	3.6 mm
View angle:	• 83 ° (manufacturer data) • 80 ° (our tests result)
White light LED illuminator range:	40 m
Video output:	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω
Audio:	• Microphone built-in, • Audio support via coaxial cable - HD-CVI only
OSD menu:	OSD menu available via DAHUA recorder
Main features:	• Possibility to turn off the LED illuminator • D-WDR - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • Sharpness - sharper image outlines • AGC - Automatic Gain Control • Privacy zones • Mirror - Mirror image • Auto White Balance
"Index of Protection":	IP67

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Power supply:	12 V DC / 420 mA
Power consumption:	≤ 5 W
Housing:	Compact, Plastic + Metal
Vandal-proof:	—
Color:	White + Black
Operation temp:	-40 °C ... 60 °C
Weight:	0.3 kg
Dimensions:	198 x 80 x 76 mm
Manufacturer / Brand:	DAHUA
Guarantee:	3 years

PRESENTATION



Side view:



Mounting side view:



In the kit:



OUR TESTS

AHD:

Camera image at artificial illumination (about 30Lux):



Camera image at night conditions with internal built-in LED illuminator on:



Camera image at direct strong light opposite to camera:




HD-CVI:

Camera image at artificial illumination (about 30Lux):



Camera image at night conditions with internal built-in LED illuminator on:



Camera image at direct strong light opposite to camera:



HD-TVI:

Camera image at artificial illumination (about 30Lux):



Camera image at night conditions with internal built-in LED illuminator on:



Camera image at direct strong light opposite to camera:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------