

Code: DS-7204HUHI-K1

# AHD, HD-CVI, HD-TVI, CVBS, TCP/IP DVR **DS-7204HUHI-K1** 4 CHANNELS

Hikvision

Net: **216.72 USD** Gross: **266.57 USD**

The DS-7204HUHI-K1 digital recorder with AHD (Analog High Definition), HD-CVI (High Definition Composite Video Interface), HD-TVI (High Definition Transport Video Interface), TCP/IP and CVBS interface is a professional device applicable in surveillance systems.

The menu options layout has been designed for all users, even beginners can easy navigate and change parameters in DVR settings without any problem.



## SPECIFICATION

Standard:	AHD, HD-CVI, HD-TVI, PAL, TCP/IP
Video inputs:	4 pcs BNC - AHD / HD-CVI / HD-TVI / PAL
Video outputs:	1 pcs HDMI 1 pcs VGA 1 pcs CVBS - BNC socket
Audio inputs:	4 pcs CINCH
Audio outputs:	1 pcs CINCH
Image compression method:	H.265 / H.265+ / H.264 / H.264+
Image records resolutions:	<ul style="list-style-type: none"><li>• HD-TVI : 5.0 Mpx - 2560 x 1944, 3.7 Mpx - 2560 x 1440, 3 Mpx - 1920 x 1536, 1080p - 1920 x 1080, 720p - 1280 x 720,</li><li>• AHD : 5.0 Mpx - 2560 x 1944, 3.7 Mpx - 2560 x 1440, 1080p - 1920 x 1080, 720p - 1280 x 720,</li><li>• HD-CVI : 3.7 Mpx - 2560 x 1440, 1080p - 1920 x 1080, 720p - 1280 x 720,</li><li>• PAL : 960H - 960 x 576,</li><li>• IP : max. 8.0 Mpx - 3840 x 2160</li></ul>
Recording speed adjustment:	<ul style="list-style-type: none"><li>1 ... 25 fps @ 3840 x 2160 px IP</li><li>1 ... 12 fps @ 2560 x 1944 px</li><li>1 ... 15 fps @ 2560 x 1440 px</li><li>1 ... 18 fps @ 1920 x 1536 px</li><li>1 ... 25 fps @ 1920 x 1080 px</li><li>1 ... 25 fps @ 1280 x 720 px</li><li>1 ... 25 fps @ 704 x 576</li><li>1 ... 25 fps @ 640 x 480 px</li></ul> for each channel
Operation modes:	Firmware V3.5.37 build 180801 4 x HD-TVI / AHD / HD-CVI / PAL / IP + 2 x IP
Recording modes:	Manual, Motion Detection, Schedule
Supported hard drives:	1 x 10 TB SATA
External storage devices backup:	Backup to USB drive (pendrive)
Searching and playback the records:	Records searching: timeline or file list. Playback: forward, fast, slow. Playback max. 4 cameras in the same time
Network interface:	1 x RJ-45 - 10/100 Base-TX

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

Bitrate:	32 ... 10240 kbps
Network functions:	Network Client Software and IE browser: live view, playback and backup of the records, partial configuration of the recorder parameters
Network protocols:	TCP/IP, PPPoE, DHCP, Hik Cloud P2P, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP, HTTPS, ONVIF
Mobile phones support:	Port no.: 8000 or access by a cloud (P2P) Android: Free application <a href="#">iVMS-4500</a> iOS (iPhone): Free application <a href="#">iVMS-4500</a>
Default IP address:	DHCP or 192.168.1.64
Default admin user / password:	admin / -
Web browser access ports:	80
PC client access ports:	554 RTSP, 8000
Mobile client access ports:	8000
Port ONVIF:	80
RTSP URL:	<ul style="list-style-type: none"> <li>• rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no01/ - Main stream</li> <li>• rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no02/ - Sub stream</li> </ul>
Alarm inputs / outputs:	4 / 1
PTZ control:	RS-485 PELCO-D/P Control compatible with coax HD-TVI Hikvision
Motion Detection:	Split the screen into zones : 22 x 18 motion zones
Mouse support:	✓
IR remote controller in the set:	—
Main features:	Intelligent Image Analysis : intrusion, crossing the line (tripwire)
Power supply:	12 V DC / 1.5 A (power adapter included)
Color:	Black
Weight:	1.2 kg
Dimensions:	315 x 250 x 47 mm
Supported languages:	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Greek, Spanish, Dutch, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian
Manufacturer / Brand:	Hikvision
SAP Code:	300219673
Guarantee:	<b>3 years</b>

## PRESENTATION

Front panel:



Rear view:



In the kit:

