Code: RV-8/16-UHD/R19

VIDEO SPLITTER **RV-8/16-UHD/R19**

Net: 89.93 EUR Gross: 89.93 EUR

The RV-8/16-UHD/R19 splitter consists of 8 independent dual output video splitters. The modern design of the device enables cooperation with all standards commonly used in CCTV systems, operating in the band up to 120MHz. This means that the signal can be split in maximum resolution: AHD - 8Mpx, HD-CVI - 8Mpx, HD-TVI - 8Mpx, CVBS - 960H.

The device is designed to continuous work in closed spaces.

The proper distances among sockets allow to easy BNC connectors mounting.




SPECIFICATION

Standard:	• AHD / HD-CVI / HD-TVI - 8 Mpx 4K UHD, • CVBS - PAL, NTSC
Number of inputs:	8 pcs BNC
Number of outputs:	16 pcs BNC
Bandwidth:	0 ... 120 MHz (-3dB)
Inputs impedance:	75 Ω
Outputs impedance:	75 Ω
Input protection:	ESD, IEC 61000-4-2, ±30kV contact, ±30kV air Lightning, IEC 61000-4-5, 12A (t_p=8/20μs)
Outputs protection:	ESD, IEC 61000-4-2, ±30kV contact, ±30kV air Lightning, IEC 61000-4-5, 12A (t_p=8/20μs)
Power supply:	7 ... 26 V DC (power adapter not included)
Current consumption:	120 mA @ 12 V DC
Gain :	0 dB
Housing type:	1 U Rack 19"
Dimensions:	490 x 44 x 38 mm
Weight:	0.34 kg
Manufacturer / Brand:	DELTA
Guarantee:	**5 years**

PRESENTATION

Front view:



1) Inputs
2) Outputs
3) Power supply

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Rear view:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg