

Code: DS-2CD2025FWD-I(2.8MM) BLACK/HIKVISION

## IP CAMERA **DS-2CD2025FWD-I(2.8MM) BLACK/HIKVISION** - 1080p

Hikvision

Net: **211.51 EUR** Gross: **211.51 EUR**

IP camera with efficient H.264 / H.265 image compression algorithm for clear and smooth video streaming at maximal resolution of 1080p.

PoE powering possibility, compatible with the 802.3af standard makes the device more universal and easier to install.

Powered by Darkfighter - the camera has very good sensitivity, dedicated to poor lighting conditions.



### SPECIFICATION

|                           |                                                                                                                                   |
|---------------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| Standard:                 | TCP/IP                                                                                                                            |
| Sensor:                   | 1/2.8 " Progressive Scan CMOS                                                                                                     |
| Scanning system:          | Progressive                                                                                                                       |
| Matrix size:              | 2.1 Mpx                                                                                                                           |
| Resolution:               | 1920 x 1080 - 1080p ,<br>1280 x 960 - 1.3 Mpx ,<br>1280 x 720 - 720p                                                              |
| Lens:                     | 2.8 mm                                                                                                                            |
| View angle:               | <ul style="list-style-type: none"><li>• 108 ° (manufacturer data)</li><li>• 106 ° (our tests result)</li></ul>                    |
| Compression:              | H.265+ / H.265 / H.264+ / H.264 / MJPEG                                                                                           |
| S/N ratio:                | > 50 dB (AGC off)                                                                                                                 |
| Range of IR illumination: | 30 m                                                                                                                              |
| Alarm inputs / outputs:   | —                                                                                                                                 |
| Audio:                    | —                                                                                                                                 |
| Memory card slot:         | Micro SD memory cards up to 128GB support (possible local recording)                                                              |
| Bitrate:                  | 32 ... 16384 kbps - H.264                                                                                                         |
| Main stream frame rate:   | 25 fps @ 1080p                                                                                                                    |
| Network interface:        | 10/100 Base-T (RJ-45)                                                                                                             |
| Network protocols:        | TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, SNMP, IGMP, UDP, PPPoE, IEEE 802.1x, QoS, IPv6 |

|                                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|--------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WEB Server:                    | Built-in, NVR compliance                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Max. number of on-line users:  | 6                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| ONVIF:                         | 16.12                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Mobile phones support:         | Port no.: 8000 or access by a cloud (P2P)<br>• Android: Free application <a href="#">iVMS-4500</a> or <a href="#">Hik-Connect</a><br>• iOS (iPhone): Free application <a href="#">iVMS-4500</a> or <a href="#">Hik-Connect</a>                                                                                                                                                                                                                                                                                                                                                            |
| Default admin user / password: | admin / -                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Default IP address:            | 192.168.1.64                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Web browser access ports:      | 80                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| PC client access ports:        | Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Mobile client access ports:    | 8000                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Port ONVIF:                    | 80                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| RTSP URL:                      | <ul style="list-style-type: none"> <li>• Main stream<br/>rtsp://192.168.1.64:554/Streaming/Channels/101/ - RTSP - without authorization<br/>rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ - with authorization</li> <li>• Sub stream<br/>rtsp://192.168.1.64:554/Streaming/Channels/102/ - RTSP - without authorization<br/>rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ - with authorization</li> </ul>                                                                                                                                                 |
| RS-485 interface:              | —                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Main features:                 | <ul style="list-style-type: none"> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• AGC - Automatic Gain Control</li> <li>• ICR - Movable InfraRed filter</li> <li>• BLC - configurable Back Light Compensation</li> <li>• Day/Night mode (color/b&amp;w/auto)</li> <li>• Configurable Privacy Zones</li> <li>• Motion Detection</li> <li>• RESET button</li> <li>• Intelligent Image Analysis : abandoned/missing object, intrusion, crossing the line (tripwire), face detection</li> <li>• Sharpness - sharper image outlines</li> </ul> |
| Power supply:                  | <ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 420 mA</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Power consumption:             | ≤ 6.5 W @ PoE (802.3af)<br>≤ 5 W @ 12 V DC                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Housing:                       | Compact, Aluminum                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| "Index of Protection":         | IP67                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Color:                         | Black                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Operation temp:                | -30 °C ... 60 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Supported languages:           | English, Bulgarian, Chinese, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Japanese, Korean, Lithuanian, Latvian, German, Norwegian, Polish, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Vietnamese, Italian                                                                                                                                                                                                                                                                                                     |
| Weight:                        | 0.41 kg                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Dimensions:                    | Ø 70 x 154 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Manufacturer / Brand:          | Hikvision                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| SAP Code:                      | 311301388                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Guarantee:                     | <b>3 years</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |

## PRESENTATION



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
 POL; 60-713 Poznań; Graniczna 10  
 e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60



Side view:



Mounting side view:



Bottom view (after remove the cover):



In the kit:



## OUR TESTS


Camera image at artificial illumination (about 30Lux):



Camera image at night conditions with internal built-in IR illuminator on:



Camera image at direct strong light opposite to camera:



## OUR OPINIONS



- The camera is equipped with a sensor with very high sensitivity, dedicated to work in poor light conditions.

## PACKAGE

|                                  |                    |
|----------------------------------|--------------------|
| Dimensions (L x W x H): 0x0x0 mm | Gross Weight: 0 kg |
|----------------------------------|--------------------|



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60