

Code: BCS-TIP3200IR-E-IV

## IP CAMERA **BCS-TIP3200IR-E-IV** - 1080p 2.8 mm

Net: **110.24 EUR** Gross: **110.24 EUR**

IP camera with efficient H.264 image compression algorithm for clear and smooth video streaming at maximal resolution of 1080p.

The range of IR illumination according to the manufacturer data, depends on outer conditions (visibility - air transparency, environment, wall colors ie. scene reflectance). PoE powering possibility, compatible with the 802.3af standard makes the device more universal and easier to install.



### SPECIFICATION

|                           |                                                                                    |
|---------------------------|------------------------------------------------------------------------------------|
| Standard:                 | TCP/IP                                                                             |
| Sensor:                   | 1/3 " Progressive Scan CMOS                                                        |
| Matrix size:              | 2.1 Mpx                                                                            |
| Scanning system:          | Progressive                                                                        |
| Resolution:               | 1920 x 1080 - 1080p<br>1280 x 960 - 1.3 Mpx<br>1280 x 720 - 720p<br>704 x 576 - D1 |
| Lens:                     | 2.8 mm                                                                             |
| View angle:               | 110 °                                                                              |
| Range of IR illumination: | 30 m                                                                               |
| S/N ratio:                | > 50 dB                                                                            |
| RS-485 interface:         | —                                                                                  |
| Memory card slot:         | —                                                                                  |
| Image compression method: | H.265 / H.264 / MJPEG                                                              |
| Alarm inputs / outputs:   | —                                                                                  |
| Audio:                    | —                                                                                  |
| Bitrate:                  | 32 ... 10240 kbps - H.264<br>12 ... 6400 kbps - H.265                              |
| Main stream frame rate:   | 25 fps @ 1080p                                                                     |
| Network interface:        | 10/100 Base-T (RJ-45)                                                              |

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

|                                |                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|--------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Network protocols:             | HTTP, HTTPS, TCP/IP, ARP, RTSP, RTP, UDP, SMTP, FTP, DHCP, DNS, DDNS, PPPoE, IPv4/IPv6, QoS, UPnP, NTP, Bonjour, IEEE 802.1x, Multicast, ICMP, IGMP, Lechange                                                                                                                                                                                                                                                                                          |
| WEB Server:                    | Built-in                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Max. number of on-line users:  | 20                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| ONVIF:                         | 2.42                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Mobile phones support:         | Port no.: 37777 or access by a cloud (P2P)<br>• Android: Free application <a href="#">DMSS</a><br>• iOS (iPhone): Free application <a href="#">DMSS</a>                                                                                                                                                                                                                                                                                                |
| Default admin user / password: | admin / admin                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Default IP address:            | 192.168.1.108                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Web browser access ports:      | 80, 37777                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| PC client access ports:        | 37777                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Mobile client access ports:    | 37777                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Port ONVIF:                    | 80                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| RTSP URL:                      | rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream<br>rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream                                                                                                                                                                                                                                                                        |
| Main features:                 | <ul style="list-style-type: none"> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• D-WDR - Wide Dynamic Range</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Motion Detection</li> <li>• Privacy zones</li> <li>• Configurable Privacy Zones</li> <li>• Mirror - Mirror image</li> </ul> |
| Power supply:                  | <ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 420 mA</li> </ul>                                                                                                                                                                                                                                                                                                                                                         |
| Power consumption:             | ≤ 5 W                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Housing:                       | Compact - Metal                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Color:                         | White                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| "Index of Protection":         | IP66                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Operation temp:                | -30 °C ... 60 °C                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Weight:                        | 0.384 kg                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Dimensions:                    | 70 x 75 x 155 mm                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Supported languages:           | English, Polish                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Manufacturer / Brand:          | BCS                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Guarantee:                     | <b>3 years</b>                                                                                                                                                                                                                                                                                                                                                                                                                                         |

## PRESENTATION



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60



Side view:



Camera mounting side view:



In the kit:



## OUR TESTS

Camera image at artificial illumination (about 30Lux):



Camera image at night conditions with internal built-in IR illuminator on:



Camera image at direct strong light opposite to camera:



## PACKAGE

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
 POL; 60-713 Poznań; Graniczna 10  
 e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

|                                  |                    |
|----------------------------------|--------------------|
| Dimensions (L x W x H): 0x0x0 mm | Gross Weight: 0 kg |
|----------------------------------|--------------------|

