

Code: GT-CI11C3-28VF

IP CAMERA **GT-CI11C3-28VF** - 720p 2.8 ... 12 mm GEMINI TECHNOLOGY

Net: **33.38 EUR** Gross: **33.38 EUR**

IP camera with efficient H.264 image compression algorithm for clear and smooth video streaming at maximal resolution of 720p.



SPECIFICATION

Standard:	TCP/IP
Sensor:	1/4 " OmniVision OV9712 CMOS
Digital Image Processor:	Hisilicon 3518E
Matrix size:	1.0 Mpx
Resolution:	1280 x 720 - 720p 720 x 576 - D1
Lens:	2.8 ... 12 mm
View angle:	• 65 ° ... 17 ° (manufacturer data) • 70 ° ... 24 ° (our tests result)
S/N ratio:	> 50 dB
Range of IR illumination:	30 m
IR illuminator power adjustment:	Automatic
Image compression method:	H.264 / MJPEG
Alarm inputs / outputs:	—
Bitrate:	16 ... 8000 kbps
Video output:	—
Main stream frame rate:	max. 25 fps - 1280 x 720
Network interface:	10/100 Base-T (RJ-45)
Network protocols:	TCP/IP, UDP, HTTP, DHCP, RTP/RTSP, DNS, DDNS, NTP, PPPOE, UPNP, SMTP
Audio:	—
Mobile phones support:	—
Default IP address:	192.168.1.188
Default admin user / password:	admin / (null)

Web browser access ports:	80, 554, 1935
PC client access ports:	5050, 5051, 5052
WEB Server:	Built-in
Max. number of on-line users:	10
Port ONVIF:	80
ONVIF:	2.21
RTSP URL:	rtsp://ip_address:554/ch01.264 - Main stream rtsp://ip_address:554/ch01_sub.264 - Sub stream
RS-485 interface:	—
Main features:	• ICR - Movable InfraRed filter • 3D-DNR - Digital Noise Reduction • WDR - Wide Dynamic Range • Possibility to change the resolution, quality and bit rate • Time mark and image description • Image rotation and mirror • Configurable: brightness, contrast, saturation • Sharpness - sharper image outlines • Day/Night mode - configurable • Possibility to add different privileges to the users • Privacy zones - max. 4
Power supply:	12 V DC / 390 mA
Power consumption:	≤ 4.7 W
Housing:	Compact, Metal
Color:	Graphite
"Index of Protection":	IP67
Operation temp:	-20 °C ... 60 °C
Weight:	0.520 kg
Dimensions:	211 x 117 x 77 mm
Supported languages:	English, Polish
Manufacturer / Brand:	GEMINI TECHNOLOGY
Guarantee:	2 years

PRESENTATION

Front view:



Side view:



On the bottom of the camera there are two lens adjustment knobs (zoom, focus):



Mounting dimensions:



In the kit:




Package:



OUR TESTS


Camera image at artificial illumination (about 30Lux):



Camera image at night conditions with internal built-in IR illuminator on:



Camera image at direct strong light opposite to camera:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60