

Code: LE-601946

SURFACE-MOUNTING HERMETIC DISTRIBUTION CABINET 36-MODULAR
LE-601946 RN65 LEGRAND
Net: **150.06 EUR** Gross: **150.06 EUR**

2-row 36-modular surface-mounting, hermetic distribution electric cabinet.



SPECIFICATION

Method of mounting:	Surface-mounted
Number of mounted modules:	18 x 2 rows
Spacing between TH 35 rails:	150 mm
Transparent door:	✓
Main features:	• Weatherproof cabinet • Fully reversible door and cabinet • Removable chassis and faceplates • The TH 35 rail with 2-position mounting for modular products • Can be fitted with perforated plates and solid faceplates for mounting non-modular products • Lockable door handle, sealable cover and faceplate • Rated voltage : 400 V AC, 50 / 60 Hz • Max. current : 90 A • Short-circuit current : 10 kA • Equipped with terminal blocks and modules blanking plates
Equipment:	• Terminal blocks 1 x (21 x 1.5 ... 16 mm² + 1 x 6 ... 25 mm²) 3 x (8 x 1.5 ... 16 mm²) • Module blanking plates : 2 x 5 pcs
Material:	Self-extinguishing
Color:	Light gray
"Index of Protection":	IP65
IK rating:	IK09

Compliance with standards:	PN-EN 60439-3, IEC 60695-2-11, IEC 62262
Operation temp:	-25 °C ... 40 °C
Weight:	4 kg
Dimensions:	448 x 432 x 161 mm
Manufacturer / Brand:	LEGRAND
Guarantee:	2 years

PRESENTATION

Front view:




Bottom view:



Internal view of the housing:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Mounting side view:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------