

Code: LE-419236

CIRCUIT BREAKER **LE-419236** THREE-PHASE 20 A C TYPE LEGRAND

Net: **14.65 EUR** Gross: **14.65 EUR**

Thermal-magnetic circuit breaker with C-type curve and 20A rated current. The LE-419236 circuit breaker is compatible to DIN TS-35 rail mounting system.
Circuit breakers with C-type breaking curve are designed to protection against short-circuits and overloads of the installation, where are used the devices with high inrush currents (motors, transformers).




SPECIFICATION


Device type:	Circuit Breaker, Three-phase
Rated current:	20 A
Number of poles:	3
Tripping curves:	C type
Breaking capacity:	6000 A
Rated voltage:	• 230 V AC / 50 Hz • 400 V AC / 50 Hz
Connectors type:	screw terminals
Housing:	Plastic, DIN, TS-35 rail mounting
Width in 17.5 mm modules:	3
Weight:	0.38 kg
Dimensions:	54 x 83 x 75 mm
Manufacturer / Brand:	LEGRAND
Guarantee:	2 years

PRESENTATION

Front view:



Mounting side view:



1. Tripping time (s)
2. The multiplier of the rated current

PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------