


Code: LE-403358

CIRCUIT BREAKER **LE-403358** ONE-PHASE 20 A B TYPE LEGRAND

Net: **3.81 EUR** Gross: **3.81 EUR**

Thermal-magnetic circuit breaker with B-type curve and 20A rated current. The LE-403358 circuit breaker is compatible to DIN TS-35 rail mounting system. Circuit breakers with B-type breaking curve are designed to protection against short-circuits and overloads of the lighting, control circuits and outlets.



SPECIFICATION

Device type:	Circuit Breaker, One-phase
Rated current:	20 A
Number of poles:	1
Tripping curves:	B type
Breaking capacity:	6000 A
Rated voltage:	• 230 V AC / 50 Hz • 400 V AC / 50 Hz
Connectors type:	screw terminals
Main features:	• Can be equipped with DX3 series signalling and remote tripping auxiliaries and motorised controls • No possibility of connecting the residual-current blocks • Provided space for a label with description • Can be connected with using the supply busbars fork-type or prong-type
Housing:	Plastic, DIN, TS-35 rail mounting
Width in 17.5 mm modules:	1
Weight:	0.108 kg
Dimensions:	83 x 74 x 17.5 mm
Manufacturer / Brand:	LEGRAND
Guarantee:	2 years


PRESENTATION

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60


Front view:



Side view:



Mounting side view:



1. Tripping time (s)
2. The multiplier of the rated current

PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------