

Code: PFM791

VIDEO SEPARATOR AHD, HD-CVI, HD-TVI, PAL **PFM791** DAHUA

Net: **18.45 EUR** Gross: **18.45 EUR**

The PFM791 is designed for additional protection in CCTV installations, securing the cameras and other devices from voltage differences and strokes between devices in the installation.



SPECIFICATION

Standard:	AHD, HD-CVI, HD-TVI, PAL
Device type:	Passive
Number of inputs:	1 - BNC socket
Number of outputs:	1 - BNC plug
Input impedance:	75 Ω
Output impedance:	75 Ω
Opto-isolation between input and output:	800 V - peak
Insertion loss:	0.5 dB
Bandwidth:	0 ... 65 MHz
Main features:	• Overvoltage protection : 4 kV 10/700 μs • Compliance with IEC61000-4-2, IEC61000-4-5 standards • MTBF (Mean Time Between Faults) > 20000 h • Length of the cables 2 x 13 cm
ESD protection:	600 V (contact discharge) 8000 V (air-gap discharge)
Power supply:	—
Housing type:	ABS
Operation temp:	-20 °C ... 55 °C
Permissible relative humidity:	0 % ... 95 %
Weight:	0.034 kg
Dimensions:	42 x 23 x 16 mm
Manufacturer / Brand:	DAHUA
Guarantee:	3 years

PRESENTATION

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Device connectors:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------