

Code: ASC2202C-D

ACCESS CONTROLLER **ASC2202C-D** DAHUA

Net: **583.67 EUR** Gross: **583.67 EUR**

The ASC2202C-D controller is intended to use in access control systems based on electrical control of door opening.




SPECIFICATION

Number of served transitions:	2 (two-way)
Support:	DAHUA
Number of supported readers:	4 pcs
Battery backup support:	max. 7 Ah
Input lines:	12 pcs
Output lines:	4 pcs - Relay
Communication:	• 5x RS-485, • Ethernet, • 4x Wiegand 34/26
Power supply:	100 ... 240 V AC
Main features:	• Support for 2 doors (12 inputs: 2x lock state, 2x door sensor, 2x exit button, 6x alarm line) • 100000 indexed users • History of 500000 events • 128 General Purpose Schedules • Function to prevent of multiple use of the same code/card to gain access (anti-passback) • Automatic sending of alarm messages to the SmartPSS system or after entering a code, card or fingerprint defined as door opening under duress • Door Left Open and Door Forced Open alarms • Tamper detection - opening the enclosure • Watchdog built-in • Remote programming from PC • Real time clock with battery backup • Metal housing - "Index of Protection" IP20, IK rating IK04

Operation temp:	-30 °C ... 60 °C
Permissible relative humidity:	max. 95 % (non-condensing)
Weight:	2.44 kg
Dimensions:	273 x 338 x 90 mm
Manufacturer / Brand:	DAHUA
Guarantee:	3 years


PRESENTATION

Internal view of the housing:





Connectors description:



Bottom view:



Power connector:



Side view:




Mounting side view:






Dimensions:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------