

Code: GRAFIX-L22D2-3X

PTZ OUTDOOR AHD, HD-CVI, HD-TVI, PAL CAMERA **GRAFIX-L22D2-3X**
VANDAL-PROOF - 1080p 2.8 ... 8 mm
Net: **142.00 EUR** Gross: **142.00 EUR**

Megapixel camera with 1/3" CMOS sensor and AHD / HD-CVI / HD-TVI / CVBS.

The AHD / HD-CVI / HD-TVI interface allows to transmission of analog video signal via coaxial cable in 1080p resolution. It enables the transmission of HD resolution images for even 500 m distance with keeping the low costs of the installation. During transmission there are no delays and is maintained the original, high quality image.

The change of the AHD / HD-CVI / HD-TVI / CVBS standard is done by changing the settings of the configuration switches.



SPECIFICATION

Standard:	AHD / HD-CVI / HD-TVI / CVBS
Sensor:	1/3 " CMOS
Matrix size:	2.1 Mpx
Resolution:	• 1920 x 1080 - 1080p @ AHD, HD-CVI, HD-TVI • 960 x 576 @ CVBS
Range of IR illumination:	20 m
IR illuminator power adjustment:	Automatic
Lens:	2.8 ... 8 mm
View angle:	81 ° ... 33 ° (manufacturer data) 101 ° ... 51 ° (our tests result)
Optical zoom:	x 3
Rotation speed depending on ZOOM level:	✓
Horizontal rotation range:	350 °
Vertical rotation range:	0 ° ... 90 °
Rotation speed (manual control):	0.1 °/s ... 80 °/s
PTZ control:	• Via interface RS-485 • The ability to control via coaxial cable from recorder
S/N ratio:	> 50 dB
Video output:	1 Vpp 75 Ω, AHD / HD-CVI / HD-TVI / CVBS
Number of presets:	220

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Route settings:	—
Horizontal scan:	—
Park action:	—
Main features:	• The ability to control via coaxial cable from recorder • ICR - Movable InfraRed filter • DNR - Digital Noise Reduction • AGC - Automatic Gain Control • BLC - Back Light Compensation • Auto White Balance
OSD menu:	✓
Vandal-proof:	✓
"Index of Protection":	IP66
Power supply:	12 V DC / 710 mA
Power consumption:	≤ 8.5 W
Housing:	Mini Speed Dome, Metal
Color:	White
Operation temp:	-10 °C ... 50 °C
Weight:	0.56 kg
Dimensions:	Ø 109 x 101 mm
Supported languages:	English, Greek, French, Spanish, Portuguese, Russian, Italian
Manufacturer / Brand:	Grafix
Guarantee:	2 years

PRESENTATION

Camera view after remove the Dome cover:



Mounting dimensions:



The change of the AHD / HD-CVI / HD-TVI / CVBS standard is done by changing the settings of the configuration switches:



Description the settings of configuration switches:



Connectors description:



In the kit:



OUR TESTS

AHD:

Camera image at artificial illumination (about 30Lux):



Camera image at night conditions with internal built-in IR illuminator on:



Camera image at direct strong light opposite to camera:



HD-CVI:

Camera image at artificial illumination (about 30Lux):



Camera image at night conditions with internal built-in IR illuminator on:



Camera image at direct strong light opposite to camera:



HD-TVI:

Camera image at artificial illumination (about 30Lux):



Camera image at night conditions with internal built-in IR illuminator on:



Camera image at direct strong light opposite to camera:



PACKAGE

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

