

Code: SD22204T-GN-W

IP SPEED DOME CAMERA OUTDOOR **SD22204T-GN-W** Wi-Fi, - 1080p 2.7 ... 11 mm DAHUA

Net: **259.07 EUR** Gross: **259.07 EUR**

IP camera equipped with very good high resolution sensor. Due to above it is perfect solution for surveillance systems requiring persons or vehicles recognition. The used Wi-Fi module allows to remote communication with camera for max. distance up to 50 m. For a few models of IP cameras working at $\geq 1920 \times 1080$ resolution we recommend to use of network with 1Gb/s bandwidth.



SPECIFICATION

Standard:	TCP/IP
Sensor:	1/2.7 " Progressive Scan Exmor CMOS
Matrix size:	2.1 Mpx
Resolution:	1920 x 1080 - 1080p 1280 x 720 - 720p
IR illuminator:	—
Scanning system:	Progressive
Lens:	2.7 ... 11 mm
View angle:	• 113 ° ... 30 ° (manufacturer data) • 113 ° ... 36 ° (our tests result)
Optical zoom:	x 4
Digital zoom:	x 16
Min. illumination:	0.05 Lux (color) 0.005 Lux (B/W)
S/N ratio:	> 50 dB (AGC off)
Preset rotation speed:	• 100 °/s (horizontal) • 60 °/s (vertical)
Rotation speed (manual control):	• 0.1 °/s ... 100 °/s (horizontal) • 0.1 °/s ... 60 °/s (vertical)
Horizontal rotation range:	355 °
Vertical rotation range:	0 ° ... 90 °
Protocols:	DH-SN
RS-485 interface:	—
Number of presets:	300

Horizontal scan:	✓
Route settings:	5
Image compression method:	H.264 / MJPEG
Audio:	—
Bitrate:	• 448 ... 8192 kbps - H.264 • 5120 ... 10240 kbps - MJPEG
Alarm inputs / outputs:	—
Main stream frame rate:	25 fps @ 1920 x 1080 Mpx
Network interface:	10/100 Base-T (RJ-45)
Network protocols:	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour
Memory card slot:	Micro SD memory cards up to 128GB support (possible local recording)
WEB Server:	Built-in, NVR compliance
Max. number of on-line users:	20
ONVIF:	2.42
Mobile phones support:	Port 37777 • Android: Free application DMSS • iOS (iPhone): Free application DMSS
Main features:	• Wi-Fi module - IEEE 802.11 b/g/n, Range : 50 m (open area) ; Antenna - SMA socket • ICR - Movable InfraRed filter • Motion Detection • 2D-DNR / 3D-DNR - Digital Noise Reduction • Configurable Privacy Zones • Sharpness - sharper image outlines • Mirror - Mirror image • AGC - Automatic Gain Control • Day/Night mode (color/b&w/auto) • IVS analysis : face detection, crossing the line (tripwire), intrusion, abandoned/missing object
Power supply:	12 V DC / 830 mA
Power consumption:	≤ 10 W
Housing:	Speed Dome, Metal
Color:	White
Supported languages:	English, Polish
Operation temp:	-30 °C ... 60 °C
"Index of Protection":	IP66
Weight:	0.566 kg
Dimensions:	Ø 123 x 89 mm
Manufacturer / Brand:	DAHUA
Guarantee:	3 years

PRESENTATION

Camera view after remove the Dome cover:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
 POL; 60-713 Poznań; Graniczna 10
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Memory card slot:



Camera mounting dimensions:



See how to initialize DAHUA cameras:

:
In the kit:



OUR TESTS

Camera image at artificial illumination (about 30Lux):



Camera image at direct strong light opposite to camera:



Camera image at night conditions with external IR illuminator on:



Camera image at night conditions, at different illumination values show below:

1 LUX:



0.1 LUX:



0.01 LUX:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

