Code: KIT-WA1001-300/1-B26

SURVEILLANCE KIT **KIT-WA1001-300/1-B26** Wi-Fi Cell Pro - 1080p 2.8 mm IMOU

Net: 159.30 EUR Gross: 159.30 EUR

The Cell Pro product series is a 100% wireless monitoring system that supports up to 6 cameras. Thanks to the battery power, you can place them anywhere without any wiring problems. In combination with the user friendly IMOU platform, the IMOU series devices allow anyone to create a simple and effective surveillance system.

Very easy operation via mobile devices (Android / iOS), allows the users for comfortable and remote operation, and also management of the camera. The used Wi-Fi module allows to remote communication with camera for max. distance up to 50 m.

The kit consists of an IP camera and a base station. The base station allows to connect an external disk with a capacity of up to 2TB in order to save recordings. Camera is according to IP65 Index of Protection norm.

Attention! The IMOU series devices do not have a WEB interface.



SPECIFICATION

Standard:	TCP/IP
Sensor:	1/2.7 " Progressive Scan CMOS
Matrix size:	2.1 Mpx
Resolution:	1920 x 1080 - 1080p
Lens:	2.8 mm
View angle:	110 °
Range of IR illumination:	10 m
Audio:	• Microphone built-in, • Speaker built-in, • Bi-directional audio streaming support
Image compression method:	H.265 / H.264
Main stream frame rate:	20 fps @ 1080p
Network protocols:	TCP, DHCP
ONVIF:	–
Network interface:	Wi-Fi - IEEE 802.11 b/g/n
Mobile phones support:	Access by a cloud (P2P) • Android: Free application IMOU • iOS (iPhone): Free application IMOU
Default admin user / password:	admin / - The administrator password should be set at the first start
Default IP address:	DHCP
Web browser access ports:	–
PC client access ports:	–
Mobile client access ports:	–

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Port ONVIF:	–
WEB Server:	–
RTSP URL:	–
Memory card slot:	–
Main features:	• Wi-Fi module - IEEE 802.11 b/g/n, Range : 50 m (open area), • micro USB socket • PIR detector - Built-in • Estimated battery operation time : to 3 months
Power supply:	• Li-Ion battery : 7.6 V / 2300 mAh • 5 V DC / 1 A (power adapter not included)
Power consumption:	≤ 3 W
"Index of Protection":	IP65
Operation temp:	-20 °C ... 45 °C
Weight:	0.23 kg
Dimensions:	77 x 77 x 72 mm (without bracket)
Supported languages:	–

Base Station:

LAN ports:	1 x 100 Mbps Fast Ethernet
Port USB:	1 x 2.0
Network interface:	Wi-Fi - IEEE 802.11 b/g/n
Supported hard drives:	USB max. 2 TB
Main features:	• Wi-Fi module, Range : 100 m (open area) • Internal antenna - 2x2 MIMO • RESET button • Sync button • Power socket
Power supply:	12 V DC / 2 A (power adapter included)
Power consumption:	≤ 6 W
Operation temp:	-10 °C ... 50 °C
Weight:	0.28 kg
Dimensions:	157 x 108 x 154 mm

General information:

Manufacturer / Brand:	DAHUA / IMOU
Guarantee:	2 years

PRESENTATION

Base Station:



Rear view:



Connectors:

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Camera:



Rear view:



micro USB connector:

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Battery view after open the cover:



In the kit:



OUR OPINIONS

- Very small camera dimensions.

PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60