

Code: DH-IPC-HUM8230P-L1

SENSOR UNIT MODULE **DH-IPC-HUM8230P-L1** TO THE DH-IPC-HUM8230P-E1 MODULE - 1080p DAHUA

Net: **107.62 EUR** Gross: **107.62 EUR**

The DH-IPC-HUM8230P-L1 PINHOLE camera module is designed to work with the DH-IPC-HUM8230P-E1 main unit module. The device is only used to generate an image processed later in the main unit. It is not possible to use the camera for autonomous operation - even through the USB port through which the camera connects to the main module.

Attention! The device requires the purchase of the main unit module (available separately).



SPECIFICATION

Standard:	TCP/IP
Sensor:	1/2.8 " Progressive Scan CMOS
Matrix size:	2.1 Mpx
Resolution:	1920 x 1080 - 1080p
Lens:	2.8 mm (pinhole)
View angle:	• 104 ° (manufacturer data) • 100 ° (our tests result)
Min. illumination:	0.07 Lux (color) 0.007 Lux (B/W)
S/N ratio:	> 50 dB
Audio:	—
RS-485 interface:	—
RS-232 interface:	—
Main stream frame rate:	25 fps @ 1920 x 1080
Memory card slot:	—
Power supply:	From main unit module
Length of the cable:	8 m
Operation temp:	-30 °C ... 60 °C
Weight:	0.22 kg
Dimensions:	Ø 27 x 50 mm
Manufacturer / Brand:	DAHUA
Guarantee:	3 years

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

PRESENTATION



Front view:



Side view:



Camera connector:



In the kit:




OUR TESTS

Camera image at artificial illumination (about 30Lux):



Camera image at direct strong light opposite to camera:



Camera image at night conditions, at different illumination values show below:

10 LUX:



1 LUX:



0.1 LUX:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

