

Code: AT-UPS1200-LED

UPS **AT-UPS1200-LED** 1200 VA EAST

Net: **110.33 EUR** Gross: **110.33 EUR**

The AT-UPS1200-LED UPS has been equipped with a number of advanced technologies ensuring active monitoring of the power supply network.
The device works with power supply adapters having Active Power Factor Correction (APFC).



SPECIFICATION

Nominal power:	720 W
Apparent Power:	1200 VA
Input voltage:	165 V ... 275 V AC
Input frequency:	50 / 60 Hz (auto detection)
Output voltage:	230 V AC $\pm$ 10 % (Approximated Sine Wave)
Output frequency:	50 / 60 Hz $\pm$ 1 %
Transfer time:	2 ... 7 ms (typical), max. 10 ms
Charging time (recover to 90% capacity):	8 hours
Battery:	2 pcs - 12V/7Ah
Estimated battery operation time:	• 57 minutes @ 100 W, • 14 minutes @ 300 W, • 8 minutes @ 500 W
Number of outputs:	3 pcs CEE 7/3 (Schuko)
Protections:	• Glass Fuse • Overvoltage • Overload protection • Overcharge protection • Telephone line filter
Operation state indication:	• LED diodes, • Sound signaling

Main features:	• Auto restart while AC is recovering • Automatic Voltage Regulator (AVR) • Compatible with power generators • Remote management - UPSmart application included • Built-in EMI, RFI filter • Configurable alarm
Application:	• Surveillance Systems • data storage centers • network, servers, workstations • Industrial Equipment
Housing type:	Tower
Operation temp. / Relative humidity:	0 °C ... 40 °C / 20 ... 90 %
Weight:	10.17 kg
Dimensions:	330 x 227 x 125 mm
Manufacturer / Brand:	EAST
Guarantee:	2 years

PRESENTATION

Front view:



Rear view:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
 POL; 60-713 Poznań; Graniczna 10
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------