

Code: S561D-G

VIDEO DOORPHONE **S561D-G** VIDOS

Net: **203.37 EUR** Gross: **203.37 EUR**

Video Doorphone is mounted in a flush-mounted housing. Surface mounting is possible with the D561B cover.
The S561D-G is designed to cooperation with video doorphones and panels working in analog VIDOS system.



SPECIFICATION

Compatibility:	VIDOS Analog Video Doorphones
Sensor:	1/3 " 600 TVL
View angle:	87 °
IR illuminator:	✓
LED illuminator:	—
proximity reader built-in:	—
Fingerprint reader built-in:	—
Built-in keypad:	✓
The number of subscribers served:	1
Video output:	compatible with VIDOS analog video door-phone system
Main features:	• Adjustment of the opening time of the electric strike: 1s ... 99s • Electric strikes and electromagnetic locks support • Output for the additional lock release button • Timer output specifying temporary access • Vandal-proof front panel • Illuminated buttons and signboard for the surname
Power supply:	12 V DC ... 15 V DC
Power consumption:	≤ 1.5 W (operation)
Housing:	Acid-proof steel - powder painting / Plastic, Waterproof
Color:	Graphite

"Index of Protection":	IP65
Operation temp:	-20 °C ... 55 °C
Weight:	0.94 kg
Dimensions:	250 x 120 x 50 mm
Manufacturer / Brand:	VIDOS
Guarantee:	2 years

PRESENTATION

Front panel:



Side view:





Rear view:



Internal view of the housing:



Connectors:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

